



TIRE SIZE	PR	TT/TL	LOAD / SPEED INDEX	RIMS		INFLATED DIMENSIONS (NO LOAD)		INFLATED DIMENSIONS(W/LOAD)		
				RECOMMENDED (INCH)	PERMITTED (INCH)	OUTER DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOADED RADIUS (MM)	DYNAMIC ROLLING CIRCUMFERENCE (MM)	
9.00-16	12	TL	125/A6	6.00F	5.50F , 6LB	881	247	394	2675	
9.00-16	12	TT	125/A6	6.00F	5.50F , 6LB	881	247	394	2675	
9.00-16	14	TT	128/A6	6.00F	5.50F , 6LB	881	247	394	2675	
INFLATION PRESSURE (PSI/BAR)	LOAD CAPACITY PER TIRE, KG									
	SPEED (KM/H)									
	10	20	25	30	40					
49 / 3.4	1895	1675	1570	1470	1320					
52 / 3.6	1940	1710	1605	1500	1350					
58 / 4.0	2130	1880	1765	1650	1485					
57 / 3.9	2020	1785	1675	1565	1410					
61 / 4.2	2115	1865	1750	1640	1475					
67 / 4.6	2320	2050	1925	1800	1620					
67 / 4.6	2160	1910	1795	1675	1510					
72 / 5.0	2365	2090	1960	1833	1650					
80 / 5.5	2515	2225	2085	1950	1755					
9.00-16	16	TT	131/A6	9.00	-	845	290	2600	382	
11.5/80-15.3	16	TL	141 / A8	9.00	-	845	290	2600	382	