

IEC60598_2_3M ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
<b>ATTACHMENT TO TEST REPORT B5-3/244/B/23</b> <b>IEC 60598-2-3</b> <b>EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES</b> Luminaires Part 2: Particular requirements Section 3: Luminaires for road and street lighting			
<b>Differences according to</b> .....		EN 60598-2-3:2003 + A1:2011 used in conjunction with EN IEC 60598-1:2021 + A11:2022	
<b>TRF template used</b> .....		IECEE OD-2020-F2:2020, Ed. 1.1	
<b>Attachment Form No.</b> .....		EU_GD_IEC60598_2_3M	
<b>Attachment Originator</b> .....		UL(Demko)	
<b>Master Attachment</b> .....		2022-05-24	
<b>Copyright © 2022 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.</b>			
	<b>CENELEC COMMON MODIFICATIONS (EN)</b>		P
<b>3.5 (3)</b>	<b>MARKING</b>		P
3.5 (3.2.12)	Note 4 deleted		N/A
<b>3.6 (4)</b>	<b>CONSTRUCTION</b>		N/A
4.7 (4.11.6)	Electro-mechanical contact systems: electric strength test at 1 500 V		N/A
<b>3.10 (5)</b>	<b>EXTERNAL AND INTERNAL WIRING</b>		N/A
3.10 (5.2.2)	Cables equal to EN 50525 (all parts)		N/A
	Paragraph 2 deleted		N/A
	Replace table 5.1 – Supply cord		N/A
<b>3.12 (12)</b>	<b>ENDURANCE TESTS AND THERMAL TESTS</b>		P
3.12 (12.4.2c)	Thermal test (normal operation) see footnote c to table 12.2 relating to unsleeved fixed wiring		P
<b>ZB</b>	<b>ANNEX ZB, SPECIAL NATIONAL CONDITIONS (EN)</b>		N/A
(3.3)	DK: power supply cords of class I luminaires with label		N/A
(5.2.1)	CY, DK, FI, UK: type of plug		N/A

IEC60598_2_3M ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
(5.2.18)	DK: socket-outlets		N/A
<b>ZC</b>	<b>ANNEX ZC, NATIONAL DEVIATIONS (EN)</b>		<b>N/A</b>
(4 & 5)	FR: Shuttered socket-outlets 10/16A		N/A
	FR: Safety requirements for high buildings <i>(Decree of 30 December 2011 on safety regulations for the construction of high-rise buildings and their protection against fire and panic risks; Section VIII; Article GH 48, Lighting)</i>  Glow-wire test for outer parts of luminaires:		N/A
	- 850°C for luminaires in stairways and horizontal travel paths		N/A
	- 650°C for indoor luminaires		N/A
	UK: Requirements according to United Kingdom Building Regulation		N/A