

Specificații tehnice F 4.1

[Acest tabel va fi completat de către ofertant în coloanele 3, 4, 5, 7, iar de către autoritatea contractantă – în coloanele 1, 2, 6, 8]

| |
|---------------------------------------------------------------------------------|
| Numărul procedurii de achiziție _____ 21042273 _____ din _____ 26.07.2021 _____ |
| Denumirea procedurii de achiziție: ocds-b3wdp1-MD-1627019947994 |

| Cod CPV | Denumirea bunurilor | Modelul articolului | Țara de origine | Producătorul | Specificarea tehnică deplină solicitată de către autoritatea contractantă | Specificarea tehnică deplină propusă de către ofertant | Standarde de referință |
|------------|-------------------------|------------------------|-----------------|------------------|---------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| | Bunuri | | | | | | |
| 33100000-1 | Lotu 1 1) Plug screw | NPQH-BK-G18-P10 FITING | Bulgaria | Festo Production | | Solid metal push-in fitting made of chemically nickel-plated brass. High corrosion resistance CRC 3 and chemical resistance. For pneumatic applications with a temperature range up to 150 °C and a pressure range up to 20 bar. Tubing outside | |

| | | | | | | | |
|------------|---------------------------------|---------------------------------------|----------|------------------|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| 33100000-1 | Lotu 1 2) Plug screw | NPQH-BK-M5-P10 | Bulgaria | Festo Production | | Solid metal push-in fitting made of chemically nickel-plated brass. High corrosion resistance CRC 3 and chemical resistance. For pneumatic applications with a temperature range up to 150 °C and a pressure range up to 20 bar. Tubing outside | |
| 33100000-1 | Lotu 1 3) Regulator | KOAKSIALINII KLAPAN DN25 FKM | Germany | Gruner | | Tastați față-verso DN 25 Kvs [m ³ / h] 10,1 Conexiune Filet intern Rp 1 " Cilindru cooperant Gruner tip 225 cilindri, Gruner tip 227 cilindri, Gruner tip 341 cilindri Metoda de instalare. Supapa este livrată cu un servomotor | |
| 33100000-1 | Lotu 1 4) Pressure regulator | MS9-LR-G-D7-AG-BAR-AS CLAPAN REG T | Bulgaria | Festo Production | | SDE5-D10-C3-...-P-M8 with 3-pin plug M8x1, window comparator, 1 switching output | |

| | | | | | | | |
|------------|-----------------------------|--------------------------------------------------|----------|------------------|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| | | | | | | PNP, N/C contact | |
| 33100000-1 | Lotu 1 5) CPU | 6ES7212-1BE40-0XBO CPU SIEMENS | Germany | SIEMENS | | <p>Conexiuni dispozitiv software: 4 redundante / 4 max;</p> <p>Conexiuni HMI: 12 redundante / 18 max; Conexiuni S7: 8 backup / 14 max;</p> <p>Conexiuni de utilizator deschise: 8 redundante / 14 Max .; conexiuni de rețea: 2 redundante / 30 max; conexiuni OPC UA: 0 redundant / 10 max; conexiuni totale: 34 redundante / 64 max.</p> | |
| 33100000-1 | Lotu 1 6) Silencer | AMTE-M-LH-M5 GLUSITELI | Bulgaria | Festo Production | | <ul style="list-style-type: none"> • Suitable for reducing noise at the exhaust ports of pneumatic systems | |
| 33100000-1 | Lotu 1 7) Valve terminal | CPV 10 PNEBMOOSTR AV 10P-10-2C-IC-R-Y-CC+P | Bulgaria | Festo Production | | <p>With valve terminals CPV, up to 4 pressure zones can be created. The diagram shows an example of the configuration and connection of four</p> | |

| | | | | | | | |
|------------|-------------------------------|----------------------------------------------|----------|------------------|--|-------------------------------------------------------------------------------------------------------------------------|--|
| | | | | | | pressure zones with external pilot air supply and the use of a valve ...K with integrated separation of ducts 1 and 11. | |
| 33100000-1 | Lotu 1 8) connecting cable | Nebv-Z3WA2L-R-E-2.5-N-LE2-S1STEKER S CABELEM | Bulgaria | Festo Production | | Connecting cable Pre-assembled at one end For connecting valves Cable lengths 0.5 ... 30 m | |
| 33100000-1 | Lotu 1 9) Silencer | U-1/4-B GLUSITELI | Bulgaria | Festo Production | | For noise reduction and avoiding contamination at the exhaust ports of pneumatic components • Compact design | |
| | TOTAL | | | | | | |

Semnat : Alexandru Tverdohleb În calitate de: director IM „ATK Systems” SRL

Ofertantul: _____ IM „ATK Systems” SRL _____ Adresa: mun. Chisinau str. Melestiu 16\2 71 _____