



rompetrol

KazMunayGas
Group
Member

Statement of Compliance

No:69096 ;Date: 21/12/2025 Time:23:11:45

Manufacturer's name: ROMPETROL RAFINARE S.A.

Manufacturer's address: Navodari, 215 Navodari Boulevard, Administrative Building, Constanta County

Registration No. with the Register of Commerce: J1991000534130

Unique registration Code: 1860712

Hereby duly assure, guarantee, and state that:

Name of product: Gasoil EN 590 - 10PPM

of (batch/lot/tank): M92/20.12.2025.14:00-LPP107951 FOR BARGE TMS ALNIKA

Transported with: ALNIKA

Delivered from: Petromidia Secondary place of business (Navodari City, 1-283 Navodari Boulevard, Constanta County)

Quantity: Kg

Beneficiary: IM ROMPETROL MOLDOVA, destinatia REPUBLICA MOLDOVA

Drawn according to standard: ASTM D 4057-2022*

In compliance with:

Specification/Standard/Contract no.: SS-2.6.6 T **Title:** Euro 5 Diesel **Edition/Revision/Date of issuance:** - / 10 / 01/09/2023/

above-described product does not threaten life, health, labor safety and does not have a negative impact upon the environment, are maintaining characteristics if respect the requirements of :

Safety data sheet No. FDS 2.6 T **Title:** **Edition/Revision/Date of issuance:** / 11 / 20/11/2025

Derogation: It's not necessary

Validity period: 3 Months **Warranty period:** 1 month from delivery date

Additional information:

The tests performed are listed in the test report no.: 70892 of date: 21/12/2025 11:10:27PM, in attach.
Certificat RAR nr.2584/valabil pana la 18.08.2026

- Rompetrol Rafinare S.A. has the Quality-Environment-Health and Occupational Health and Safety Management Integrated System certified by DNV, according to standards: ISO 9001, ISO 14001, ISO 45001, ISO 50001.
- Rompetrol Refining has registered/ notified the product, according with the Regulation 1907/2006, REACH.
- Rompetrol Rafinare S.A. has empowered Rompetrol Quality Control SRL by a Contract of Representation Mandate to issue on its behalf the Conformity Statement.
- Material testing laboratories owned by Rompetrol Quality Control SRL are accredited by RENAR(Romanian Accreditation

For and on behalf of Rompetrol Rafinare SA

Rompetrol Quality Control SRL -

Head of Oil Products Laboratory

 ROMPETROL

Elena Lucia Pop

ROMPETROL RAFINARE S.A.



Tel: + (40) 241 506 158; 241 506 700,

Fax: + (40) 241 506 916; 241 506 929

www.rompetrol-rafinare.ro

www.rompetrol.com

office.rafinare@rompetrol.com

Rev.24/2025

ROMPETROL RAFINARE SA

215 Navodari Blvd. Administrative Building, 905700, Navodari, Constanta, ROMANIA
fax: + (40) 241 506 930 | phone: + (40) 241 506 207 | email: office.rafinare@rompetrol.com

www.rompetrol.com

page 1 of 1


Testing report no:70892; date:21/12/2025 23:10:22

Customer: ROMPETROL RAFINARE SA
Sample: Gasoil EN 590 - 10PPM
Receiving date: 21/12/2025 22:30:00
Completion date: 21/12/2025
Sampling method: ASTM D 4057-2022*
Tanks: M92/20.12.2025.14:00-LPP107951 FOR BARGE TMS ALNIKA
Sampled by: RQC-UTi
Contract/Order: Contract RR nr. 5/ 07.01.2019/ PI- rev.7 RRC.P&E
Ship: TMS ALNIKA/LPP108252
Sample tested: 4 L
Customer address: Navodari,B-dul Navodari nr. 215, Pavilion Administrativ,Constanta

No.	Property	Test Method	UM	Required value	Determined value	Uncertainty ³⁾
1	Cetane Number	EN ISO 5165:20		min. 51.0	51,3	-
2	Cetane Index	EN ISO 4264:2018		min. 46.0	50,9	-
3	Density At 15°C	EN ISO 12185:2024	kg/m³	min. 815 max. 845	841,8	-
4	Polycyclic Aromatic Hydrocarbons	EN 12916:2019+A1:2024	% (m/m)	max. 8.0	4,9	-
5	Sulfur Content	EN ISO 20846:20	mg/kg	max. 10.0	8,7	-
6	Flash Point, Pm	EN ISO 2719:2016,EN ISO 2719:2016/A1:2021:21	°C	min. >55	59,0	-
7	Carbon Residue(In 10% Distillation Residue)	EN ISO 10370:15	% (m/m)	max. 0.30	<0.10	-
8	Ash Content	EN ISO 6245:03	% (m/m)	max. 0.010	0,001	-
9	Water Content	SR EN ISO 12937:01, SR EN ISO 12937:01/C91:14	% (m/m)	max 0.020	0,010	-
10	Total Contamination	EN 12662:2024	mg/kg	max. 24	<12	-
11	Corrosion, Copper Strip (3H At 50°C)	EN ISO 2160:03	evaluation	clasa 1	1b	-
12	Fatty Acid-Methyl Ester (Fame) Content	EN 14078:14	% (v/v)	max. 7	<0.05	-
13	Oxidation Stability	EN ISO 12205:1999	g/m³	max. 25	6,0	-
14	Lubricity, Wear Scar Diameter (Wsd) At 60°C	EN ISO 12156-1:2023	µm	max. 460	380	-
15	Viscosity At 40°C	EN ISO 3104:2023	mm²/s	min. 2.000 max. 4.500	2,906	-
16	%(V/V) Recovered At 250°C	EN ISO 3405:19	% (v/v)	<65	32,1	-
17	%(V/V) Recovered At 350°C	EN ISO 3405:19	% (v/v)	min. 85	92,6	-
18	95 %(V/V) Recovered At	EN ISO 3405:19	°C	max. 360	358,9	-
19	Cold Filter Plugging Point (Cfpp): Winter Grade, Class E	EN 116:16	°C	max. -15	-19	-
20	Manganese(S)	SR EN 16576:15*	mg/l	max. 2.0	<0.5	-

Amendment: not applicable

Remarks: Fatty Acid Methyl Ester (EMAG) Content - Test Performed in RQC – Environmental Laboratory;



1. The Rompetrol Quality Control SRL laboratory is accredited by RENAR for testing activity in compliance with SR EN ISO/CEI 17025:2018 as specified in the accreditation certificate no. LI 333. The tests covered by the accreditation are available at www.renar.ro
2. "" The marked tests are not covered by the RENAR accreditation.
3. Expanded uncertainty of 95% confidence level with coverage factor k=2.
4. The testing report cannot be partially reproduced without explicit written approval of the testing laboratory.
5. The testing results refer to the tested sample and not the entire lot.
6. The observations contained in this report are not covered by the Renar accreditation

ROMPETROL QUALITY CONTROL SRL

215 Navodari Blvd., 2nd floor, room 220, Navodari - Constanta, Postal Code 905700 ROMANIA
phone: + (40) 241 50 6700 | fax: +(40) 241 506 916 , email: Comercial.RQC@rompetrol.com

www.rqc.ro

cod: F. LPP.02-PG.07

ed.5/rev.4/04.2023

page 1 of 1