



# XTG 75W140 LS

## DESCRIPTION

Fully synthetic oil with a high viscosity index, formulated to lubricate mechanical transmissions and differentials submitted to difficult operating conditions (heavy loads, high speed and temperature).

## APPLICATION

**Bardahl XTG 75w140 LS** is particularly suitable for heavy loaded hypoid differentials, with «Limited Slip and Auto-Locking». Provides an excellent stability at different temperatures.

## SPECIFICATIONS

This product offers the following performance level:

API	GL5
-----	-----

## PROPERTIES

- ✓ Offers a good resistance to high temperature,
- ✓ Provides very good extreme pressure (EP) properties,
- ✓ Has a low pour point,
- ✓ Provides a high resistance against corrosion and oxidation,
- ✓ Provides anti-wear and antifoam properties,
- ✓ Has a limited slip.



## TECHNICAL DATA SHEET V102020

### TECHNICAL DATA

Density at 20°C	Kg/l	0,840
Viscosity at 40°C	mm <sup>2</sup> /S	180
Viscosity at 100°C	mm <sup>2</sup> /s	25
Viscosity index		165
Flash point COC, °C	°C	>200
Pour point, °C	°C	<-30

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

### RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

### REFERENCES & AVAILABILITIES

33061	12 x 1L
33063	3 x 5L
33064	60 L
33067	205L



**NOTHING WILL STOP YOU**

SADAPS BARDAHL ADDITIVES & LUBRICANTS  
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2  
T: (+32) (0) 69 59 03 60

[www.bardahl.fr](http://www.bardahl.fr)  
[www.bardahlois.com](http://www.bardahlois.com)