



DATASHEET

TRASSIR MiniNVR AnyIP 4/9/16



TRASSIR MiniNVR – network video recorder for building CCTV systems.
Up to 16 channels are record, playback and display.



Rear panel:

- | | |
|-----------------------|-----------------------|
| 1. 12V DC power input | 5. HDMI interface |
| 2. Network interface | 6. VGA interface |
| 3. USB 3.0 interface | 7. Audio input/output |
| 4. USB 2.0 interfaces | 8. Power button |

Specification:

Operation system	TRASSIR OS (based on Linux)
IP video input ¹	4/9/16-ch (any models ²)
Resolution of cameras	Up to 5MP (depending on camera model ²)
Bitrate	Up to 256Mb/s
Video compression	H.264, MPEG4 or MJPEG (depending on camera model ²)
Maximum internal storage	Up to 2xHDD (2.5"/3.5")
Network interfaces	1 Ethernet 10/100/1000 Mb/s
USB interfaces	2xUSB 2.0 and 1xUSB 3.0
Video output ³	1 VGA and 1 HDMI
Audio inputs/outputs	In: 1 jack 3.5mm ⁴ Out: 1 jack 3.5mm
Dimensions, mm	440 x 293.6 x 44.5
Power supply	DC 12V
Power consumption	Up to 30W (without HDD)
Working temperature	10...30°C
Package size, mm	490 x 400 x 130
Gross, kg	5.5 (without HDD)

¹ Depending on NVR model.
² You can find list of per-integrated cameras on www.trassir.com
³ The NVR can be connected to two independent displays (VGA + HDMI).
⁴ NVR works only with the active microphone.

Basic equipment:

- Network Video Recorder 1 pcs
- Power Supply 12V (5A) 1 pcs
- Power cord 1 pcs
- Mouse 1 pcs
- Set of fixing elements 1 pcs
- Datasheet for server 1 pcs

Warranty service:

- Specify the information about the warranty on www.trassir.com.

DATE OF PRODUCTION

KEY NUMBER

SERIAL NUMBER