



HF-YZW60SWII

UV Sterilization Lamp

HF-YZW60SWII

UV Sterilization Truck Used for air sterilization in all sorts of sanitary medical units or departments, scientific research units, pharmaceutical and food process industry, etc.



Household disinfection

160 degree comprehensive sterilization.

160 degree adjustable lamp, wide range of disinfection

When the working space design is changeable and the space angle is inconsistent, the 160 degree adjustable lamp holder makes the disinfection coverage larger.



Product Parameters

Structure features

1. Double tubes structure, which can also be used independently.
2. Angle of lamp arm can be adjusted. In order to protect tubes from dust and damage, please leave protection door shut while it doesn't work.
3. Sterilization timing range: 30-180 minutes for sterilization. Once sterilization is finished, buzzer rings, circuit breaks down and pipe turns off.
4. Do circuit test before use to make sure if there is no leakage prior to application.

Main technical data

UV Wavelength: 253.7nm
Power Source: 220V/50Hz or 110V/60Hz
Adjustment angle of lamp arm: 0-160° (II model)
Timing range: 30-180 minutes
Illumination: 100um/cm²
Light: Quartz light tube 30W×2
Type: Remote control type, electric timing (double-tube)
Material: Steel material, plastic-spray

Optional human sensor: It can sense people within 5-8 meters of the sterilizer and stop the sterilization by itself.