









## Concerning (1):

- -approval granted
- approval extended
- -approval refused
- -approval withdrawn
- -production definitely discontinued

of a type of tyre for motor vehicles pursuant to Regulation number 30.

**RDW** 

**Approval number:** E4-30R-0238801 **Extension number: 01** 

: Continental Reifen Deutschland GmbH 1. Manufacturer's name and address

> Vahrenwalder Str. 9 30165 Hannover

Germany

Tyre type designation (2) 2.

2.1 Brand-name(s)/trademark(s) : CONTINENTAL

**BARUM** 

2.2 Trade description(s)/Commercial name(s) : CONTINENTAL, CONTIPREMIUMCONTACT 2

BARUM, BRAVURIS 5HM

3. If applicable, name and address of the

> manufacturer's representative : not applicable

Summarized description 4.

4.1 Tyre size designation : 195/65 R 15

(1) 4.2 Category of use : normal /snow / special use / temporary use

(1) 4.3 Structure : diagonal/bias belted/ radial/ run flat tyre

4.4 Speed category symbol : T

: 91 4.5 Load-capacity index

Technical Service and, where : Continental Reifen Deutschland GmbH applicable, test laboratory approved Vahrenwalder Str. 9

for purposes of approval or of verification 30165 Hannover

of conformity Germany

6. Date of report issued by that service : 27.07.2015, 26.05.2015 7. : 4460018, 4460026

8. Reason(s) of extension (if applicable) : Tyre Type Designation added

9. Any remarks

Number of report issued by that service



Approval number: E4-30R-0238801 Extension number: 01

10. Place : Zoetermeer


11. Date : 13-MAR-2018

12. Signature :


T. H. K. Spatz

- 13. The list of documents in the approval file which are deposited at the administrative service having delivered the approval and which can be obtained upon request.
  - Application form relating to ECE approval for a pneumatic tyre pursuant to Regulation number 30.
  - The drawing of the tyre's sidewalls, tread and dimensioned cross-section.
  - The test report as mentioned in item 7.
  - (1) Strike out what does not apply.
  - (2) A list of Brand name(s)/trademark(s) or Trade description(s)/ Commercial name(s) may be annexed to this communication

Serial Side (SS)
Off Serial Side (OSS)



The drawing may contain more position numbers than required by UNECE type approval.



**RDW** 

Company proprietary
Unauthorized duplication prohibited

		min				min			Design Dimensions	(calculated / <del>Annex 5)</del>		
Position	Description	1	Tire Side	TSL Content	Position		height	Tire Side	TSL Content	Overall diameter	A (mm)	635
1/194	Brand Name (Trade mark)		both	BARUM	116	"Inside"/"Outside" marking		SS	OUTSIDE	Section Width	B (mm)	201
2 or 3	Trade description		both	BRAVURIS 5HM	117	"Inside"/"Outside" marking		oss	INSIDE	Measuring rim	C (Rim Code)	6.0Jx15
.	(Commercial name)				134	Date of manufacturing	>4 mm	SS	[WWYY]	1		
4	Tire size designation	>6 (or 9	both	195/65 R 15	179	Alpine Symbol		both	-	1		•
6	Structure	>4 mm	both	RADIAL	184	Runflat Symbol		both	-	1		•
7 or 8	Service description (LI / SSY)	>6 mm	both	91 T	191	"FRT" marking	>4 mm	both	-	Approval No.	E4-30R-0238801	
9 or 10	Additional service description	>6 mm	both	1	135	UN approval mark	>12 mm	both	E4	Extension:	01	
13 or 14	"M+S" (or "M.S" or "M&S")		both	7	137	UN R30/R54/R75 approval no.		both	0238801	Name:	D. Schoenfelder	
15	Tube type / Tubeless		both	TUBELESS			•	•		Drawing No.:	1	
17	Extra Load or Reinforced	>6 mm	both	7	If Pos 78	Tread depth			-	Date:	3/6/18 5:38 PM	
19	PSI index	>2 mm	both	7	is used	Surface void/ fill ratio			-	Pattern	4736.01	
27	Regroovability		both	7	If Pos 79	Number of circumferential ribs			-	4	-	
32	"TEMPORARY USE ONLY"	>12,7 mm	both	7	is used	Number of block-like elements -			-	<u> </u>		
34	"INFLATE TO 420 kPa (60 PSI)"	>12,7 mm	both	7	1	Depth of lateral grooves/sipes >=50%of main groove			- ([]			
73	Test inflation Pressure in KPA	>2 mm	both	7	1	depth?				DE MAINTIENDRAI	49 4 . 1/	
78	Mark for special use tires	>4 mm	both	7					<u> </u>	<u> </u>	'inentai'	
79	"TRACTION"	>4mm	both	1	1				\	* MAINTIENDRAI		_

