

Safety Data Sheet

according to Regulation 830/2015/EU (Annex II)

TEST CLEANER SPRAY



GHS02:Flammable



GHS07: Irritant



GHS09: Environmental hazards

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name: TEST CLEANER SPRAY

Product form: Mixture containing

Name:	N. CAS:
HYDROCARBONS, C3-4	68476-40-4
HEPTANE (AND ISOMERS)	-
ETHYL ACETATE	141-78-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Detergent Cleaner for metal surface (aerosol).

1.3 Details of the supplier of the safety data sheet

GCE GROUP

GCE Holding AB
Källvattengatan 9
Box 21044
200 21 Malmö SWEDEN

Tel: +46(0)40-38 83 45
Fax: +46(0)40-38 83 33
mujelli@gcegroup.com
www.gcegroup.com

1.4. Emergency telephone number

National Poisons Information Service (NPIS) – UK
dial 111 (England, Wales and Scotland)
dial 01 809 2166 (Rep. of Ireland)
Contact your local GP or pharmacist during normal hours (N. Ireland)
www.npis.org/telephone.html



2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] and its amendments.

- Danger, Flam. Aerosol 1, Extremely flammable aerosol.
- Warning, Skin Irrit. 2, Causes skin irritation..
- Warning, Eye Irrit. 2, Causes serious eye irritation.
- Warning, STOT SE 3, May cause drowsiness or dizziness.
- Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects.

No other hazards

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms (CLP):



GHS02



GHS07



GHS09

Signal Word (CLP) : Warning

Hazard component: Heptane (and isomers)

Hazard statements (CLP) :

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing spray.
- P271 Use only outdoors or in a well-ventilated area.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
- P501 Dispose of container in accordance with national regulation.

Special Provisions:

The manufacturer cannot be held responsible in case of damages caused by incorrect use of the product.

Special provisions according to Annex XVII of REACH and subsequent amendments:

Restricted to professional users.

2.3. Other hazards

- vPvB Substances: None
- PBT Substances: None
- Other Hazards: No other hazards

3. COMPOSITION/INFORMATION ON INGREDIENTS









3.1. Substances

Not Applicable

3.2. Mixtures

Classification according to Regulation No. 1272/2008 and its amendments:

Name: HYDROCARBONS, C3-4		REACH No: 01-2119486557-22
		CAS No: 68476-40-4
Concentration: >= 40% - < 50%		EC No: 270-681-9
Classification: substance with a Community workplace exposure limit.		Index No: 649-199-00-1
Press. Gas H280	Flam. Gas 1 H220	
Note K* The substance contains < 0,1 % weight/weight 1,3-butadiene (EINECS No. 203-450-8).		

Name: HEPTANE (AND ISOMERS)			REACH No: 01-2119475515-33
Concentration: $\geq 40\%$ - $< 50\%$			CAS No: -
Classification:			EC No: 927-510-4
Index No:			
 Flam. Liq. 2 H225	 Asp. Tox. H304	 Skin Irrit.2 H315	
 STOT SE 3 H336	 Aquatic Chronic 2 H411		
Name: ETHYL ACETATE			REACH No: 01-2119475103-46
Concentration: $\geq 1.5\%$ - $< 2.5\%$			CAS No: 141-78-6
Classification:			EC No: 205-500-4
Index No: 607-022-00-5			
 Flam. Liq. 2 H225	 Eye Irrit. 2 H319	 STOT SE 3 H336	

For the wording of the listed risk phrases refer to section 16.

4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing. Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath). Remove contaminated clothing immediately and dispose off safely. After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

N.A. as aerosol preparation.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

5. FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Unsuitable extinguishing media:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately.

This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation. Use appropriate respiratory protection.
See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand.

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Pressurized container. Do not perforate or burn even after use. Do not use near fire or other possible sources of ignition. During work phase do not smoke. Avoid contact with skin and eyes, inhalation of vapours and mists.
Use localized ventilation system. Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working. See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
Incompatible materials:
None in particular. See also section number 10
Instructions as regards storage premises:
Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Hydrocarbons, C3-4

TLV TWA - 1000 ppm (2400mg/m³)

TLV STEL - 4000 ppm (9600mg/m³)

Heptane (and isomers)

TLV TWA - 1600 mg/m³ (395 ppm)

Ethyl acetate - CAS: 141-78-6

ACGIH, 400 ppm - Notes: URT and eye irr

DNEL Exposure Limit Values :

Heptane (And Isomers)

Category	Route of Exposure	Exposure Duration	Effect	Value
Worker	Human Inhalation	Short Term	systemic effects	2085 mg/m ³
Consumer	Human Inhalation	Short Term	systemic effects	477 mg/m ³
Worker	Human Dermal	Long Term	systemic effects	300 mg/kg
Consumer	Human Dermal	Long Term	systemic effects	149 mg/kg
Consumer	Human Oral	Long Term	systemic effects	149 mg/kg

PNEC Exposure Limit Values:
N.A.

8.2. Exposure controls

Eye protection:

Wear goggles with lateral protection EN166 .

If exposure to vapours cause a sense of bother to eyes, use antigas mask with complete facial.

Protection for skin:

It is not necessary in case of brief contact except for wearing antistatic clean and covering garments.

In case of long and frequent contact use protective and waterproof garments to this material.

Choosing specific protection as peak, gloves, boots, overalls depends on the type of operations.

Protection for hands:

During normal manipulation it is not necessary a particular protection.

In case of frequent contacts protect hands with gloves resistant to solvents (OVC, PE, neoprene, not natural rubber).

Respiratory protection:

The levels of air concentration should be maintained under the exposure limits. If inhalation are over exposure limit use a supplied air respirator with cartridge filter. Filter type EN 141.

Thermal Hazards:

The aerosol container if overheated, deforms, breaks and it can be thrown a considerable distance.

Environmental exposure controls:

Keep the container and use the product only in well ventilated place. A located ventilation may be necessary for some operations.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

- | | |
|--|---|
| a) Appearance: | pressurized container with base and liquefied gas |
| b) Odour: | Characteristic |
| c) Odour threshold: | N.A. |
| d) pH: | N.A. |
| e) Melting point/freezing point; | N.A. |
| f) Initial boiling point and boiling range; | N.A. |
| g) Flash point: | < 0 °C |
| h) Evaporation rate: | N.A. |
| i) Flammability (solid, gas): | N.A. |
| j) Upper/lower flammability or explosive limits: | N.A. |
| k) Vapour pressure: | 3-5 bar |
| l) Vapour density: | 2 |
| m) Relative density: | N.A. |
| n) Solubility(ies): | |
| • Solubility in water: | Not soluble |
| • Lipid solubility: | Yes |
| o) Partition coefficient: n-octanol/water: | N.A. |
| p) Auto-ignition temperature: | > 400°C |
| q) Decomposition temperature: | N.A. |
| r) Viscosity: | N.A. |
| s) Explosive properties: | N.A. |
| t) Oxidising properties. | N.A. |

9.2. Other information

- | | |
|---------------------------------------|------|
| Miscibility: | N.A. |
| Fat Solubility: | N.A. |
| Conductivity: | N.A. |
| Substance Groups relevant properties: | N.A. |

10. STABILITY AND REACTIVITY

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Keep away from sunlight, overheating.
Keep at temperature not exceeding 50°C.
Keep away from oxidant agents.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological information of the mixture: N.A.

Toxicological information of the main substances found in the mixture:

Heptane (and isomers)

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5840 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2920 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 23.3 mg/l - Duration: 4h

Ethyl Acetate - CAS: 141-78-6

LD50 (RABBIT) ORAL: 4935 MG/KG

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

12. ECOLOGICAL INFORMATION

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

It doesn't Contain CHLORINE-FLUORINE-CARBIDE.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Heptane (And Isomers)

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 13.4 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 3 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 20 mg/l - Duration h: 72

12.2. Persistence and degradability

None

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None

PBT Substances : None

12.6. Other adverse effects

None

13. DISPOSAL CONSIDERATION

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing comply with the local and national regulations currently in force. Aerosol container can explode at temperature above 50°C if contains little gas residue. Spray all the aerosol content before disposal. The product has to be considered: special dangerous disposal.

Waste disposal key:

The aerosol as a domestic waste is excluded from the application of such a normative for industrial activity, the empty aerosol for professional use can be classified as follow: 15.01.10: packaging containing residues of dangerous substances or residues contaminated by these substances.

14. TRANSPORT INFORMATION

14.1. UN number

ADR-UN number: UN 1950

IATA-UN number: UN 1950

IMDG-UN number: UN 1950

14.2. UN proper shipping name

ADR-Shipping Name: AEROSOLS,

IATA-Technical name: AEROSOLS,

IMDG-Technical name: AEROSOLS

Limited Quantity: max 1000ml Total gross mass of package not exceed 30 kg LQ2

14.3. Transport hazard class(es)

ADR-Class: 2, 5F

IATA-Class: 2.1

IMDG-Class: 2

ADR-Label: <UN1950 AEROSOLS>

IATA-Label: <UN1950 AEROSOLS>

IMDG-Label: <UN1950 AEROSOLS>

14.4. Packing Group

14.5 Environmental hazards

Marine pollutant: No

14.6. Special Precautions for User

IMDG-Technical name: AEROSOLS,

IMDG-EMS: F-D

IMDG-MFAG: S-U

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

N.A.

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
 Dir. 2000/39/EC (Occupational exposure limit values)
 Dir. 2006/8/EC
 Regulation (EC) n. 1907/2006 (REACH)
 Regulation (EC) n. 1272/2008 (CLP)
 Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
 Regulation (EU) n. 453/2010 (Annex II)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: None

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.
 Regulation (EC) nr 648/2004 (detergents).

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II): N.A

15.2. Chemical Safety Assessment

N.A.

16. OTHER INFORMATION

Legenda

N.A.: not applicable
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 CAS: Chemical Abstracts Service (division of the American Chemical Society).
 CLP: Classification, Labelling, Packaging.
 DNEL: Derived No Effect Level.
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals.
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 IMDG: International Maritime Code for Dangerous Goods.
 INCI: International Nomenclature of Cosmetic Ingredients.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 LTE: Long-term exposure.
 PNEC: Predicted No Effect Concentration.
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 STE: Short -term exposure.
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 EC European Community number

Full text of phrases referred to in Section 3:

H220 Extremely flammable gas.
 H280 Contains gas under pressure; may explode if heated.
 H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 H319 Causes serious eye irritation.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold
CCNL - Appendix 1

Safety Data Sheet prepared according to with Regulation 830/2015/EU.

This Safety Data Sheet has been compiled in accordance with current European regulations and is applicable to all countries that have implemented these standards in their national laws.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The Company shall not be liable for any damages or injury resulting from its use.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended. It is always the responsibility of the user to comply with the rules of hygiene, safety and environmental protection provided by applicable law.

This MSDS cancels and replaces any preceding release.

Revision 04: Revision of the document in accordance with Regulation 830/2015/EU.

This Data Sheet is based on information supplied by producer (Version 3.7 dated 1/12/14).

