

according to Regulation (EC) No 1272/2008

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

NORD-TEST Reiniger U 87 A/M Spray

Further trade names

Article no. (user): 121.300.105

UFI: RQK5-MXG8-7Q67-U2X1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Washing and cleaning products (including solvent based products)

1.3. Details of the supplier of the safety data sheet

Company name: Helling GmbH
Street: Spoekerdamm 2
Place: D-25436 Heidgraben

Telephone: +49-4122-922-0 Telefax: +49-4122-922-201

e-mail: info@helling.de Internet: www.helling.de

1.4. Emergency telephone Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Hazard categories: Aerosols: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.
May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

acetone; propan-2-one; propanone

Signal word: Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.



according to Regulation (EC) No 1272/2008

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 2 of 12

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to industrial incineration plant.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation (EC)	No 1272/2008)	·		
67-64-1	acetone; propan-2-one; propar	one		35 - 45 %	
	200-662-2	606-001-00-8	01-2119471330-49		
	Flam. Liq. 2, Eye Irrit. 2, STOT	SE 3; H225 H319 H336 EU	JH066		
109-87-5	Dimethoxymethane	35 - 45 %			
	203-714-2		01-2119664781-31		
	Flam. Liq. 2, Eye Irrit. 2; H225				
74-98-6	propane	12 - 17 %			
	200-827-9	601-003-00-5	01-2119486944-21		
	Flam. Gas 1; H220				
106-97-8	butane	3 - 8 %			
	203-448-7	601-004-00-0	01-2119474691-32		
	Flam. Gas 1; H220				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

Opecine of	0116. E1111113, WI-I	actors and ATE	
CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
67-64-1	200-662-2	acetone; propan-2-one; propanone	35 - 45 %
	inhalation: LC	C50 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg	
109-87-5	203-714-2	Dimethoxymethane	35 - 45 %
	dermal: LD50) = > 5000 mg/kg; oral: LD50 = 6453 mg/kg	
74-98-6	200-827-9	propane	12 - 17 %
	inhalation: LC	C50 = > 20 mg/l (vapours)	
106-97-8	203-448-7	butane	3 - 8 %
	inhalation: LC	250 = 658 mg/l (dusts or mists)	

SECTION 4: First aid measures

4.1. Description of first aid measures





according to Regulation (EC) No 1907/2006

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 3 of 12

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Change contaminated clothing.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Following inhalation: Headache. drowsiness. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up

Other information

Ventilate affected area.

Flammable liquids: Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling





according to Regulation (EC) No 1907/2006

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 4 of 12

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. When using do not eat or drink. After work, wash hands and face.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

Hints on joint storage

Do not store together with: Oxidizing agents.

7.3. Specific end use(s)

Washing and cleaning products (including solvent based products)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
109-87-5	Dimethoxymethane	1000	3160		TWA (8 h)	WEL
		1250	3950		STEL (15 min)	WEL



according to Regulation (EC) No 1907/2006

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 5 of 12

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone			
Consumer DN	EL, long-term	oral	systemic	62 mg/kg bw/day
Consumer DN	EL, long-term	dermal	systemic	62 mg/kg bw/day
Worker DNEL	, long-term	dermal	systemic	186 mg/kg bw/day
Worker DNEL	, acute	inhalation	local	2420 mg/m³
Consumer DN	EL, long-term	inhalation	systemic	200 mg/m³
Worker DNEL	, long-term	inhalation	systemic	1210 mg/m³
109-87-5	Dimethoxymethane			
Consumer DNEL, long-term		oral	systemic	18,1 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	18,1 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	17,9 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	31,5 mg/m³
Worker DNEL, long-term		inhalation	systemic	126,6 mg/m³

PNEC values

CAS No	Substance	
Environmen	tal compartment	Value
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Freshwater	(intermittent releases)	21 mg/l
Marine wate	er	1,06 mg/l
Freshwater	sediment	30,4 mg/l
Marine sediment		3,04 mg/l
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		29,5 mg/l
109-87-5	Dimethoxymethane	
Freshwater		14,5 mg/l
Marine water		1,48 mg/l
Freshwater sediment		13,135 mg/kg
Marine sediment		1,3135 mg/kg
Micro-organ	isms in sewage treatment plants (STP)	4,65 mg/kg

8.2. Exposure controls





Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment





according to Regulation (EC) No 1907/2006

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 6 of 12

Eye/face protection

Wear eye/face protection.

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of

Protect skin by using skin protective cream.

Skin protection

Body protection: not required.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol Colour: colourless characteristic Odour:

Melting point/freezing point: not determined Boiling point or initial boiling point and not determined

boiling range: Flammability

Solid/liquid: not applicable not determined Gas: Lower explosion limits: not determined Upper explosion limits: not determined Flash point: not applicable Decomposition temperature: not determined pH-Value: not determined The study does not need to be conducted Water solubility:

because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined Density: not determined Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties not explosive. Self-ignition temperature

Solid: not applicable not determined Gas:

Oxidizing properties Not oxidising.

Other safety characteristics

not determined Evaporation rate:



according to Regulation (EC) No 1907/2006

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 7 of 12

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No risks worthy of mention.

10.2. Chemical stability

No risks worthy of mention.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Remove all sources of ignition. Keep away from heat.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (inhalation gas) 13708,3 ppm

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
67-64-1	acetone; propan-2-one; propanone							
	oral	LD50 mg/kg	5800	Rat	RTECS			
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID			
	inhalation (4 h) vapour	LC50	76 mg/l	Rat				
109-87-5	Dimethoxymethane							
	oral	LD50 mg/kg	6453	Rat				
	dermal	LD50 mg/kg	> 5000	Rabbit				
74-98-6	propane							
	inhalation (4 h) vapour	LC50	> 20 mg/l	Rat				
106-97-8	butane							
	inhalation (4 h) dust/mist	LC50	658 mg/l	Rat				

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 8 of 12

STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

see section 12

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
67-64-1	acetone; propan-2-one; propanone							
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss			
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna			
	Algae toxicity	NOEC	530 mg/l	8 d	Microcystis aeruginosa			
109-87-5	Dimethoxymethane							
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Danio rerio (zebrafish)			
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna			
74-98-6	propane							
	Acute fish toxicity	LC50 mg/l	> 100	96 h				
	Acute algae toxicity	ErC50 mg/l	> 100					
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h				

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
74-98-6	propane	2,36
106-97-8	butane	2,89

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.



according to Regulation (EC) No 1907/2006

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 9 of 12

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The product has not been tested.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS14.3. Transport hazard class(es):2

Hazard label: 2



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2
Hazard label: 2.1



5F

Classification code:





according to Regulation (EC) No 1907/2006

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 10 of 12

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: See SP277 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1 Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

2004/42/EC (VOC): 59,5 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: acetone; propan-2-one; propanone



according to Regulation (EC) No 1907/2006

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 11 of 12

SECTION 16: Other information

Changes

section 1, 9, 11, 12, 13, 14, 15, 16

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container SVHC: Substance of Very High Concern

Key literature references and sources for data

General review and adaption to regulation (EC) 2020/878

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eve irritation.

H336 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be





according to Regulation (EC) No 1907/2006

NORD-TEST Reiniger U 87 A/M Spray

Revision date: 05.06.2023 Page 12 of 12

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)