

VersaLink[®] B7000 Series Multifunction Printers are built on Xerox[®] ConnectKey[®] Technology. For more information, go to **www.connectkey.com**.



SYSTEM SPECIFICATIONS	VERSALINK [®] B7025	VERSALINK [®] B7030	VERSALINK [®] B7035
One-sided Speed ¹			
8.5 x 11 in./A4/210 x 297 mm	Up to 25 ppm (pages per minute) long edge feed (LEF)	Up to 30 ppm LEF	Up to 35 ppm LEF
8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	Up to 16 ppm Up to 14 ppm	Up to 20 ppm Up to 17 ppm	Up to 22 ppm Up to 19 ppm
Two-sided Speed ¹			
8.5 x 11 in./A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	Up to 19 ppm LEF Up to 10 ppm Up to 9 ppm	Up to 23 ppm LEF Up to 12 ppm Up to 11 ppm	Up to 26 ppm LEF Up to 14 ppm Up to 13 ppm
Monthly Duty Cycle ²	Up to 107,000 pages/month ¹	Up to 129,000 pages/month ¹	Up to 153,000 pages/month ¹
Recommended Average Monthly Print Volume ³	Up to 13,000 pages	Up to 15,000 pages	Up to 17,000 pages
Hard Drive	320 GB HDD (Optional on Desktop model)		
Processor	1.05 GHz Dual-Core		
Memory	2 GB		
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair		

Controller Features	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support				
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian				
DEVICE SPECIFICATIONS					
ELECTRICAL REQUIREMENTS					
North America	Voltage: 110-127 V -10	%/+6%			
	Frequency: 50/60 Hz +/-	3%,12A			
Europe and Other Geographies	Voltage: 220-240 V +/-				
	Frequency: 50 Hz +/-3 %	, 8A			
POWER CONSUMPTION					
Printing ⁴		pm = 1.5 kWh; 35 ppm = 1.7	kWh		
Standby Mode ⁴	110V: 83 watts or less; F	For 220V: 86 watts or less			
Sleep Mode ⁴	0.81 Watts or less				
OPERATING ENVIRONMENT	-				
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)			
Required Temperature Range (Operating)	50 to 90° F (10 to 32° C	50 to 90° F (10 to 32° C)			
Required Relative Humidity	10% to 85%				
Sound Power Levels	Printing: 6.75 B(A) or les	Printing: 6.75 B(A) or less			
	 25 ppm = 6.54 B(A); 30 ppm = 6.70 B(A); 35 ppm = 6.75 B(A) Standby: 4.10 B(A) or less 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A); 35 ppm = 4.10 B(A) 				
	Full System (including				
	Printing: 25 ppm = 7.22 B(A); 30 ppm = 7.37 B(A); 35 ppm = 7.46 B(A) Standby: 25 ppm = 6.54 B(A); 30 ppm = 6.70 B(A); 35 ppm = 6.75 B(A)				
Sound Pressure Levels	Printing: 50.0 dB(A)				
	• 25 ppm = 49.4 dB(A)	; 30 ppm = 49.7 dB(A); 35 pp	om = 50.0 dB(A)		
	Standby: 16.4 dB(A)				
	• 25 ppm = 16.4 dB(A); 30 ppm = 16.4 dB(A); 35 ppm = 16.0 dB(A)				
	Full System (including				
	Printing: 25 ppm = 53.4 dB(A); 30 ppm = 53.6 dB(A); 35 ppm = 54.0 dB(A)				
	Standby: 25 ppm = 16.0 dB(A); 30 ppm = 16.0 dB(A); 35 ppm = 15.7 dB(A)				
Boot Time (from Off to UI Ready)					
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds				
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT	
Base Unit	23.23 in./590 mm	26.41 in./670.8 mm	30.23 in./767.9 mm	113.1 lbs./51.3 kg	
Base Unit with Single Tray with Stand Module	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1118.6 mm	168.21 lbs./75.8 kg	
Base Unit with High Capacity Tandem Tray Unit	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1118.6 mm	193.35 lbs./87.2 kg	

Base Unit with Three Tray Module and Office Finisher (with Booklet Maker)	45.22 in./1148.6 mm	.22 in./1148.6 mm 26.7 in./678.6 mm		273.81 lbs./124.2 kg	
Base Unit with Three Tray Module and Office Finisher LX (with Booklet Maker)	47.0 in./1194.0 mm	26.8 in./681.8 mm	44.04 in./1118.6 mm	249.12 lbs./113.0 kg	
CERTIFICATIONS					
To view the latest list of certification	s, go to www.xerox.com/(OfficeCertifications.			
PRINT	VERSALINK [®] B7025	VERSALINK [®]	87030 VER	SALINK [®] B7035	
First-Print-Out Time	As fast as 10.4 seconds	As fast as 9.1 s	econds As f	As fast as 9.1 seconds	
Print Resolution	Up to 1200 x 1200 dpi				
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3 [™] (Optional)				
Maximum Print Area		paper, 2 mm from Side and	d Trail edges of paper		
Print Features	Job Monitoring (Client or LAN Fax (requires Fax Kit N-up Page Layout (up to Paper Selection by Attribu Personal Print Print Around Enable/Disa Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages	tatus ng) D or Banner, Print ID in ma Local User Interface)) 16 pages per sheet) ute ble ble page programming: covers ettings			
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A				

Operating Systems	Windows [®] 7, 8, 8.1, 10		P2 6 2016			
		008 R2 SP1, Server 2012, Server 2012	R2, Server 2016			
	Mac OS [®] version 10.12, 10.13	Citrix®				
		Redhat® Enterprise Linux®				
	·	Reanat® Enterprise Linux® Fedora Core				
	IBM® AIX®					
	HP-UX®					
	Oracle [®] Solaris					
	SUSE®					
	SAP®					
	Note: For information about suppor Downloads page and specify your d	ted versions for the above operating s levice at www.support.xerox.com .	systems, please visit our Drivers &			
Fonts	PostScript fonts: 136					
	PCL fonts: 83					
Xerox® Global Print Driver®	devices from a single driver. It provi	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox [®] and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.				
Xerox [®] Pull Print Driver	Print environment. Uses a single que across a broad range of printing ass	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.				
СОРҮ	VERSALINK [®] B7025	VERSALINK [®] B7030	VERSALINK [®] B7035			
Document Scanner	110-sheet Single Pass Duplex Auton	natic Document Feeder (DADF)				
Document Scanner Size	Platen: Up to 13.1 x 17.2 in./332.0 x	437 mm				
	DADF: Up to 11.7 x 17 in./297 x 431	1.8 mm				
Simplex Copy Speed	Up to 25 cpm (copies per minute) 8.5 x 11 in.					
	Up to 25 cpm A4 (210 x 297 mm)	Up to 25 cpm A4 (210 x 297 mm) Up to 30 cpm A4 (210 x 297 mm) Up to 35 cpm A4 (210 x 29				
Duplex Copy Speed	Up to 20 cpm (copies per minute)Up to 20 cpm (copies per minute)Up to 20 cpm (copies per minute)8.5 x 11 in.8.5 x 11 in.8.5 x 11 in.		Up to 20 cpm (copies per minute) 8.5 x 11 in.			
	Up to 20 cpm A4 (210 x 297 mm)	Up to 20 cpm A4 (210 x 297 mm)	Up to 20 cpm A4 (210 x 297 mm)			
First-Copy-Out Time	As fast as 6.8 seconds					
Sides (input: output)	1:1, 1:2, 2:2 and 2:1	1:1, 1:2, 2:2 and 2:1				
Quantity	1 to 999					
Resolution (max.)	Up to 600 x 600 dpi					
	Variable zoom from 25% to 400% in 1% increments					
Reduction/Enlargement	Variable zoom from 25 % to 400 %	in 1% increments				
Reduction/Enlargement Concurrency	Variable zoom from 25% to 400% Concurrent scanning and printing	in 1% increments				

Copy Features	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping)*
	Automatic Background Suppression
	Book Copying with Center Erase
	Booklet Copying*
	Collation
	Darkness Control
	Edge Erase
	Front Cover
	ID Card Copy
	Image Enhancement
	Image Shift
	Lighten/Darken
	N-up
	Reduce/Enlarge 25 % to 400 %
	Original Orientation
	Original Size
	Original Type
	Page Layout
	Sample Copy
	Saturation
	Sharpness
	*Requires HDD/Productivity Kit
SCAN	
Capability	Black-and-white and color scanning
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
Simplex Input Speed	Black-and-white: Scan up to 55 ipm – 8.5 x 11 in./A4 (210 x 297 mm)
	Color: Scan up to 55 ipm – 8.5 x 11 in./55 ipm A4 (210 x 297 mm)
Duplex Input Speed	Black-and-white: Scan up to 26 ipm – 8.5 x 11 in./A4 (210 x 297 mm)
	Color: Scan up to 26 ipm – 8.5 x 11 in./26 ipm A4 (210 x 297 mm)
Resolution	Optical – 600 x 600 dpi
Bit Depth	24-bit color/8-bit grayscale
Maximum Scan Area	Platen: Up to 13.1 x 17.2 in./332 x 437 mm
	Document Feeder: 11.7 x 17 in./297 x 431.8 mm
Network Filing Protocols	FTP
rection in hing rotocolo	SMTP
	SMB
	sFTP
File Formats	JPG
The Formats	TIFF (single and multi-page)
	XPS (single and multi-page)
	PDF (single and multi-page)
	Searchable PDF via Optical Character Recognition (OCR)
	Password-protected PDF
	Linearized PDF (set via embedded web server) and PDF/A
Scan Driver Compatibility (Network Only)	WIA
(INCLIMOIN OILLY)	TWAIN

Supported Scan Destinations	Scan to Home
	Scan to USB
	Scan to Email
	Scan to Network (Browse FTP or Browse SMB)
NETWORK SCANNING – SOFTWAR	
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey [®] Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey [®] Apps to the Xerox [®] ConnectKey [®] Technology-enabled multifunction printer.
PSTN ONE-LINE OR THREE-LINE F	FAX (OPTIONAL)
Fax ⁵	
Fax Speed	33.6 Kbps
Resolution	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Server Fax Enablement, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
FAX OVER IP (OPTIONAL)	
Compliance	T.38 compliant IP/SIP
Resolution	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
MOBILE SOLUTIONS AND MOBIL	E DEVICE APPS
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone [®] or iPad [®] with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopria® Print Service	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.
Xerox [®] @PrintByXerox App	@PrintByXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android [™] , Google [®] Chromebook [™] and more) to a Xerox [®] printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox [®] Print Service plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play [™] store.
Xerox® Workplace Mobile App (download from the Xerox App Gallery)	The Xerox [®] Workplace Mobile App gives you the personal contactless connection you need with your multifunction printer (MFP), allowing you to save time on daily tasks and get work done safely. You can scan, print, copy or release jobs using your mobile smartphone as a remote control, without having to touch your MFP user panel. It takes the guesswork out of quickly and securely connecting your iOS and Android devices to your Xerox [®] MFP. Download the app for free. Use it with Xerox [®] Workplace Solutions to access advanced features.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox [®] Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.

Access Controls	
AES 256-bit Encryption	
Audit Log	
Certificate Path Validation	
Certificate Revocation List (CRL)/Status Protocol (OCSP)	
Detection of External Program Falsification (XCP Plug-in)	
Cisco [®] Identity Services Engine (ISE)	
Integration Domain Filtering	
FIPS 140-2	
Firmware Verification	
Immediate Disk Overwrite*	
IP Address Filtering	
IPsec	
Network Authentication	
Port Filtering	
Pre-installed Self-Signed Certificates	
Role Based Permissions	
Secure Email	
Secure Fax	
Secure Print	
Security Certificate Management	
Smart Card Enablement (CAC/PIV/.NET)	
SNMPv3	
Status Protocol (OCSP)	
TLS/SSL	
TLS/SSL	
TLS/SSL *Requires HDD/Productivity Kit	
*Requires HDD/Productivity Kit	
*Requires HDD/Productivity Kit INTING/NETWORK ACCOUNTING (STANDARD)	
*Requires HDD/Productivity Kit INTING/NETWORK ACCOUNTING (STANDARD) Copy, Print, Fax, Scan and Email usage	
*Requires HDD/Productivity Kit INTING/NETWORK ACCOUNTING (STANDARD) Copy, Print, Fax, Scan and Email usage Xerox® Standard Accounting Tool	
*Requires HDD/Productivity Kit INTING/NETWORK ACCOUNTING (STANDARD) Copy, Print, Fax, Scan and Email usage Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD	
*Requires HDD/Productivity Kit INTING/NETWORK ACCOUNTING (STANDARD) Copy, Print, Fax, Scan and Email usage Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD	
*Requires HDD/Productivity Kit INTING/NETWORK ACCOUNTING (STANDARD) Copy, Print, Fax, Scan and Email usage Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts	
*Requires HDD/Productivity Kit INTING/NETWORK ACCOUNTING (STANDARD) Copy, Print, Fax, Scan and Email usage Kerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting)	
*Requires HDD/Productivity Kit INTING VECTION (STANDARD) Copy, Print, Fax, Scan and Email usage Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD	
*Requires HDD/Productivity Kit INTING VATING VETWORK ACCOUNTING (STANDARD) INTING Verify Copy, Print, Fax, Scan and Email usage Verify Verify Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Verify Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD	
*Requires HDD/Productivity Kit INTING/NETWORK ACCOUNTING (STANDARD) Copy, Print, Fax, Scan and Email usage Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)	
*Requires HDD/Productivity Kit INTING/NETWORK ACCOUNTING (STANDARD) Copy, Print, Fax, Scan and Email usage Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts without HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 50,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions) Administrator can manage the feature via the Embedded Web Server.	
*Requires HDD/Productivity Kit INTINE INTENE INTINE	
*Requires HDD/Productivity Kit INTING/NETWORK ACCOUNTING (STANDARD) INTING/NETWORK ACCOUNTING Tool INTING/NETWORK Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions) Administrator can manage the feature via the Embedded Web Server.	
*Requires HDD/Productivity Kit INTING/FUNCTIVERK ACCOUNTING (STANDARD) INTING/FUNCTIVERK ACCOUNTING (STANDARD) Copy, Print, Fax, Scan and Email usage Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts without HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 6,000 User IDs; Up to 6,0000 Account IDs without HDD Up to 14,000 Accounting Records (transactions) Administrator can manage the feature via the Embedded Web Server. IETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING) * Enhanced network accounting with up to the minute data on how the system is being used * Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print,	
*Requires HDD/Productivity Kit INTING / FUNCK ACCOUNTING (STANDARD) INTING / FUNCK ACCOUNTING Tool INTING / FUNCK Accounting Tool Intervention Intervention	
*Requires HDD/Productivity Kit INTING/VETWORK ACCOUNTING (STANDARD) Copy, Print, Fax, Scan and Email usage Variable	

PAPER HANDLING	
DOCUMENT FEEDER	
Capacity ⁶	Duplex Automatic Document Feeder (DADF): 110 sheets
Sizes One-sided: Two-sided:	Custom sizes: 4.92 x 3.35 in. to 11.69 x 17 in./125 x 85 mm to 297 x 431.8 mm 4.92 x 4.33 in. to 11.69 x 17 in./125 x 110 mm to 297 x 431.8 mm
Weights One-sided: Two-sided:	11 to 34 lb. bond/38 to 128 gsm 13 to 34 lb. bond/50 to 128 gsm
BYPASS TRAY	
Capacity ⁶	100 sheets
Sizes	Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in./88.9 x 98.4 mm to 297 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 216 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	BondPlain PaperCardstockCustomEnvelopesHole PunchedLabelsHeavyweight LabelsLetterheadLightweight CardstockPre-PrintedRecycled
TRAY 1	
Capacity ⁶	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	BondPlain PaperCardstockCustomHole PunchedLabelsHeavyweight LabelsExtra Heavyweight LabelsLetterheadLightweight CardstockHeavyweight CardstockPre-PrintedRecycled

SINGLE TRAY MODULE (OPTIONAL – BASE MODEL ONLY)
Capacity ⁶	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	Bond
	Plain Paper
	Cardstock
	Custom
	Hole Punched
	Labels
	Heavyweight Labels
	Extra Heavyweight Labels
	Letterhead
	Lightweight Cardstock
	Heavyweight Cardstock
	Pre-Printed
	Recycled
SINGLE TRAY MODULE W	VITH STAND (OPTIONAL)
Capacity ⁶	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	Bond
	Plain Paper
	Cardstock
	Custom
	Hole Punched
	Labels
	Heavyweight Labels
	Extra Heavyweight Labels
	Letterhead
	Lightweight Cardstock
	Heavyweight Cardstock
	Pre-Printed
	Recycled
THREE TRAY MODULE (O	PTIONAL)
Capacity ⁶	Tray 2: 520 sheets
	Tray 3: 520 sheets
	Tray 4: 520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights	
One-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm
Two-sided:	16 lb. bond to 60 lb. cover/60 to 169 gsm

Types	Bond
	Plain Paper
	Cardstock
	Custom
	Hole Punched
	Labels
	Heavyweight Labels
	Extra Heavyweight Labels
	Letterhead
	Lightweight Cardstock
	Heavyweight Cardstock
	Pre-Printed
	Recycled
HIGH CAPACITY TANDEM TRAY	(MODULE (OPTIONAL)
Capacity ⁶	Tray 2: 520 sheets
	Tray 3: 870 sheets
	Tray 4: 1,130 sheets
Sizes	Tray 2: Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
	Tray 3: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5
	Tray 4: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5
Weights	
One-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm
Two-sided:	16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	Bond
	Plain Paper
	Cardstock
	Custom
	Hole Punched
	Labels
	Heavyweight Labels
	Extra Heavyweight Labels
	Letterhead
	Lightweight Cardstock
	Heavyweight Cardstock
	Pre-Printed
	Recycled
ENVELOPE TRAY – REPLACES TR	
Capacity ⁶	Up to 60 envelopes
Sizes	#10 commercial, Monarch, DL, C5
	Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 mm to 162 x 241 mm
Weights	20 to 25 lb. bond/75 to 90 gsm
HIGH CAPACITY FEEDER (OPTI	
Capacity ⁶	2,000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5
	Standard Sizes, 0.5 & TTHIL and 7.25 & TO.5 III.//14 OF B5
Weights	16 lb. bond to 80 lb. cover/60 to 216 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm

TOTAL CAPACITY	
Base Unit Capacity ⁶	620 sheets
Single Tray Module Capacity ⁶	1,140 sheets
Single Tray Module with Stand Capacity ⁶	1,140 sheets
Three Tray Module Capacity ⁶	2,180 sheets
High-Capacity Tandem Tray Capacity ⁶	3,140 sheets
FINISHING	
OUTPUT TRAYS (OPTIONAL ON DI	ESKTOP MODEL)
Dual Catch Trays ⁶	250 sheets each; Lower tray offsets
INTEGRATED OFFICE FINISHER TY	'PE A AND INTEGRATED OFFICE FINISHER (OPTIONAL)
Stacking Tray	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3
Sizes	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm
Weights	Integrated Office Finisher Type A: 16 lb. bond to 80 lb. cover/60 to 220 gsm Integrated Office Finisher: 16 lb. bond to 95 lb. cover/60 to 256 gsm
Stapling	Dual Auto Stapling (Single for Type A): 50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or (2) 220 gsm covers)
OFFICE FINISHERS (OPTIONAL)	
Capacity ⁶	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4) (dual stapling only with optional booklet maker)
Sizes: Office Finisher LX Office Finisher	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm 5.8 x 11.7 in. to 5.8 x 17 in./148.0 x 297.0 mm to 148.0 to 432.0 mm
Weights	Office Finisher LX: 16 lb. bond to 80 lb. cover/60 to 220 gsm Office Finisher: 16 lb. bond to 80 lb. cover/60 to 256 gsm
Multiposition Stapling	50 sheets of 24 lb. bond/90 gsm
Hole Punch (Optional) North America: Europe:	Office Finisher LX up to 65 lb. cover (200 gsm)/Office Finisher up to 80 lb. cover (220 gsm) 2-3 Hole Punch 2-4 Hole Punch
BOOKLET MAKER FOR OFFICE FIN	ISHERS (SCORE/CREASE, SADDLE-STITCH STAPLE) (OPTIONAL)
Capacity ⁶	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Ledger – 11 x 17 in./A3 SEF
Saddle-stitch Stapling	2-15 sheets/8-60 page booklet Office Finisher LX: 16 lb. bond to 24 lb. bond/60 to 90 gsm Office Finisher: 16 lb. bond to 80 lb. cover/64 to 220 gsm
Score/Crease	1-15 sheets/unstapled/64-105 gsm
CONVENIENCE STAPLER (OPTION	
Capacity ⁶	50-sheet stapling 5,000 staples Requires a separate outlet
DEVICE MANAGEMENT	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ FTP
	Most protocols not in use can be disabled

Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS			
REMOTE CONTROL PANEL	1	· · · · · · · · · · · · · · · · · · ·		
	• Enables f	aster, more convenient technical sup	port and user training	
			can control the device remotely from a web page on	
	any devic			
	Remote user experience is identical to performing tasks directly at the device			
XEROX [®] CENTREWARE [®] WEB				
	• A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system			
	• Works wi	th any SNMP-managed printer from	any manufacturer	
		help with device discovery and install s, as well as basic accounting and ass	lations, health checks and troubleshooting, and device et management	
XEROX [®] EMBEDDED WEB SERVER	- INTEGRAT	ED DEVICE WEB PAGE		
Device Status	• Tray Stat	us/Contents		
	Consume	ables Status		
	• Billing/Us	sage		
	Quick Lin	ks		
	 Online Su 	ıpport		
Print Queue Viewing	Job print qu	ieue management — view and delet	e	
Job Submission	Print-ready	files (PS (with optional PostScript opt	ion), PCL, PDF, XPS, JPEG)	
Device Administration	Allows simp	le, remote installation setting of conf	figuration options and management of the device	
Browsers		Internet Explorer®		
	Microsoft E	-		
	Mozilla™ Fir			
	Apple® Safari® Google Chrome™			
REMOTE SERVICES	5			
Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox [®] Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.			
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox [®] output devices based on actual usage, eliminating the need to manually manage supplies inventory.			
SUPPLIES AND ACCESSORIES		QUANTITY	PART NUMBER	
SUPPLIES				
Standard Capacity Print Cartridges ⁷		15,500 standard pages	106R03393	
High Capacity Print Cartridges ⁷		31,000 standard pages	106R03394	
Worldwide Metered Print Cartridge	Worldwide Metered Print Cartridge ⁸		106R03392	
Black Drum Cartridge ⁹		80,000 pages	113R00779	
Office Finishers Booklet Maker Car (8 cartridges per carton)	tridge	16,000 staples	008R12897	
Staple Refills for Finishers (3 cartridges per carton)		15,000 staples	008R12941	
Staple Cartridge for Finishers (1 cartridge per carton)				

ACCESSORIES/OPTIONS	PART NUMBER
Single Tray Module (does not include Stand – for Base Model only)	097S04910
Single Tray with Stand Module	097S04907
Three Tray Module	097S04908
High-Capacity Tandem Tray Module	097S04909
Envelope Tray (This replaces Tray 1)	497K17720
Center Output Tray (Dual Catch Tray)	497K17800
HDD (320 GB Hard Drive)	497K17740
Integrated Office Finisher (Type A)	097S04911
Integrated Office Finisher	097S04847
Office Finisher LX	097S04848
Office Finisher	097S05019
Booklet Maker for Office Finisher LX	497K03852
Booklet Maker for Office Finisher	497K20590
2/3 Hole Punch for Office Finisher LX (available in Western Hemisphere)	497K03860
2/3 Hole Punch for Office Finisher (available in Western Hemisphere)	497K20600
2/4 Hole Punch for Office Finisher LX (available in Eastern Hemisphere)	497K03870
2/4 Hole Punch for Office Finisher (available in Eastern Hemisphere)	497K20610
1 Line Fax Kit (PSTN Fax)	497K17750
3 Line Fax Kit (PSTN Fax)	497K17760
Wireless Network Adapter Kit	497K16750
Internal Card Reader/RFID Kit	497K18120 (Western Hemisphere)
	497K18140 (Eastern Hemisphere)
PostScript Kit	497K17810
Fax Over IP Kit	497K17820

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR[®] Program requirements for Imaging Equipment.

⁵ Requires analog phone line.

⁶ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁷ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

⁸ Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in./A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.

⁹ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed.

For more information visit: https://www.office.xerox.com/latest/SUPGL-01.pdf.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.

