

SKIN TRANSPLANTATION

We care



Technical details Dermatome D80

D80 Dermatome Features

- Cordless, lightweight dermatome for optimal free movement
- Easy thickness adjustment from 0.0 to 1.2mm with 0.1mm increments
- Standard cutting width of 80mm, supplied with reducing clamps for a width of 35, 50 and 65 mm
- Quick blade replacement possible without tooling
- Anodised aluminium and stainless steel

Technical data

Weight	1330 [g] / 47 [oz]
Motor capacity	15 [W]
Dimensions (l x w)	295 x 104 [mm] / 11.6" x 4.09"
Battery (Li-Ion)	7.4 [V] / 2400 [mAh]
Diameter grip	45 [mm] / 1.77"
Charge supply	100-240 [V]
Cutting width	80 [mm] / 3.15"
Charge current	1200 [mA]
Graft thickness	0-1.2 [mm] / 0-0.048"
Charge time	~ 3 [hrs]
Stroke blade	3 [mm] / 0.118"

Set contents

- 4.D80STS** D80 dermatome, complete set, 2400mAh Li-Ion battery, this includes:
- 4.D80** D80 dermatome without battery- and motor cartridge
- 4.ANS-HC** Dermatome battery charger with adaptors for Li-Ion 2400 mAh battery
- 4.SF02** Sterile funnel for large diameter dermatome shaft
- 4.SCL** Sterile clamp
- 4.D80 AC1** D80 sterilization case
- 4.D80CL35-20** D80 width reducing clamp 35 mm
- 4.D80CL50-21** D80 width reducing clamp 50 mm
- 4.D80CL65-22** D80 width reducing clamp 65 mm
- 4.SU01** Dermatome charger support unit
- 4.BC7.4V2400** Dermatome battery cartridge Li-Ion, 7.4V, 2400 mAh
- 4.MCX15** Dermatome motor cartridge, long (new) version
- 4.076** Torx T20 screwdriver
- 5.D80BL10** D80 dermatome blades, box 10 pcs.



4.D80STS



4.D80



4.ANS-HC



4.SF02



4.SCL



4.D80AC1



4.D80CL35 / 4.D80CL50 4.D80CL65



4.SU01



4.BC7.4V2400



4.MCX15



5.D80BL10



4.076