



Product Data Sheet Delta

May, 2023

Type of flooring	EN ISO 26986	Expanded (cushioned) polyvinyl chloride floor covering			
Class of use	ISO 10874 (EN 685)				
CE certification	EN 14041:2004/AC:2006	2701-0082-DoP-2021-11			
TECHNICAL CHARACTERISTICS AND PERFORMANCES					
	ISO 24346 (EN 428) Total thickness	2,50 mm		ISO 24341 (EN 426) Roll lenght Roll width	30m (15-30) 2; 2,5; 3; 3,5; 4m
	ISO 24340 (EN 429) Wear layer thickness	0,15 mm		ISO 717/2 Impact sound absorption	19 dB
	ISO 23997 (EN 430) Weight per m²	1,600 kg/m²		ISO 24343-1 (EN 433) Residual indentation	≤ 0,35 mm
	ISO 105 B02 Method 3 Light fastness	≥ 6		Underfloor heating Suitable provided that the surface of the subfloor does not exceed 27°C	
	ISO 23999 (EN 434) Dimensional stability	Requirement by standard: < 0,4 % Tarkett result: ≤ 10,011 %		EN 13893 Slip resistance	
	EN 13501-1 Fire classification	Bfl-s1	EN 12524 Thermal resistance		0,03 - 0,04m²/kW
Wear layer binder content ISO 11638 Type I					



2701-0082-DoP-2021-11



This product is 100% recyclable

