

VIS-DCP2000-D

Full Digital Networked DSP Conference Processor for wired units



Features

- The unique AUDIO-LINK digital ring network technology achieve full-digital signal transmission and processing
- One CAT5e cable to transmit up 64 channels audio and other signals.
- All microphone units support audio, ID independent output. Working with voice recognition system to achieve voice role separation.
- High-fidelity sound quality by lossless audio transmission technology, 48K audio sampling rate and 20Hz ~ 20KHz frequency response
- A single conference controller can realize the independent control and merging of 4 conference rooms, can handle the cascade of multiple conference controllers to realize the merging and separation of larger conference rooms (Optional).
- "Hand-in-Hand-Loop-Network" connection makes the system always working perfectly no matter changing discussion unit or having any malfunctioned units
- The sensitivity of the unit microphone and 8 segment equalizer EQ adjusted independently.
- Conference controller can output 16 segment equalized EQ to achieve sound field adjustment; pressure limit, which can recognize the noise gate passed by human voice. AGC automatic volume gain control; AFC automatic feedback suppression and auto-mix technology.
- Sound output by separated zones function, each zone is automatically adjusted according to the volume of the position of the microphone, achieve longer distances pickup without whistle.
- Echo cancellation, remote two-way real-time call with another conference controller or another third-party video conferencing terminal.
- USB recording, controller monitor, advanced noise cancellation technology to realize clearer recording.
- System date, time management, and support count-down speech.
- Optional DANTE output module with other DANTE equipment used.
- Can drive 2x120W POE speaker, through extension main unit, support up to 16 POE speakers.

Functions

- Compliance with IEC 60914, GBT 15381-94
- Connect with VIS-EXM full-digital extension main unit, it can expand to 5200 discussion units
- "Hand-in-Hand-Loop-Network" connection and the system assigned to each unit independently ID to avoid ID conflict.
- Only wired discussion units can connect to the controller, fast and easily to adding delegate of meetings.

- 2 channel audio input, XLR or RCA type, for local audio input or remote video-conferencing input.
- Maximum 8-channel audio output, XLR, RCA or Phoenix type, can be connected to simultaneous interpretation output or partitioned output.
- Add the audio input box, the system can be connected to other condenser microphones or dynamic microphones, more choices for users.
- Built-in multi-way internal communication function.
- TCP/IP connection between controller and PC
- RS232 central control, realize microphone switch, priority, volume and other controls.
- RS232 or RS485 to send the PELCO/VISCA protocol to realize camera auto-tracking function.
- Hot plug-and-play, and auto-recovery function.
- Wide range of voltage from 100V~240VAC
- Without using PC software, our conference controller still owns following settings:
 - Limit on the number of speaking persons: By Setting the number of active units at the same time (Number is 1/2/4/6/ units), supports up to open 32 wired microphones in full-on mode.
 - Discussion modes:

"OPEN" Free for all, limited by the active units setting by controller, "VOICE" Can activate MIC by detecting sound without press button, "OVERRIDE" First in First out, "APPLY" To apply then to speak, "PTT" Press to speak(Optional),"ALL" Full open mode(Optional).

- Voting function: Approve/Abstain/Object
- Chairman unit has priority to close all other units or mute them temporarily
- Chairman unit can consent the application for speaking from delegate
- Simultaneous language interpretation
- With PC software to add more ways of voting:
 - Approve/Object
 - Approve/Abstain/Object
 - Level: 1/2/3/4/5
 - Ranking: --/0/+/++
- By using RFID card to identify, can realize voting with names.

Control & Indicators

LCD display to show all the operations and results

4-Way button for menu operate

One-button press to start recording

light indicator

Master volume control knob

Interfaces

Front panel USB recording interface

3.5mm headphone for monitoring

1x RCA audio input

1x XLR audio input

1x RCA audio output

1x XLR audio output

Page 6

6x Phoenix audio output connector
2x RJ45 digital audio connection
2x RJ45 for chairman unit, delegate unit, unit translators and other connection
1x RJ45 for wireless AP or router
1x DP9 male interface for external control
1x DP9 female interface for camera
1x three-pin phoenix interface for camera control keyboard
1x RJ45 for computer connection or network switcher
1x grounding screw
1x 100 ~ 240V AC Power Interface

Technical Parameters

Power 100V / 240V AC
Static power consumption 12W
Maximum power consumption 150W
Frequency Response 20Hz ~ 20KHz
Noise ratio (S / N) >96dBA
Total harmonic distortion <0.05%
Channel Crosstalk > 85dB
Dynamic range >94dB
RS-232 control: 1×9-pole Sub-D female socket 1×9-pole Sub-D male socket
Ethernet control: RJ45 connected to PC
Mounting: 19" standard rack
Dimensions (mm) 483L x 260W x43.6H
Weight: 3kg
Black color

Max. audio inputs
LINE IN 1: +10dBu
LINE IN 2: +10dBu
Max. audio outputs
LINE OUT 1: +12dBu BAL.
LINE OUT 2: +12dBu BAL.
LINE OUT 3: +12dBu BAL.
LINE OUT 4: +12dBu BAL.

Output impedance: >1kΩ
PC communication method: TCP/IP
Camera control method: RS-232/UDP
Network Interface: RJ45
Display: LCD1602
Recording file size: 0.8M/min
Limit on the number of speakers: 1/2/4/6, max in 8 persons
Page 7