

Specificații tehnice

[Acest tabel va fi completat de către oferant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5]

Numărul procedurii de achiziție: ocds-b3wdp1-MD-1749471765615						
Obiectul achiziției: Echipamente de radioteleviziune						
Denumirea bunurilor	Denumirea modelului bunului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde de referință
1	2	3	4	5	6	7
Lotul nr. 1						
1.1. Camera PTZ	AW-UE160KEJ 12V Power Supply with 4-Pin XLR Connection	Japonia China	Panasonic IndiPRO	Camera PTZ 4K 1" Type 9.6MP MOS Sensor Up to UHD 4K60 & 1080 Simultaneous Out 12G-SDI, HDMI, Fiber & IP Transmission Improved Phase-Detection Autofocus 20x Optical Zoom, 2x High-Speed Capture HDR Mode with HLG/BT.2020 Compatibility Wide 75.1° Horizontal Viewing Angle Up to 180°/Sec Pan/Tilt Speed Live Stream to Platforms via RTMP 2 x XLR Audio In, Front/Rear Tally Lamps Include 12v power supply 4-pin XLR connection	Camera PTZ 4K 1" Type 9.6MP MOS Sensor Up to UHD 4K60 & 1080 Simultaneous Out 12G-SDI, HDMI, Fiber & IP Transmission Improved Phase-Detection Autofocus 20x Optical Zoom, 2x High-Speed Capture HDR Mode with HLG/BT.2020 Compatibility Wide 75.1° Horizontal Viewing Angle Up to 180°/Sec Pan/Tilt Speed Live Stream to Platforms via RTMP 2 x XLR Audio In, Front/Rear Tally Lamps Include 12v power supply 4-pin XLR connection	ISO 9001, IATF 16949, ISO 14001, ISO45001, FCC, RHEL, RoHS RoHS
1.2. Tripod	VX-18M	China	Viltrox	Tripod + Fluid Head + Quick Release Plate + Pan Handle Load Capacity: 5.99 kg Maximum Working Height: 1.88 m Minimum Working Height: 0.84 m Folded Length: 89.92 cm Materials: Aluminum Versatile -75°to +90° tilt range and 360° pan range Separate pan/tilt locks and built-in bubble level indicator for aligning the horizon line Sliding QR plate features 1/4"-20 top mounting screw and spare 3/8" screw	Tripod + Fluid Head + Quick Release Plate + Pan Handle Load Capacity: 5.99 kg Maximum Working Height: 1.88 m Minimum Working Height: 0.84 m Folded Length: 89.92 cm Materials: Aluminum Versatile -75°to +90° tilt range and 360° pan range Separate pan/tilt locks and built-in bubble level indicator for aligning the horizon line Sliding QR plate features 1/4"-20 top mounting screw and spare 3/8" screw	CE, FCC, RoHS

				Interchangeable pan bar handle with angular adjustment that fits on either the left or right side of the head. Three-section leg design with mid-level spreader and adjustable height	Interchangeable pan bar handle with angular adjustment that fits on either the left or right side of the head. Three-section leg design with mid-level spreader and adjustable height	
1.3. SDI Cable	L-4.5CHWS	Japonia	Canare	HD-SDI – high-flex video cable 0.8L/3.7 -inner conductor –Annealed Copper, 7 x 0.34 mm -insulation – Foamed Polyethylene, Ø 4.57 mm -Designed for mobile applications -Flexible stranded center conductor -Highly-foamed PE insulation -High-density double braided shield -Equivalent L-4.5CHWS -suitable for mobile HD-SDI use	HD-SDI – high-flex video cable 0.8L/3.7 -inner conductor –Annealed Copper, 7 x 0.34 mm -insulation – Foamed Polyethylene, Ø 4.57 mm -Designed for mobile applications -Flexible stranded center conductor -Highly-foamed PE insulation -High-density double braided shield -Equivalent L-4.5CHWS -suitable for mobile HD-SDI use	FCC, CE, ISO 9001, RoHS
1.4. BNC connector	BCP-B45HW	Japonia	Canare	BNC Connector: -Compatible for HD-SDI digital video cable at position nr. 1.3	BNC Connector: -Compatible for HD-SDI digital video cable at position nr. 1.3	FCC, CE, ISO 9001, RoHS
1.5. Instalare	Instalare	Instalare	Instalare	Materiale și elemente pasive/active necesare pentru interconectarea echipamentelor și punerea în funcțiune a acestora; Lucrările de montare, precum și operațiunile de instalare, ajustare; Sistemul va fi predat la cheie; Garanția hardware minim 3 ani.	Materiale și elemente pasive/active necesare pentru interconectarea echipamentelor și punerea în funcțiune a acestora; Lucrările de montare, precum și operațiunile de instalare, ajustare; Sistemul va fi predat la cheie; Garanția hardware minim 3 ani.	
Lotul nr. 2						
2.1. SXS adapter	MxR Extreme Expresscard Adapter	China	E-Films	The ExpressCard SxS Replacement Adapter allows you to use SDHC cards, in Sony EX1 and EX3 cameras. The adapter has a convenient Push-In/Push-Out mechanism allowing to quickly change memory cards.	The ExpressCard SxS Replacement Adapter allows you to use SDHC cards, in Sony EX1 and EX3 cameras. The adapter has a convenient Push-In/Push-Out mechanism allowing to quickly change memory cards.	RoHS
2.2. microSDXC card	SDSQXAA-128G-AN6MA	China	Sandisk	microSDXC Card Type - microSDXC with Full-Size SD Adapter Storage Capacity – min. 128 GB Bus Type - UHS-I UHS Speed Class - U3 Video Speed Class - V30	microSDXC Card Type - microSDXC with Full-Size SD Adapter Storage Capacity – min. 128 GB Bus Type - UHS-I UHS Speed Class - U3 Video Speed Class - V30	RoHS, CE, FCC
2.3. SD Card	SDSDXXU-064G-ANCIN	China	Sandisk	Include Memory card (Echivalent SanDisk Extreme Pro SDXC 64 GB) Interface UHS-I capacity 64 GB Transfer Speed (READ) minim 170MB/S; Transfer Speed (WRITE) minim 90MB/S Speed Class 10(SD Speed Class), V30 (Video Speed Class)	Include Memory card (Echivalent SanDisk Extreme Pro SDXC 64 GB) Interface UHS-I capacity 64 GB Transfer Speed (READ) minim 170MB/S; Transfer Speed (WRITE) minim 90MB/S Speed Class 10(SD Speed Class), V30 (Video Speed Class)	RoHS, CE, FCC

2.4. Card Reader	CR-CFXASDX	China	Xcellon	CFexpress Type A and UHS-II SD Card Reader Media Card Reader - 1x CFexpress Type A, 1x SDXC (UHS-II [312 MB/s]) System Connection - USB-C Female [3.1/3.2 Gen 2 (10 Gb/s)] Power Source - USB Bus Power Include: USB-C to USB-C Cable and USB-C to USB-A Cable	CFexpress Type A and UHS-II SD Card Reader Media Card Reader - 1x CFexpress Type A, 1x SDXC (UHS-II [312 MB/s]) System Connection - USB-C Female [3.1/3.2 Gen 2 (10 Gb/s)] Power Source - USB Bus Power Include: USB-C to USB-C Cable and USB-C to USB-A Cable	CE, FCC
Lotul nr. 3 Crane Kit with Tripod Stand and Dolly + Pan/Tilt Head Joystick Control Box	KITE-22-ULTIMATE	India	Proaim	TELESCOPIC CAMERA JIB Jib Arm Material - High Grade Aluminum HE30 Jib Arm Shape - Octagonal Height from Ground - 5.8m Jib Arm Thickness - 3mm Jib Crane Length - 7.5m Coupling Jib Arm Sections - A union coupling design of Jib Arm is done by washer and Steel bolt and shank with external clamps as well as Pin Lock for double locking System Jib Arm Breaks down to - 7 Sections of 4' each Camera Platform Leveling - By Control Cable Stress cable - High carbon steel with electro galvanized 4mm tested wire at 800kg Multiple Alignment - Multiple user friendly alignment of Stress Cable is provided For making Jib Stand straight without any curve Max Camera Package Load Capacity - 20kg (including Pan Tilt Head) PAN TILT HEAD Pan Tilt Head Material - High Grade Aluminium Maximum Camera Package Load Capacity - 15kg Pan, tilt, roll movement - 360 degrees Speed Panning/Rotation: Minimum: 20 Sec, Maximum: 5 sec; Speed Tilting Rotation: Minimum: 1 min 33 sec, Maximum : 8 sec; Speed Rolling/Rotation: Minimum: 1 min 24 sec, Maximum: 8 sec; Motors - Three high torque DC motors 12V that rotates (pans), tilts & roll the head 360 degrees Minimum height of head - 59.69cm	TELESCOPIC CAMERA JIB Jib Arm Material - High Grade Aluminum HE30 Jib Arm Shape - Octagonal Height from Ground - 5.8m Jib Arm Thickness - 3mm Jib Crane Length - 7.5m Coupling Jib Arm Sections - A union coupling design of Jib Arm is done by washer and Steel bolt and shank with external clamps as well as Pin Lock for double locking System Jib Arm Breaks down to - 7 Sections of 4' each Camera Platform Leveling - By Control Cable Stress cable - High carbon steel with electro galvanized 4mm tested wire at 800kg Multiple Alignment - Multiple user friendly alignment of Stress Cable is provided For making Jib Stand straight without any curve Max Camera Package Load Capacity - 20kg (including Pan Tilt Head) PAN TILT HEAD Pan Tilt Head Material - High Grade Aluminium Maximum Camera Package Load Capacity - 15kg Pan, tilt, roll movement - 360 degrees Speed Panning/Rotation: Minimum: 20 Sec, Maximum: 5 sec; Speed Tilting Rotation: Minimum: 1 min 33 sec, Maximum : 8 sec; Speed Rolling/Rotation: Minimum: 1 min 24 sec, Maximum: 8 sec; Motors - Three high torque DC motors 12V that rotates (pans), tilts & roll the head 360 degrees Minimum height of head - 59.69cm	RoHS, FCC, ISED, CCC

				Maximum height of head - 63.5cm Camera Plate Size - 12x3", camera mount slot - 8" (20.32cm) JOYSTICK CONTROLLER Joystick Controller - 3-Axis Connectors - 1x 4-Pin XLR male connectors, 6 Pin XLR GRAVITY ROBUST TRIPOD STAND Weighing Capacity - On Minimum Height 250kg, on maximum height 180kg Material Used - Solid aluminum Hub Assembly Material - High Grade Aluminum HE30 Jib Stand Legs - Micro Adjustment. Stand Height when Collapsed - 82cm Stand Height when opened - 120cm Pipe dia - 42mm Dimensions - Folded: 94cm DOLLY Stand Weight - 11.320 kg Maximum Load capacity - 800kg Wheels Diameter – min. 148.7mm Wheels Thickness – min. 49.40mm Wheel Material – Polyurethane Central Distance - 72cm Height From Ground - 3.54cm Dolly Type - Three leg Floor dolly Weight - 15.2kg Included: Telescopic Jib Arm, Crane with Accessories, (3-Axis) Motorized Dutch Roll Pan Tilt Head, Camera Dolly, Gravity Robust Tripod Stand, Tools and Tool Pouch/Wrap- Complimentary, Customized Storage cases. -Warranty 2 years	Maximum height of head - 63.5cm Camera Plate Size - 12x3", camera mount slot - 8" (20.32cm) JOYSTICK CONTROLLER Joystick Controller - 3-Axis Connectors - 1x 4-Pin XLR male connectors, 6 Pin XLR GRAVITY ROBUST TRIPOD STAND Weighing Capacity - On Minimum Height 250kg, on maximum height 180kg Material Used - Solid aluminum Hub Assembly Material - High Grade Aluminum HE30 Jib Stand Legs - Micro Adjustment. Stand Height when Collapsed - 82cm Stand Height when opened - 120cm Pipe dia - 42mm Dimensions - Folded: 94cm Stand Weight - 11.320 kg DOLLY Maximum Load capacity - 400kg Wheels Diameter – min. 148.7mm Wheels Thickness – min. 49.40mm Wheel Material – Polyurethane Central Distance - 72cm Height From Ground - 22.86cm Dolly Type - Three leg Floor dolly Weight - 15.2kg Included: Telescopic Jib Arm, Crane with Accessories, (3-Axis) Motorized Dutch Roll Pan Tilt Head, Camera Dolly, Gravity Robust Tripod Stand, Tools and Tool Pouch/Wrap- Complimentary, Customized Storage cases. -Warranty 2 years	
Lotul nr. 4 Optical Disc	ODC3300R.EU	Japonia	Sony	Optical Disc Archive Cartridge Generation 2 compatible with ODS-D280U Total capacity: 3300 GB (3.3TB) Recording layer: Double sided Disc with Triple layer/side	Optical Disc Archive Cartridge Generation 2 compatible with ODS-D280U Total capacity: 3300 GB (3.3TB) Recording layer: Double sided Disc with Triple layer/side	CE, FCC, ISO 9001, RoHS

				Recording method: Land & Groove recording Recording type: Write Once Read cycle: 1,000,000 cycles Archival life: 100 year(estimated)	Recording method: Land & Groove recording Recording type: Write Once Read cycle: 1,000,000 cycles Archival life: 100 year(estimated)	
Lotul nr. 5 Ecran de proiecție	Nu se aplică	Nu se aplică	Nu se aplică	Portable projection screen provides a high-quality 4K HD viewing experience, designed for both indoor and outdoor use. It is simple to set up using the included tripod and offers a wide 160-degree viewing angle. The screen is lightweight and portable, making it convenient for various events and settings. Screen Size: 120 inches (265.6 x 149.4 cm), 16:9 aspect ratio Material: Aluminum frame, 1.2 gain surface Viewing Angle: 160 degrees Mounting: Foldable tripod and wall mount Use: Indoor and outdoor, with ground stakes included		
Lotul nr. 6 Battery Charger	Nu se aplică	Nu se aplică	Nu se aplică	Dual Simultanius Battery Charger From 8.4V to 16.8V Power Out Battery Charger Plate for Sony L and NP-F Battery Mount Types (equivalent RP-DFM50 DV) USB Output 5.1V / 2.1A Fast Charging Speed option LCD Display 12V / 24V DC In for field charging		
Lotul nr. 7						
7.1. USB Charger	Nu se aplică	Nu se aplică	Nu se aplică	4x USB-A ports Input voltage: 100 - 240V AC Max. input current: 1 A Output voltage: 5V DC Max. output current: 6 A Max. output power 30 W		
7.2. USB Charger	Nu se aplică	Nu se aplică	Nu se aplică	USB Charger 1x USB-A port; 1x USB-C port Input voltage: 100 - 240V AC Max. input current: 0.5 A Output voltage: 5 - 12V DC Max. output current: 3 A Max. output power 18 W Integrated Power Delivery (PD) and Quickcharge (QC) fast charging protocol		
7.3. USB Cable	Nu se aplică	Nu se aplică	Nu se aplică	USB 3.2 Gen 2 Cable Type A to C Length: 0.5 m		

				Supports data transfer rates up to 10GBit/s Connector A: USB 3.2 plug type A Connector B: USB 3.2 plug type C		
7.4. USB Cable	Nu se aplică	Nu se aplică	Nu se aplică	USB 3.2 Gen 2 Cable Type A to C Length: 1.0 m Supports data transfer rates up to 10GBit/s Connector A: USB 3.2 plug type A Connector B: USB 3.2 plug type C		
7.5. USB Cable	Nu se aplică	Nu se aplică	Nu se aplică	USB 3.2 Gen 2 Cable Type A to C Length: 1.5 m Supports data transfer rates up to 10GBit/s Connector A: USB 3.2 plug type A Connector B: USB 3.2 plug type C		
Lotul nr. 8 Light Meter	Nu se aplică	Nu se aplică	Nu se aplică	Meter Type Ambient, Cine, Flash, Spot Spot Metering 1° Spot Flash Metering Cordless Light Reading Method Incident, Reflected Light Readings Candelas per Meter Squared (cd/m²), Foot Lamberts (fl), Footcandle, Lux Measuring Modes Aperture Priority, FPS Metering, Flash Duration Analysis, HSS Flash, Shutter Priority Aperture Range Flash, Incident: f/0.5 to 128.9 at ISO 100; Flash, Reflected: f/1 to 128.9 at ISO 100; f/0.5 to 161.2 (1, 1/2, 1/3-Step Increments) at ISO 100 EV Range Ambient, Incident: -5 to 22.9 EV at ISO 100; Ambient, Reflected: -1 to 24.4 EV at ISO 100. ISO Range 3 to 13,107,200 (1/3-Step Increments), Plus 850 Shutter Speed Range 1/64,000 to 30 Minutes (1, 1/2, 1/3-Step Increments), Plus 1/400, 1/200 Max Flash Sync Speed 1/16,000 Illuminance Range 0.1 to 2,000,000 Lux / 0.01 to 180,000 fc Luminance Range 0.3 to 290,000 fL / 0.1 to 980,000 cd/m² Cine Speed / Shutter Angle 0.001 to 1000 fps at 1 to 358° Diffuser Adjustable Spherical to Flat Display 6.9 cm Color Touchscreen LCD Battery 2x AA		
Lotul nr. 9						

9.1. Stage Platform	Nu se aplică	Nu se aplică	Nu se aplică	Technical specs: Load capacity: 750 kg/m² Length: 2000 mm; Width: 1000 mm ; Height: 90 mm Weight: 32,00 kg New plugs for round & square feet from 48,3 to 60mm Advantages of the stage platforms: High load capacity High quality aluminium frame Easy & quick installation Compatible to many decks from other brands Compatible with existing podium Duratruss 750		
9.2. Leg set	Nu se aplică	Nu se aplică	Nu se aplică	4 pcs. fixed square stage deck legs made of aluminium. Technical specs load capacity: Height: 600 mm; Width: 60 mm; Depth: 60 mm. Compatible with existing podium Duratruss 750		
9.3. Leg set	Nu se aplică	Nu se aplică	Nu se aplică	4 pcs. fixed square stage deck legs made of aluminium. Technical specs load capacity: Height: 300 mm; Width: 60 mm; Depth: 60 mm. Compatible with existing podium Duratruss 750		

Semnat: _____ Numele, Prenumele: Popa Rodica În calitate de: Administrator
Ofertantul: “INNOVATOR REGIONAL” SRL Adresa: mun.Chișinău, str.N.M.Spătarul 19/2, ap.10, MD-2075

***Notă: Coloanele 2, 3, 4, 6, 7 se completează fără nici o abatere de la formular. Completarea defectuoasă a formularului atrage respingerea ofertei.**

