



# AERON EVO2

## UNCOOLED LWIR THERMAL FIXED AND ZOOM LENS OPTIONS:

- 55mm 25 to 75mm
- 75mm 26 to 105mm
- 100mm 25 to 150mm



Above: Aeron EVO2 26-105mm.  
Other models will vary.

The EVO2 range utilises the very latest in both thermal sensor and lens technology, providing advanced surveillance capabilities in the most extreme conditions. Available with either zoom or fixed FoV lenses, the Aeron EVO2 range also benefits from a choice of two thermal sensor resolutions; **640 x 512 (12µm)** and **XGA 1024 x 768 (12µm)**.

**FPS across both lenses 30fps adjustable as desired .**

The Aeron EVO2 is an accurate, rugged, continuous rotation dual sensor PTZ camera utilising an uncooled LWIR thermal sensor with a range of fixed lenses (up to 100mm), zoom lenses (up to 150mm), and a HD visible sensor.

The camera sensors are housed within the Aeron's rugged enclosure, which also provides fast and accurate camera positioning. Tested to an IP67 level of environmental protection and hard anodised, the Aeron can be used in the most harsh and challenging applications such as maritime, border security and vehicle mount installations.

## KEY FEATURES

- Thermal detection\* ranges up to 4.6km (human) and 14.3km (vehicle)
- Uncooled LWIR thermal sensors:
  - Fixed lens options up to 100mm
  - Zoom lens options up to 25-150mm
- Range of resolutions up to 1024 x 768 (XGA)
- Pixel pitch down to 12µm (improves range by up to 20%)
- Push autofocus as standard on selected thermal zoom lenses
- 30x zoom HD visible sensor with a wiper as standard
- 360° continuous rotation with pan and tilt speeds up to 160° per second
- High level of camera positioning accuracy: 0.01°
- Absolute feedback, virtually zero backlash with automatic self-position correction
- Compact and ruggedised for extreme and marine environments
- IP67 rating
- Mounting options include inverted, upright or inclined
- Suitable for mobile and vehicle mounted applications
- Milestone, Genetec and Avigilon VMS compatible (Xprotect Corporate)



### FLEXIBLE MOUNTING

Options include inverted, upright, or inclined



### WIPER AS STANDARD

The visible HD camera comes with a wiper as standard



### 360° ROTATION

The Aeron EVO2 offers continuous 360° rotation

\*Johnsons Criteria, Human at 1.8m x 0.5m, vehicle at 2.3m², Detection at 2 pixels, Recognition at 8 pixels and Identification at 13 pixels. 50% probability subject to environmental conditions. Based on RC4-511YJ30X-EC25Z150FW.

Specifications may be subject to change without notice.  
E&OE 10/10/2022 V4.8r1





# AERON EVO2

## UNCOOLED LWIR THERMAL FIXED / ZOOM LENS CAMERAS



Above: Aeron EVO2 26-105mm.  
Other models will vary.

### THERMAL IMAGER – 640 x 512, 12µm PIXEL PITCH

Part Number	RC4-511YJ30X-EB08FW	RC4-511YJ30X-EB05FW	RC4-511YJ30X-EB04FW	RC4-511YJ30X-EB25Z75FW	RC4-511YJ30X-EB26Z105FW	RC4-511YJ30X-EB25Z150FW
Focal Length	55mm	75mm	100mm	25 to 75mm (3x optical zoom)	26 to 105mm (4x optical zoom)	25 to 150mm (6x optical zoom)
Horizontal Field of View	8.0°	5.9°	4.4°	17.6° (W) to 5.9° (T)	16.9° (W) to 4.2° (T)	17.6° (W) to 2.9° (T)
F Number	F1.0	F1.0	F1.0	F1.2	F1.6	F1.4
Focus	Fixed	Manual		Push autofocus, manual		Manual

### THERMAL IMAGER – 1024 x 768, 12µm PIXEL PITCH

Part Number	RC4-511YJ30X-EC12FW	RC4-511YJ30X-EC09FW	RC4-511YJ30X-EC07FW	RC4-511YJ30X-EC25Z75FW	RC4-511YJ30X-EC26Z105FW	RC4-511YJ30X-EC25Z150FW
Focal Length	55mm	75mm	100mm	25 to 75mm (3x optical zoom)	26 to 105mm (4x optical zoom)	25 to 150mm (6x optical zoom)
Horizontal Field of View	12.8°	9.3°	7.0°	28.5° (W) to 9.3° (T)	27.1° (W) to 6.7° (T)	28.2° (W) to 4.7° (T)
F Number	F1.0	F1.0	F1.0	F1.2	F1.6	F1.4
Focus	Fixed	Manual		Push autofocus, manual		Manual

### THERMAL SENSOR

Sensitivity	≤50mK at 25°C, F1.0	
Detector Type	Uncooled VOx microbolometer	
Spectral Band	7.5 to 14µm (LWIR / 8 to 14µm)	
Frequency	50Hz (640 x 512 imager only)	30Hz (1024 x 768 imager only)
Digital Zoom	1x to 8x (0.1 steps) (640 x 512 imager only)	1x to 4x (0.1 steps) (1024 x 768 imager only)
Image Stabilisation	Yes, electronic (cost option)	
Image Processing	Non-Uniform Correction (NUC), noise filtering, polarity control, Digital Detail Enhancement (DDE)	
Image Control	Polarity: White hot / black hot (18x colour palettes) Orientation: Invert / revert	

### HD VISIBLE SENSOR

Focal Length	4.3 to 129mm
Image Sensor	1/2.8" CMOS Exmor (2.13MP), full HD 1080p (1920 x 1080)
F-Number	F1.6 to F4.7
Horizontal FOV	63.7° (W) to 2.32° (T)
Optical Zoom	30x
Digital Zoom	12x
Focus	Automatic, manual
Min. Sensitivity	Colour 0.01 lux, mono 0.0008 lux (high sensitivity mode)
Other Features	De-fog, digital noise reduction, WDR, image stabilisation, boresight adjustment

### AERON PAN AND TILT UNIT

Pan Range; Pan Velocity	360° Continuous; 0.01° to 160.0° per second
Tilt Range; Tilt Velocity	-30° to +90°; 0.01° to 160.0° per second (upright) -90° to +30°; 0.01° to 160.0° per second (inverted) -68° to +90°; 0.01° to 160.0° per second (inclined)
Accuracy	0.01° / 0.17 mRad
Repeatability	0.05° / 0.87 mRad
Actuation	Custom stepper motors
Interfaces	Ethernet (control + video), RS485 (control and firmware upgrade)

### PART CODES

RC4-511YJ30X-EB08FW	Aeron EVO2 with a 640x512, 12µm, 50Hz thermal camera and a 55mm, F1.0 thermal fixed lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour
RC4-511YJ30X-EB05FW	Aeron EVO2 with a 640x512, 12µm, 50Hz thermal camera and a 75mm, F1.0 thermal fixed lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour
RC4-511YJ30X-EB04FW	Aeron EVO2 with a 640x512, 12µm, 50Hz thermal camera and a 100mm, F1.0 thermal fixed lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour
RC4-511YJ30X-EB25Z75FW	Aeron EVO2 with a 640x512, 12µm, 50Hz thermal camera and a 25-75mm, autofocus, F1.2 thermal zoom lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour
RC4-511YJ30X-EB26Z105FW	Aeron EVO2 with a 640x512, 12µm, 50Hz thermal camera and a 26-105mm, autofocus, F1.6 thermal zoom lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour
RC4-511YJ30X-EB25Z150FW	Aeron EVO2 with a 640x512, 12µm, 50Hz thermal camera and a 25-150mm, F1.4 thermal zoom lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour
RC4-511YJ30X-EC12FW	Aeron EVO2 with a 1024x768, 12µm, 30Hz thermal camera and a 55mm, F1.0 thermal fixed lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour
RC4-511YJ30X-EC09FW	Aeron EVO2 with a 1024x768, 12µm, 30Hz thermal camera and a 75mm, F1.0 thermal fixed lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour
RC4-511YJ30X-EC07FW	Aeron EVO2 with a 1024x768, 12µm, 30Hz thermal camera and a 100mm, F1.0 thermal fixed lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour
RC4-511YJ30X-EC25Z75FW	Aeron EVO2 with a 1024x768, 12µm, 30Hz thermal camera and a 25-75mm, autofocus, F1.2 thermal zoom lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour
RC4-511YJ30X-EC26Z105FW	Aeron EVO2 with a 1024x768, 12µm, 30Hz thermal camera and a 26-105mm, F1.6 thermal zoom lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour
RC4-511YJ30X-EC25Z150FW	Aeron EVO2 with a 1024x768, 12µm, 30Hz thermal camera and a 25-150mm, F1.4 thermal zoom lens, and a HD, 4.3-129mm (30x optical zoom lens) video camera, white colour

### IMAGE PRESENTATION

Video Output	IP, ONVIF, RTSP (Composite (PAL / NTSC) and HD-SDI are cost options)
Video over IP	Integrated IP encoders provide simultaneous H.264 RSTP H.265 and ONVIF Profile-S

### TELEMETRY

Presets	127x Preset positions, 16x preset tours
Protocols	Pelco D, Pelco D Extended, ONVIF Profile-S
Interface	RS485, ONVIF Profile-S, Serial <-> IP RJ45 100m data network
Humidity	95 – 100%

### ELECTRICAL AND MECHANICAL

Input Voltage	Nominal 28VDC (24-32VDC)
Power Consumption	Typical: 60W, peak: 100W (with heater)
Housing Material	Anodised aluminium, white powder marine grade paint finish (other colours are available upon request)
Camera Weight	10.6kg / 23.3lb
Camera Turning Diameter	340mm / 13.40" Normal - 370mm / 14.57" offset
Height	370mm / 14.57" Normal - 340mm / 13.86" offset
Core Modules	Visible sensor boresight, wiper

### ENVIRONMENTAL

IP Rating	IP67
Temperature Range	-30°C (-22°F) up to 65°C (149°F) (-40°C with optional heater)

### OPTIONS

Automatic Tracking	Hardware based target acquisition and tracking capability
Stabilisation	Electronic image stabilisation (for the thermal sensor) cost option
Gyro	2-Axis gyro stabilisation
Thermal Imager	340 x 288 and 1280 x 1024 (HD options available upon request)
4K Visible Sensor	4K colour sensor, 4.4mm to 88.4mm lens, 20x optical zoom, 12x digital zoom, colour 0.4 lux; colour 0.06 lux (slow shutter on). Replaces the HD visible sensor
Fusion	Visible and thermal image fusion - image fusion for fixed lens thermal sensors (not available with zoom lens thermal sensors)
Storage	Up to 64GB in total via SD/MMC (32GB available per channel if using thermal and video / 2x sensors)

