



ATLANTIC 2 STROKE OILS

PRODUCT DATA

ATLANTIC X 2T 2-Stroke Motor Oil

DESCRIPTION

Atlantic X 2T MOTOR OILS are a high performance, semi synthetic, low smoke, low ash two stroke engine oil made from the latest synthetic additives and premium base oils. It exceeds many manufacturer requirements including API TC, JASO FC & ISO FG-C requirements.

APPLICATIONS

Atlantic X 2T MOTOR OILS are suitable for use in all types of two stroke engines including motorcycles, mopeds and scooters that use either a premix or oil injection system. It is suitable for use in two stroke chainsaws, brush cutters, lawn mowers and other gardening equipment in domestic and industrial use. It is also suitable for stationary engines and industrial power units. **Atlantic X 2T MOTOR OILS** should not be used in outboard engines.

PERFORMANCE FEATURES AND BENEFITS

- Reliable and consistent performance
- Self-mixing with leaded and unleaded petrol
- Low Smoke, Low Ash formulation
- Extends engine life
- Good anti-scuff properties
- Mixes readily with petrol
- Meets the requirements of leading manufacturers
- Enhanced lubricity and detergency, keeping engines clean
- Maximizes spark plug life
- Reduces exhaust port blockages
- Keeps piston rings free from deposits
- Suitable both for all oil-injection and premix systems

INDUSTRY SPECIFICATIONS: API TC, JASO FC, ISO EG-C

ATLANTIC 2T SPECIAL Premium Fully Synthetic Two-Stroke Engine Oil

DESCRIPTION

Atlantic X 2T Special is advanced, fully synthetic 2-stroke engine oil for use in modern, high speed, high performance 2 stroke engines. Its fast burn, high protection formula is designed to release the full potential from highly tuned motorcycle engines with enhanced throttle response for faster acceleration to give ultimate performance for extreme riding.

APPLICATIONS

Atlantic X 2T Special is suitable for all modern, high performance 2-stroke motorcycle engines from European and Japanese manufacturers. It is designed for two stroke engines used in motorcycles on road or in competition both oil injection and pre-mix lubrication, as per manufacturers' instructions, up to a fuel/oil ratio of 50:1. Suitable for use in lawn mowers, chainsaws.

PERFORMANCE FEATURES AND BENEFITS

- Fully Synthetic 2-stroke motorcycle engine oil
- Environmentally Friendly - low smoke, biodegradable
- Excellent engine cleanliness
- Exceptional resistance to seizure
- Extends engine life
- Superior anti scuff properties
- Fast burning, high protection formula
- Faster acceleration from the start
- Synthetic protection
- Reduces exhaust port blockages
- Keeps piston rings free
- Exceeds OEM warranty requirements

INDUSTRY SPECIFICATIONS: API TC, JASO FD, ISO EG-D

TYPICAL TECHNICAL PROPERTIES

	2T	2T Special
Product code	12441A _L	12442A _L
Density at 15°C, g/ml, ASTM D4052	0.872	0.855
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	63.2	39
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	8.9	7.8
Viscosity Index, ASTM D2270	116	175
Flash Point(COC), °C, ASTM D92	122	74
Pour Point, °C, ASTM D97	-21	-51
Colour	RED	RED

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.



Packing : 25ml | 500ml | 800ml | 1L

ATLAD02/AL012/07, 10.08.10, Page 1/1
*supersedes all previous versions

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.

