

Motor ventilator unitate interioara	Model		ZKFP-30-8-3
	lesire	W	36.0
	Condensator	uF	/
	Viteza (Hi/Mi/Lo)	r/min	1130 / 900 / 800
Serpentina unitate interioara	a. Numar de randuri		2.0
	b. Pas tub(a)x pas rand(b)	mm	21x13.37
	c. Distanta aripioare	mm	1.2
	d. Tip aripioare (cod)		Aluminiu hidrofilic
	e. Diametru ext. tub si tip	mm	Φ7, canal interior tub
	f. Lungime x inaltime x latime serpentina	mm	750x189x26.74+750x105x26.74
	g. Numar circuite		3
Debit aer unitate interioara (Hi/Mi/Lo)		m3/h	840/680/540
Nivel zgomot unitate interioara (Hi/Mi/Lo/Si)		dB(A)	42.5/36/26
Nivel zgomot unitate interioara (Hi)		dB(A)	56
Unitate interioara	Dimensiuni(W*D*H)	mm	957x213x302
	Ambalare (W*D*H)	mm	1035x295x385
	Masa neta/bruta	Kg	10/13
Motor ventilator unitate interioara	Model		ZKFN-34-10-1-3
	lesire	W	/
	Condensator	uF	/
	Viteza (Hi/Mi/Lo)	r/min	740/650
Serpentina unitate exterioara	a. Numar de randuri		2.0
	b. Pas tub(a)x pas rand(b)	mm	21x22
	c. Distanta aripioare	mm	1.3
	d. Tip aripioare (cod)		Aluminiu hidrofilic
	e. Diametru ext. tub si tip	mm	Φ7, canal interior tub
	f. Lungime x inaltime x latime serpentina	mm	860*504*44
	g. Numar circuite		4
Debit aer unitate exterioara		m3/h	2100
Nivel zgomot unitate exterioara		dB(A)	56
Nivel max. zgomot unitate exterioara		dB(A)	63
Unitate exterioara	Dimensiuni(W*D*H)	mm	805x330x554
	Ambalare (W*D*H)	mm	915x370x615
	Masa Neta/bruta	Kg	32.7/35.4
Refrigerant	tip		R32
	GWP		675
	Cantitate incarcare	Kg	1.08
Presiune proiectata		MPa	4.3/1.7
Conducte refrigerant	Lateral lichid/ lateral gaz	mm(inch)	6.35mm(1/4in)/12.7mm(1/2in)
	Lungime max. conducta refrigerant	m	30
	Diferenta max. de nivel	m	20
Conexiuni cablaj			1.5x5//
Tip stecher			//fara
Tip termostat			Comanda de la distanta
Temperatura lucru	Unitate interioara(racire/ incalzire)	℃	17~32/0~30
	Unitate exterioara(racire/ incalzire)	℃	-15~50/-15~30
Domeniu aplicare	minim-maxim	m2	24~35

Caracteristici principale

-  **Racire si incalzire**  **Control prin WIFI**
-  **Funcție Follow me**  **Auto curatare**
-  **Auto restart**  **Mod noapte (Sleep mode)**

CONTER

breeze

POWERED BY

Midea®

ISO 9001
BUREAU VERITAS
Certification

