

## SPECIFICAȚII TEHNICE (F4.1)

Numărul licitației: ocds-b3wdp1-MD-1557838810064 din 14.05.2019	Data: 23.05.2019	
Denumirea licitației: Dispozitive pentru sistemul de videomonitorizare	Lot: <b>1, 2, 3</b>	Pagina 1 din 5

#	Codul CPV	Denumirea bunurilor și/sau a serviciilor	Modelul articolului	Tara de origine	Producator	Specificarea tehnică deplină solicitată	Specificarea tehnică deplină propusă de către ofertant	Standard de referinta
1		2	3	4	5	6	7	
1	<b>Lotul nr.1 Echipament videomonitorizare (Camere video IP + Registrator video IP (NVR)+ HDD)</b>							
1.1	32330000-5	Camere video IP interioare 4Mpx, 2.8mm CUBE	DS-2CD2443G O-I	China	Hikvision	<ul style="list-style-type: none"> <li>2688 x 1520 @ 30fps 4 megapixel resolution; Image Sensor 1/3"</li> <li>WDR 120dB</li> <li>Built-in Micro SD/ up to 128 GB</li> <li>IR range approx. 10 meters</li> <li>Built-in microphone and speaker</li> <li>Support PIR(Passive Infrared Detection)</li> <li>Functii inteligente (Support intrusion detection, line crossing detection, motion detection)</li> <li>Video Compression H265+</li> <li>Lens 2.8mm; -10°Cto+60°C</li> <li>Tip carcasei "CUBE"</li> <li>Material - Metal &amp; Plastic</li> </ul>	<ul style="list-style-type: none"> <li>2688 x 1520 @ 30fps 4 megapixel resolution; Image Sensor 1/3"</li> <li>WDR 120dB</li> <li>Built-in Micro SD/ up to 128 GB</li> <li>IR range approx. 10 meters</li> <li>Built-in microphone and speaker</li> <li>Support PIR(Passive Infrared Detection)</li> <li>Functii inteligente (Support intrusion detection, line crossing detection, motion detection)</li> <li>Video Compression H265+</li> <li>Lens 2.8mm; -10°Cto+60°C</li> <li>Tip carcasei "CUBE"</li> <li>Material - Metal &amp; Plastic</li> </ul>	-
1.2	32330000-5	Camere video IP exterioare 4Mpx, 4 mm Dome	DS-2CD2347G 3E-L	China	Hikvision	<ul style="list-style-type: none"> <li>25fps (2688 * 1520) 4 megapixel resolution</li> <li>Image Sensor 1/1.8"</li> <li>0.0014 @ (F1.0, AGC ON), 0 Lux with Light</li> <li>WDR 120dB</li> <li>IMAGINE IN CULORI 24/24</li> <li>Functii SMART (Line crossing detection, intrusion detection, object removal detection, unattended baggage detection)</li> <li>Face Detection Yes</li> <li>VideoBitRate 32 Kbps to 16 Mbps</li> <li>Built-in Micro SD/ up to 128 GB</li> <li>IR range approx. 40 meters</li> <li>Video Compression H265+</li> <li>Lens 4mm; 1P67, PoE; -30 °C to +60 °C</li> <li>Tip carcasei DOME</li> <li>Material - Metal &amp; Plastic</li> </ul>	<ul style="list-style-type: none"> <li>25fps (2688 * 1520) 4 megapixel resolution</li> <li>Image Sensor 1/1.8"</li> <li>0.0014 @ (F1.0, AGC ON), 0 Lux with Light</li> <li>WDR 120dB</li> <li>IMAGINE IN CULORI 24/24</li> <li>Functii SMART (Line crossing detection, intrusion detection, object removal detection, unattended baggage detection)</li> <li>Face Detection Yes</li> <li>VideoBitRate 32 Kbps to 16 Mbps</li> <li>Built-in Micro SD/ up to 128 GB</li> <li>IR range approx. 40 meters</li> <li>Video Compression H265+</li> <li>Lens 4mm; 1P67, PoE; -30 °C to +60 °C</li> <li>Tip carcasei DOME</li> <li>Material - Metal &amp; Plastic</li> </ul>	

1.3	32330000-5	Camere video IP exterioare 4Mpx, 2.8mm Bullet	DS- 2CD2043G O-I	China	Hikvision	<ul style="list-style-type: none"> <li>• 4 megapixel resolution (2560 x 1440) 20fps</li> <li>• Image Sensor 1/3"</li> <li>○ Lux @(F1.2, AGC ON), 0.028 Lux</li> <li>• Video Bit Rate 32 Kbps to 8 Mbps</li> <li>• IR range approx. 30 meters</li> <li>• Video Compression H265+</li> <li>• Lens 2.8mm; IP67, PoE; -30 °C to +60 °C</li> <li>• Tip carcasei BULLET</li> <li>• Material - Metal &amp; Plastic</li> </ul>	<ul style="list-style-type: none"> <li>• 4 megapixel resolution (2560 x 1440) 20fps</li> <li>• Image Sensor 1/3"</li> <li>○ Lux @(F1.2, AGC ON), 0.028 Lux</li> <li>• Video Bit Rate 32 Kbps to 8 Mbps</li> <li>• IR range approx. 30 meters</li> <li>• Video Compression H265+</li> <li>• Lens 2.8mm; IP67, PoE; -30 °C to +60 °C</li> <li>• Tip carcasei BULLET</li> <li>• Material - Metal &amp; Plastic</li> </ul>	
1.4	32330000-5	Camere video IP interioare 4Mpx, 2,8mm dome	DS- 2CD1143G O-I 2,8MM	China	Hikvision	<ul style="list-style-type: none"> <li>• 4 megapixel resolution (2560 x 1440) 20fps</li> <li>• Image Sensor 1/3"</li> <li>• 0.01 Lux@(F1.2, AGCON), 0.028 Lux</li> <li>• Video Bit Rate 32 Kbps to 8 Mbps</li> <li>• IR range approx. 30 meters</li> <li>• Video Compression H265+</li> <li>• Lens 2.8mm; IP67, PoE; -30 °C to +60 °C</li> <li>• Tip carcasei DOME</li> <li>• Material - Metal &amp; Plastic</li> </ul>	<ul style="list-style-type: none"> <li>• 4 megapixel resolution (2560 x 1440) 20fps</li> <li>• Image Sensor 1/3"</li> <li>• 0.01 Lux@(F1.2, AGCON), 0.028 Lux</li> <li>• Video Bit Rate 32 Kbps to 8 Mbps</li> <li>• IR range approx. 30 meters</li> <li>• Video Compression H265+</li> <li>• Lens 2.8mm; IP67, PoE; -30 °C to +60 °C</li> <li>• Tip carcasei DOME</li> <li>• Material - Metal &amp; Plastic</li> </ul>	
1.5	32330000-5	Camere video IP interioare 4Mpx, 4mm dome	DS- 2CD1143G O-I 4MM	China	Hikvision	<ul style="list-style-type: none"> <li>• 4 megapixel resolution (2560 x 1440) 20fps</li> <li>• Image Sensor 1/3"</li> <li>• 0.01 Lux @(F1.2, AGC ON), 0.028 Lux</li> <li>• Video Bit Rate 32 Kbps to 8 Mbps</li> <li>• IR range approx. 30 meters</li> <li>• Video Compression H265+</li> <li>• Lens 4mm; IP67, PoE; -30 °C to +60 °C</li> <li>• Tip carcasei DOME</li> <li>• Material - Metal &amp; Plastic</li> </ul>	<ul style="list-style-type: none"> <li>• 4 megapixel resolution (2560 x 1440) 20fps</li> <li>• Image Sensor 1/3"</li> <li>• 0.01 Lux @(F1.2, AGC ON), 0.028 Lux</li> <li>• Video Bit Rate 32 Kbps to 8 Mbps</li> <li>• IR range approx. 30 meters</li> <li>• Video Compression H265+</li> <li>• Lens 4mm; IP67, PoE; -30 °C to +60 °C</li> <li>• Tip carcasei DOME</li> <li>• Material - Metal &amp; Plastic</li> </ul>	
1.6	32330000-5	Registrator video IP (NVR), 32- canale, HDD 24Tb	DS-7632NI- K2	China	Hikvision	<ul style="list-style-type: none"> <li>• Nr. canale: 32</li> <li>• Recording resolution 8MP/6MP/5MP/4MP/3MP/1080p</li> <li>• Synchronous playback 16 canale</li> <li>• Functia ANR</li> <li>• Compresie video: H.265+/H.264</li> <li>• Interfata video: HDMI+VGA, simultan</li> <li>• Incoming Bandwidth: min. 256 Mbps</li> <li>• Outgoing bandwidth: min 160 Mbps</li> <li>• Stocare: 2 SATA III Port, Up to 6 TB capacity for each HDD</li> <li>• Support Smart Detection Alarm</li> <li>• Support Smart Search Playback</li> <li>• Porturi Auxiliare: USB</li> <li>• Alarm in/out(4/1)</li> <li>• Network: 2 RJ-45 Ports(10/100/1000Mbps)</li> <li>• Network Function: HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE,DDNS, FTP.</li> <li>• Power: DC 12V</li> </ul>	<ul style="list-style-type: none"> <li>• Nr. canale: 32</li> <li>• Recording resolution 8MP/6MP/5MP/4MP/3MP/1080p</li> <li>• Synchronous playback 16 canale</li> <li>• Functia ANR</li> <li>• Compresie video: H.265+/H.264</li> <li>• Interfata video: HDMI+VGA, simultan</li> <li>• Incoming Bandwidth: min. 256 Mbps</li> <li>• Outgoing bandwidth: min 160 Mbps</li> <li>• Stocare: 2 SATA III Port, Up to 6 TB capacity for each HDD</li> <li>• Support Smart Detection Alarm</li> <li>• Support Smart Search Playback</li> <li>• Porturi Auxiliare: USB</li> <li>• Alarm in/out(4/1)</li> <li>• Network: 2 RJ-45 Ports(10/100/1000Mbps)</li> <li>• Network Function: HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE,DDNS, FTP.</li> <li>• Power: DC 12V</li> </ul>	

1.7	32330000-5	HDD 3.5" 6,0TB-SATA- 64MB	ST6000VX 0003	China	Seagate	<ul style="list-style-type: none"> <li>• Capacitate stocare: 6TB</li> <li>• Interfață: SATA III; Cache: 64Mb</li> <li>• Form factor: 3,5"</li> <li>• Specializat pentru sisteme de supraveghere 24/24</li> </ul>	<ul style="list-style-type: none"> <li>• Capacitate stocare: 6TB</li> <li>• Interfață: SATA III; Cache: 64Mb</li> <li>• Form factor: 3,5"</li> <li>• Specializat pentru sisteme de supraveghere 24/24</li> </ul>		
1.8	32330000-5	Bloc alimentare DC 12V, 10A	Power supply 12V 10A	China		<ul style="list-style-type: none"> <li>• Tensiune: 12V; Amperaj: 10 A</li> <li>• Radiator; Carcasă metalică forată</li> <li>• Montabil prin înșurubare</li> </ul>	<ul style="list-style-type: none"> <li>• Tensiune: 12V; Amperaj: 10 A</li> <li>• Radiator; Carcasă metalică forată</li> <li>• Montabil prin înșurubare</li> </ul>		
1.9	32330000-5	Conector DC/M	PigTail Conector DC Plug 2.1	China		Conector de alimentare, echipat cu terminale.	Conector de alimentare, echipat cu terminale.		
1.10	32330000-5	Cutie distributie 100X100		China		<ul style="list-style-type: none"> <li>• Carcasă plastic; Dimensiuni 100*100mm</li> </ul>	<ul style="list-style-type: none"> <li>• Carcasă plastic; Dimensiuni 100*100mm</li> </ul>		
2	<b>Lotul nr.2 Echipamente de rețea(switch-uri, cabluri, conecitoare)</b>								China
2.1	32330000-5	Managed Switch 8-port Gigabit L2 + 2xSFP	T2500G- 10TS(TL- SG3210)	China	TP-Link	<p><b>Standarde și Protocoale:</b> IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE 802.3ad, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1x, IEEE 802.1p</p> <p><b>Interfață:</b> 8 10/100/1000Mbps RJ45 ports (Auto Negotiation/Auto MDI/MDIX) 2 Gigabit SFP Slots 1 RJ45 Console Port 1 Micro-USB Console Port</p> <p><b>Rețea nedia:</b> 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000Base-T: UTP category 5, 5e, 6 or above cable (maximum 100m) 1000BASE-X: MMF, SMF</p> <p><b>Sursă Alimentare:</b> 100~240VAC, 50/60Hz</p> <p><b>Bandwidth/Backplane:</b> 20Gbps</p> <p><b>Packet Forwarding Rate:</b> 14.9Mpps <b>Management:</b> Web-based GUI and CLI management SNMP v1/v2c/v3, compatible with public MIBs and TP-LINK private MIBs RMON (1, 2, 3, 9 groups) DHCP/BOOTP Client, DHCP Snooping, DHCP Option82 CPU Monitoring Port Mirroring Dual Image Time Setting: SNTP Integrated NDP/NTDP feature Firmware Upgrade: TFTP &amp; Web System Diagnose: VCT SYSLOG &amp; Public MIBS</p> <p><b>Cerințe de sistem:</b> Microsoft® Windows® 10, 8, 7, Vista™, XP or MAC® OS, NetWare®, UNIX® or Linux.</p> <p><b>Alimentare:</b> 220V AC</p>	<p><b>Standarde și Protocoale:</b> IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE 802.3ad, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1x, IEEE 802.1p</p> <p><b>Interfață:</b> 8 10/100/1000Mbps RJ45 ports (Auto Negotiation/Auto MDI/MDIX) 2 Gigabit SFP Slots 1 RJ45 Console Port 1 Micro-USB Console Port</p> <p><b>Rețea nedia:</b> 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000Base-T: UTP category 5, 5e, 6 or above cable (maximum 100m) 1000BASE-X: MMF, SMF</p> <p><b>Sursă Alimentare:</b> 100~240VAC, 50/60Hz</p> <p><b>Bandwidth/Backplane:</b> 20Gbps</p> <p><b>Packet Forwarding Rate:</b> 14.9Mpps <b>Management:</b> Web-based GUI and CLI management SNMP v1/v2c/v3, compatible with public MIBs and TP-LINK private MIBs RMON (1, 2, 3, 9 groups) DHCP/BOOTP Client, DHCP Snooping, DHCP Option82 CPU Monitoring Port Mirroring Dual Image Time Setting: SNTP Integrated NDP/NTDP feature Firmware Upgrade: TFTP &amp; Web System Diagnose: VCT SYSLOG &amp; Public MIBS</p> <p><b>Cerințe de sistem:</b> Microsoft® Windows® 10, 8, 7, Vista™, XP or MAC® OS, NetWare®, UNIX® or Linux.</p> <p><b>Alimentare:</b> 220V AC</p>	-	
2.2	32330000-5	Switch 8-port Gigabit + 1xSFP	TL-SL2210	China	TP-Link	<ul style="list-style-type: none"> <li>• Viteza portului - 10/100/1000 Mbit/s</li> <li>• interfețe 1 port RJ45 pentru consola</li> <li>• Porturi RJ-45 totale - 9</li> </ul>	<ul style="list-style-type: none"> <li>• Viteza portului - 10/100/1000 Mbit/s</li> <li>• interfețe 1 port RJ45 pentru consola</li> <li>• Porturi RJ-45 totale - 9</li> </ul>		

						<ul style="list-style-type: none"> <li>• Numărul de porturi de 1000 Mbit - 1</li> <li>• Număr de porturi optice - 1</li> <li>• Sprijin pentru PoE - nu</li> <li>• Caracteristici suplimentare</li> <li>• SSH v1 / v2 SSL v2 / v3 / TLSv1</li> <li>• Controlul protecției portului Broadcast / Multicast / unknow-unicast</li> </ul>	<ul style="list-style-type: none"> <li>• Numărul de porturi de 1000 Mbit - 1</li> <li>• Număr de porturi optice - 1</li> <li>• Sprijin pentru PoE - nu</li> <li>• Caracteristici suplimentare</li> <li>• SSH v1 / v2 SSL v2 / v3 / TLSv1</li> <li>• Controlul protecției portului Broadcast / Multicast / unknow-unicast</li> </ul>	
2.3	32330000-5	Switch 16-port Gigabit	TL-SG1016D	China	TP-Link	<ul style="list-style-type: none"> <li>• Porturi: 16</li> <li>• Standarde: IEEE 802.3ab 1000BaseT IEEE 802.3az Energy Efficient Ethernet IEEE 802.3u 100BaseTX</li> <li>• IEEE 802.3 10BaseT</li> <li>• Management: Fara Management</li> <li>• Conectivitate: RJ-45 Ports: 16 Transmission Media: 10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP 1000BaseT Cat. 5E UTP/STP Alimentare: 220V AC</li> </ul>	<ul style="list-style-type: none"> <li>• Porturi: 16</li> <li>• Standarde: IEEE 802.3ab 1000BaseT IEEE 802.3az Energy Efficient Ethernet IEEE 802.3u 100BaseTX</li> <li>• IEEE 802.3 10BaseT</li> <li>• Management: Fara Management</li> <li>• Conectivitate: RJ-45 Ports: 16 Transmission Media: 10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP 1000BaseT Cat. 5E UTP/STP Alimentare: 220V AC</li> </ul>	
2.4	32330000-5	Switch 8-port Gigabit	TL-SG1008D	China	TP-Link	<ul style="list-style-type: none"> <li>• Porturi: 8</li> <li>• Standarde: IEEE 802.3ab 1000BaseT IEEE 802.3az Energy Efficient Ethernet IEEE 802.3u 100BaseTX</li> <li>• IEEE 802.3 10BaseT</li> <li>• Management: Fara Management</li> <li>• Conectivitate: RJ-45 Ports: 8 Transmission Media: 10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP 1000BaseT Cat. 5E UTP/STP Alimentare: 220V AC</li> </ul>	<ul style="list-style-type: none"> <li>• Porturi: 8</li> <li>• Standarde: IEEE 802.3ab 1000BaseT IEEE 802.3az Energy Efficient Ethernet IEEE 802.3u 100BaseTX</li> <li>• IEEE 802.3 10BaseT</li> <li>• Management: Fara Management</li> <li>• Conectivitate: RJ-45 Ports: 8 Transmission Media: 10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP 1000BaseT Cat. 5E UTP/STP Alimentare: 220V AC</li> </ul>	
2.5	32330000-5	Media Converter	11SZ-A20	China	Noname	<ul style="list-style-type: none"> <li>• Porturi optice: 1 port 100Base-FX</li> <li>• Porturi Fast Ethernet: 1 port 10/100Mbps</li> <li>• Standarde: IEEE 802.3ab 1000BaseT IEEE 802.3az Energy Efficient Ethernet IEEE 802.3u 100BaseTX</li> <li>• IEEE 802.3 10BaseT</li> <li>• Lungime de Undă: 13 10nm Tx/1550nm Rx</li> <li>• Transmisie prin fibră optică: max 20km</li> <li>• Carcasă: metalică</li> <li>• Alimentare: Adaptor alimentare extern inclus!</li> </ul>	<ul style="list-style-type: none"> <li>• Porturi optice: 1 port 100Base-FX</li> <li>• Porturi Fast Ethernet: 1 port 10/100Mbps</li> <li>• Standarde: IEEE 802.3ab 1000BaseT IEEE 802.3az Energy Efficient Ethernet IEEE 802.3u 100BaseTX</li> <li>• IEEE 802.3 10BaseT</li> <li>• Lungime de Undă: 13 10nm Tx/1550nm Rx</li> <li>• Transmisie prin fibră optică: max 20km</li> <li>• Carcasă: metalică</li> <li>• Alimentare: Adaptor alimentare extern inclus!</li> </ul>	
2.6	32330000-5	Conector RJ-45		China	LSS	conectorul modular 8P8C utilizat în Ethernet și alte legături de date	conectorul modular 8P8C utilizat în Ethernet și alte legături de date	
2.7	32330000-5	Cablu UTP Cat.5, CU		China	LSS	<ul style="list-style-type: none"> <li>• Model CAT5, Tip UTP</li> <li>• Dimensiuni 4*2*0,5 lmm, numar de fire - 8</li> <li>• Tip material - cupru, culoarea - alb</li> </ul>	<ul style="list-style-type: none"> <li>• Model CAT5, Tip UTP</li> <li>• Dimensiuni 4*2*0,5 lmm, numar de fire - 8</li> <li>• Tip material - cupru, culoarea - alb</li> </ul>	
2.8	32330000-5	Cablu extern FTP-5e 4x2x1/0.5CU + tros		China	LSS	<ul style="list-style-type: none"> <li>• Model CAT5, Tip FTP cu tros</li> <li>• Dimensiuni 4*2*0,51 mm, numar de fire - 8</li> <li>• Tip material - cupru, culoarea - negru</li> </ul>	<ul style="list-style-type: none"> <li>• Model CAT5, Tip FTP cu tros</li> <li>• Dimensiuni 4*2*0,51 mm, numar de fire - 8</li> <li>• Tip material - cupru, culoarea - negru</li> </ul>	
2.9	32330000-5	Cablu Optic 8 fire, m				<ul style="list-style-type: none"> <li>• Lungime de unda 1310nm...1550nm;</li> <li>• Temperatura de lucru: -40C - +70 °C;</li> <li>• Greutate cablu (kg/km): Approx. 45 kg/km - 55kg/km;</li> <li>• Diametru exterior: Approx. 7.0mm (2...12) — 8.0mm (16,24).</li> </ul>	<ul style="list-style-type: none"> <li>• Lungime de unda 1310nm...1550nm;</li> <li>• Temperatura de lucru: -40C - +70 °C;</li> <li>• Greutate cablu (kg/km): Approx. 45 kg/km - 55kg/km;</li> <li>• Diametru exterior: Approx. 7.0mm (2...12) — 8.0mm (16,24).</li> </ul>	

2.10	32330000-5	Canal Cablu 20*10				<ul style="list-style-type: none"> <li>• Canal pentru cablu 20*10*2000mm</li> <li>• Culoarea - alb</li> </ul>	<ul style="list-style-type: none"> <li>• Canal pentru cablu 20*10*2000mm</li> <li>• Culoarea - alb</li> </ul>	
3	<b>Lotul nr.3 Echipamente periferice</b>							
3.1	32330000-5	Monitor 24", 1920x1080, LED, HDMI, VGA	GL2460H M	China	BenQ	<ul style="list-style-type: none"> <li>• Ecran diagonal 24 " Rezoluția ecranului 1920 x 1080 Raportul aspectului 16: 9 Tipul de tip matrice TFT strălucire 250 cd / m2 contrast 1000: 1 Contrast dinamic 10M: 1 Matricea timpului de reacție 1 ms interfețe 1 x HDMI, 1 x VGA (D-Sub), 1 x DVI Consumul de energie (în timpul funcționării) 16 W , culoare negru</li> </ul>	<ul style="list-style-type: none"> <li>• Ecran diagonal 24 " Rezoluția ecranului 1920 x 1080 Raportul aspectului 16: 9 Tipul de tip matrice TFT strălucire 250 cd / m2 contrast 1000: 1 Contrast dinamic 10M: 1 Matricea timpului de reacție 1 ms interfețe 1 x HDMI, 1 x VGA (D-Sub), 1 x DVI Consumul de energie (în timpul funcționării) 16 W , culoare negru</li> </ul>	-
3.2	32330000-5	Mouse USB	RX-110	China	SVEN	<ul style="list-style-type: none"> <li>• Mouse, interfața USB</li> </ul>	Mouse, interfața USB	-
3.3	32330000-5	Keyboard	Standard 303	China	SVEN	<ul style="list-style-type: none"> <li>• Claviatură QWERTY, interfața USB</li> </ul>	Claviatură QWERTY, interfața USB	-

Semnat:  Numele, prenumele: Victor Baciu În calitate de: Administrator

Ofertantul: SC Rapid Link SRL Adresa: mun. Chisinau, MD-2028, str. Gh. Asachi 71/7