



Class II A2 Biological Safety Cabinet



BSC-700IIA2-Z/11231BBC86
Button Screen Type

BSC-700IIA2-Z
Color Touch Screen Type



Button Screen
Large LCD display is easy to monitor all the safety parameters at a glance; and ergonomically sized control panel improves users interface.



Color Touch Screen
Touch operation, real-time and clearer display of various values and appointment timing function.



Work Zone
Work zone is made of 304 stainless steel, is surrounded by negative pressure.



Waterproof Socket
2 waterproof sockets are located in the side panel, for optimum convenience of using small devices inside the cabinet.



Remote Control
All functions can be realized with it, making the operation much easier and convenient.



UV Lamp
Emission of 253.7 nanometers for most efficient decontamination.

ADVANTAGE

1. Small dimension, save space.
2. Centrifugal fan, speed adjustable; H14 HEPA filter.
3. Motorized front window: The front window is motorized for convenient, one-hand operation.
4. Audio and visual alarm: Abnormal airflow velocity, Filter replacement, Front window at unsafe height, High filter pressure alarm.
5. Time reserve function: This can save 30 minutes waiting time after activating the cabinet and the sterilization time after experiment.
6. Remote control: Each function can be realized 6 meters away from the cabinet by remote control, which can protect the operator under emergency.
7. Large LCD display: Operators can check detailed status of the cabinet, such as inflow and downflow velocity, work area temperature and humidity, filter pressure, UV working time and filter working time, filter life indicator etc.
8. With memory function in case of power-failure.
9. Interlock function: UV lamp and front window; UV lamp and blower, LED lamp; blower and front window.

TECHNICAL PARAMETERS

Model	BSC-700IIA2-Z	11231 BBC 86
External Size(W*D*H)	700*650*1230mm(without base stand)	
Internal Size(W*D*H)	600*500*540mm	
Tested Opening	Safety height 200mm(8")	
Max Opening	370mm(15")	
Inflow Velocity	0.53±0.025m/s	
Down Flow Velocity	0.33±0.025m/s	
HEPA Filter	Two, 99.995% efficiency at 0.3µm. Filter life indicator	
Front Window	Motorized. Single Layer toughened glass 5mm. Anti UV.	
Noise	≤ 67dB	
UV Lamp	15W*1 UV timer, UV life indicator, emission of 253.7 nanometers for most efficient decontamination	
LED Lamp	8W*2	
Illumination	≥1000Lux	
Consumption	700W	
Socket	Two, total load of two sockets: 500W	
Display	LCD display	
Control System	Microprocessor	
Airflow System	70% air recirculation, 30% air exhaust	
Visual and Audio Alarm	Filter replacement, window over height, abnormal air flow velocity; High filter pressure alarm.	
Material	Work Zone: 304 stainless steel. Main Body: Cold-rolled steel with anti-bacteria powder coating	
Work Surface Height	750mm with optional base stand	
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	
Standard Accessory	LED lamp*2, UV lamp*1, Remote control, Waterproof sockets*2	
Optional Accessory	SS Water tap*1, SS Gas tap*1, Base stand	
Packing Size (without base stand)	Carton: 757*820*1280mm	Carton: 730*787*1450mm Wood: 860*780*1420mm
Gross Weight (without base stand)	Carton: 121kg	Carton: 120kg Wood: 140kg
Package Size(with base stand)	Carton: 860*800*1450mm	Carton: 850*787*1450mm Wood: 860*970*1420mm
Gross Weight (with base stand)	Carton: 141kg	Carton: 140kg Wood: 160kg