

9.00R20



SP901



SP907



SP908



SP912

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX.LOAD(kg)	PRESSURE(kPa)
SP901	7.00	16PR	144/142	K	15.5	2800/2650	900
SP907	7.00	16PR	144/142	K	15.5	2800/2650	900
SP908	7.00	16PR	144/142	K	16.5	2800/2650	900
SP912	7.00	16PR	144/142	K	17.5	2800/2650	900

14.00R20



SP307



SP309



SP321

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX.LOAD(kg)	PRESSURE(kPa)
SP307	10.00	20PR	164/161	J	20	5000/4625	790
SP309	10.00	20PR	164/161	J	20	5000/4625	790
SP321	10.00	20PR	164/161	J	20	5000/4625	790

16.00R20



SP309

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX.LOAD(kg)	PRESSURE(kPa)
SP309	11.25	22PR	174/171	G	20.5	6700/6150	760

12.5R20



SP319



SP329

PATTERN	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX.LOAD(kg)	PRESSURE(kPa)
SP319	11.00	18PR	145	L	16.9	3250	650
SP329	11.00	18PR	145	L	16.9	3250	650