

RB2011UiAS-2HnD-IN

RouterBOARD 2011UiAS-2HnD has most features and interfaces from all our Wireless routers. It's powered by the new Atheros 600MHz 74K MIPS network processor, has 128MB RAM, five Gigabit LAN ports, five Fast Ethernet LAN ports and SFP cage (SFP module not included!). Also, it features powerful (up to 1W!) dual chain 2.4Ghz 802.11bgn wireless, RJ45 serial port, full size USB port and RouterOS L5 license.

RB2011UiAS-2HnD-IN comes with desktop enclosure, two indoor antennas for wireless, power supply and touchscreen LCD panel.

General specifications	
CPU	Atheros AR9344 600MHz
Memory	128MB DDR2 SDRAM onboard memory
Ethernet	Five 10/100 Mbit Fast Ethernet ports with Auto-MDIX Five 10/100/1000 Mbit Gigabit Ethernet ports with Auto-MDIX
Wireless	AR9344, built in 2GHz dual chain 802.11b/g/n wireless device Also includes two 4dBi swivel antennas
Wireless regulations	Specific frequency range may be limited by country regulations
Expansion	One fixed Gigabit Ethernet SFP cage (Mini-CBIC, SFP module not included)
Extras	Reset button, Reset jumper, RJ45 serial port, LCD panel, Temperature and Voltage sensors, USB connector, Beeper
Power input	Jack 8-28V DC; POE: 8-28V DC on Ether1 (Non 802.3af), 11W max consumption
Power output	500mA on Port 10
Dimensions	230x90x25mm, Weight (board with LCD): 233g
Operating temperature	-40°C to 60°C
Operating System	MikroTik RouterOS, L5 license
Package includes	RB2011, 24V 1.2A power adapter

Feature / Model		2011UiAS-2HnD-IN	
Enclosure		Desktop	
SFP port		Yes	
Serial port		Yes	
USB		Yes	
Wireless		Yes	
Antennas		2x built in 4dBi swivel	
LCD display		Yes	

	802.11b/g	RX Sensitivity	TX Power	802.11n	RX Sensitivity
1Mbit	-96	MCS0/8 20MHz	30dBm	MCS0/8 20MHz	-95
11Mbit	-80	MCS0/8 40MHz	28dBm	MCS0/8 40MHz	-92
6Mbit	-96	MCS7/15 20MHz	30dBm	MCS7/15 20MHz	-76
54Mbit	-80	MCS7/15 40MHz	27dBm	MCS7/15 40MHz	-73



24V 1.2A Adapter

