

Technical Data

Applicable Syringe Size	2/3ml, 5ml, 10ml, 20ml, 30ml, 50/60ml	
Rate	2/3ml:0.01~60ml/h 10ml:0.01~300ml/h 30ml:0.01~900ml/h	5ml:0.01~150ml/h 20ml:0.01~600ml/h 50ml:0.01~2200ml/h
Bolus Rate & Volume	2/3ml:0.01~60ml/h 5ml:0.01~150ml/h 10ml:0.01~300ml/h 20ml:0.01~600ml/h 30ml:0.01~900ml/h 50/60ml:0.01~2200ml/h	0.1~2ml 0.1~5ml 0.1~10ml 0.1~20ml 0.1~30ml 0.1~50ml
FF Rate	2/3ml:0.01~60ml/h 10ml:0.01~300ml/h 30ml:0.01~900ml/h	5ml:0.01~150ml/h 20ml:0.01~600ml/h 50/60ml:0.01~2200ml/h
Manual KVO Rate & Volume	<p>Rate 0.01~5ml/h (0.01ml/h step)</p> <p>Volume</p> <p>2/3ml: 0.01~0.2ml 5ml: 0.01~0.2ml 10ml: 0.01~0.2ml 20ml: 0.01~0.5ml 30ml: 0.01~0.5ml 50/60ml: 0.01~1ml</p>	
Rate Accuracy	Within±2%(after calibration)	
Occlusion Pressure Levels	13 Levels are available	
Alarms Information	<p>Infusion finished, near infusion end, VTBI completed, near VTBI end, KVO completed, standby task completed, infusion is blocked, syringe falls off, syringe is improperly installed, forgotten operation, low battery, battery empty, abnormal running state, equipment failure, power failure, battery disconnected, etc.</p>	
Prompts	<p>Parameter overrun, infusion begins, AC power has been pulled out, speed overrun, uncalibrated accuracy, etc.</p>	
Power Source	<p>100~240VAC, 50/60Hz. Internal rechargeable 11.1V Li battery. After the new battery is fully charged, turn off wifi and set the screen brightness to "10", which allows the syringe pump to continuously operate at a rate of 5ml/h for 8 hours DC power supply. (The DC power supply shall meet the requirements of EN/IEC 60601-1). For larger battery capacity contact local dealer.</p>	
Drug Library	Can be configured and updated as needed	
Dimensions	301mm(L)x183mm(W)x82mm(H)	



BYOND

Sunfusion[®] Syringe Pump Semi-1|Erch-3|Anim-5



24 hours service hotline // +86-731-82564299 / +86-19807315856 (WeChat & WhatsApp)

Email : sales@beyondmedtech.com URL: www.beyondmedtech.com
Add: Beyond Zone, Zhixian Rd, Xueshi Street, Yuelu District, 410208, Changsha, China
Version number: CY-02-10-01 A/0-002



Beyond Website



Scan for video

Beyond MedTech. Beyond Imagination.

Sunfusion[®] Syringe Pump



Semi-1



Erch-3



Anim-5

Innovative Design

> UI Design



- Brand-new appearance, small and light weight, design as portable;
- 3.5" colorful touch screen to display various information on one page;
- Easier operations are provided by simple UI design.


> High-quality PBT Enclosure



- High-quality PBT enclosure, which makes medical disinfection and cleaning convenient;
- Multi-and Across-combination of syringe pump and infusion pump is enabled by slide guide and lock catch design, which is safe and practical.


Intelligent Safety

> Fast Start



- 9 injection modes are able to satisfy various clinical needs;
- Applicable to 2/3ml, 5ml, 10ml, 20ml, 30ml, 50ml/60ml syringes;
- Rate are adjustable during running state.

> Dynamic Alarm Instructions



- 10 levels for forgotten operation time are selectable;
- 30 levels for near finished alarm time are optional to make supervision reliable;
- Intuitively demonstrate operation instructions by the application of smart alarm system.

> Multi-function Interface



- DC power connector;
- Multi-function connector.

≤ ±2%

Precision

0.01ml/h
2200ml/h

Rate

IP24

High IP Level

13 Levels

DPS

Features



Auto-Lock Screen

Up to 14 levels time setting;
Prevention for operation errors.



Night Mode

Design for nighttime safe operation.



Dual CPU

Guarantee for safe work.



System Self-test

System self-test is conducted every time turning on, including alarm indicator, volume, pressure, etc;
Safeguard for every-time use.



Human Voice Alarm

Exclusive technology;
Combination of human voice, readable words and visual light alarm; 8 volume levels are available.



WLAN Function

Capable of communicating with information management system;
Remotely monitor patient's condition in real time.



History Record Cassette

Up to 2000 pcs records, including operation, alarm and modification;
Trackable treatments are ensured.



Certification

Certified by TÜV Rheinland and EN ISO13485 : 2016

