

Performance Specification		
Nominal Pressure		PN25
Test Pressure	Intensity test	3.75
	Seal test	2.75
		
	Gas test	0.6
Working Temperature		-29~180℃
Medium: water oil & gas		

1. Design and manufacture:EN 593
2. Face-to-face:EN 558
3. Flanged ends:EN1092-1
4. Inspection and test: EN12266.1

12	Sealing Ring	PTFE	24	Worm Gear	Parts
11	Disc	A216 WCB	23	Key	1045
10	Stem	13Cr	22	Yoke	C.S
9	Pin	13Cr	21	Stud Bolt	A193 B7
8	Clamp	A3	20	Gasket	1566
7	Stud Bolt	A193 B7	19	Nut	A194 2H
6	Body	A216 WCB	18	Gland Packing	A216 WCB
5	Bearing	SF-1	17	Stud Bolt	A193 B7
4	Ring	13Cr	16	Gasket	1566
3	Winding Gasket	Flexible Graphite	15	Nut	A194 2H
2	Bottom Cover	A3	14	Packing	PTFE
1	Stud Bolt	A193 B7	13	Bearing	SF-1

NO.	PART NAME	MATERIAL	NO.	PART NAME	MATERIAL
			Assembly Drawing		
					Butterfly Valve
					D962F-25C
		Date 25.9.3			

