

orto alresa

Centrifuges and laboratory products

info@ortoalresa.com

www.ortoalresa.com

+34 91 884 40 16



General applications: Centrifuges universal

Series DIGICEN 21

DIGICEN 21R

LCD



Max. capacity: 4 x 100 ml.
Max. volume: 480 ml.

Max. speed: 26.480 xg / 16.500 RPM

Versatility fused with effectiveness. The centrifuge Digicen 21 R has a wide range of angle fixed rotors, both for low revolutions, with capacity up to 32 tubes of 15 ml./15 ml. conical, and for microtubes, cryotubes and high speed tubes. For the swing out versions, it has rotors for 4 tubes of 100 ml. and up to 28 positions for 15 ml. tubes. The wide range of reducers that accompany each of these rotors give the great versatility that defines the universal centrifuges. Its powerful refrigeration system enables it to maintain the minimum temperature of the chamber below 4°C regardless of the type of rotor and the speed selected.

This particularity, joined to the control of the process of each of the stages and the parameters that control them, gives the user confidence in traceability during the centrifugation cycle.

Features

LCD screen:

- Shows RPM and RCF, time, temperature and acceleration/deceleration (PCBS).
- Speed programming in 10 RPM/ 10 xg steps.
- Timer countdown/up from "0" or at "set RPM/ RCF" for reproducible tests.
- Timer from 5 sec. to 99 min. programmable in 5 sec. steps and hold position.
- PCBS: Progressive controlled acceleration and braking system up to 175 selectable ramps that prevents sample homogenization after separation.
- 16 programmable memories.
- Several acoustic and visual messages warning the user the device situation.

Easy to use

- Microprocessor controlled.
- Induction motor maintenance free (brushless).
- Rotors list on memory.
- Noise level: below 60 dB.
- Start, stop, open lid and short spin with adjustable speed buttons.
- Option of free/locked adjustment of RPM/ RCF along the run.
- Low height for easy access.
- Last values remain in memory.
- Automatic rotor recognition. Over-speed protection.

Safety

- Lid provided with security systems:
 - Automatic lid lock system, motorized with double lock.
 - Emergency lid-lock release.
 - Locking and protection against opening along the run.
 - Lid dropping protection.
 - Port in the lid for calibration and operation checking.
- Unbalance detection and switch off.
- Protection safety ring between the centrifugation chamber and the housing.
- Chamber of centrifugation in stainless steel (easy cleaning).
- Rotors can be removed with the lid closed. Hermetic lids.
- Rotors and adapters autoclavable, easy to install by the user.
- Automatic disconnection for energy saving up to 8 h.

Refrigeration

- Remains the refrigeration after centrifugation process.
- Precooling program with rotor spinning and temperature selectable.
- Guarantee 4°C at maximum RPM.
- Temperature range from -20°C (-4°F) to 40°C (104°F) in 1°C steps.
- Temperature sensor inside the chamber.
- Gas R 449A HFO (CFC free).

EU Directives: 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 98/79/EC.

Regulation n°: (EC) 1005/2009, (EU) 517/2014.

Standards: EN 61010-1, EN 61010-2-101, EN 61010-2-020, EN 61326-2-6, EN 61326-1.

Versions

	Dimensions (mm)(w x d x h)			Net weight (Kg)	Voltage (V)	Frequency (Hz)	Consumption (W)	Z max advisable (Hz)
CE 113	590	620	320	65	220-230	50	700	< 0.446
CE 119	590	620	320	65	110-120	60	800	< 0.446

Accessories

Centrifuges
series Digicen 21

		RT 267		RT 143		RT 138		RT 150		MICROTUBES				RT 253	
															
						(1)		(2)						(4)	
ROTOR		SWING OUT		SWING OUT		SWING OUT		SWING OUT		ANGLE FIXED 45 °		ANGLE FIXED 45 °		ANGLE FIXED 45 °	
Max. capacity		28 x 15 ml.		4 x 50 ml.		4 x 100 ml.		6/4/2 microtiter		32 x 0,2 ml.		24 x 1,5-2 ml.		12 x 5 ml	
RPM Max.		5.000		5.300		5.000		4.000		16.500		16.500		16.500	
Radius (mm)		147		145		147		122 (3)		55 (3)		82		87	
RCF Max. (xg)		4.108		4.554		4.109		2.182		16.741		24.959		26.480	
Min. temp. at max. speed (°C)		-6		-7		-7		-9		-6		-4		-2	
SAMPLE VOLUME		Dim (mm) approx.		ADAPTERS Tubes Ref.		ADAPTERS Tubes Ref.		ADAPTERS Tubes Ref.		ADAPTERS Tubes Ref.		ADAPTERS Tubes Ref.		ADAPTERS Tubes Ref.	
100 ml.		ø48 x 100		-	-	-	-	4	RE 446	-	-	-	-	-	-
85 ml. (ha) / 80 ml. (ha)		ø38 x 112		-	-	-	-	4	RE 380	-	-	-	-	-	-
80 ml.		ø44 x 100		-	-	-	-	4	RE 338	-	-	-	-	-	-
50 ml. (ha)		ø29 x 108		-	-	4	RE 342	4	RE 341	-	-	-	-	-	-
50 ml.		ø34 x 100		-	-	4	RE 445	4	RE 335	-	-	-	-	-	-
50 ml. conical		ø29 x 117		-	-	4	RE 342	4	RE 341	-	-	-	-	-	-
30 ml. / 30 ml. (ha)		ø25 x 98		-	-	4	RE 333	4	RE 332	-	-	-	-	-	-
25 ml. conical		ø29 x 83		-	-	4	RE 596	4	RE 597	-	-	-	-	-	-
15 ml.		ø16 x 100		28	-	4	RE 329	16	RE 316	-	-	-	-	-	-
15 ml. conical		ø17 x 122		4	-	4	RE 329	4/8	RE 339/579	-	-	-	-	-	-
10 ml. (ha)		ø16 x 80		28	-	4	RE 329	16	RE 316	-	-	-	-	-	-
10 ml.		ø13 x 100		28	RE 516	12	RE 313	20	RE 320	-	-	-	-	-	-
10 ml. blood sample		ø16 x 107		28	-	4	RE 329	16	RE 316	-	-	-	-	-	-
7/10 ml. blood sample		ø13 x 107		28	RE 516	4	RE 337	20	RE 320	-	-	-	-	-	-
5 ml.		ø13 x 75		28	RE 512	12	RE 313	20	RE 320	-	-	-	-	-	-
5 ml. conical / screw cup		ø17 x 60/ 68		-	-	-	-	-	-	-	-	-	-	12/6	-
5 ml. blood sample		ø13 x 82		28	RE 512	4	RE 337	20	RE 320	-	-	-	-	-	-
Microtubes 1,5-2 ml.		ø11 x 42		28	RE 578	12	RE 463	20	RE 408	72	RE 401	-	-	24	RE 506
Microtubes 0,5-0,6 ml.		ø8 x 30		28	RE 582	12	RE 531	20	RE 519	72	RE 580	-	-	24	RE 507
Microtubes 0,2-0,4 ml.		ø6 x 45		28	RE 583	12	RE 532	20	RE 473	72	RE 581	32 x 0,2	-	24	RE 508
Microtiter plates		128x86x15/21/45		-	-	-	-	-	-	6/4/2	-	-	-	-	-
Cell culture		128x86x22		-	-	-	-	-	-	4	-	-	-	-	-

(1) This rotor includes hermetic lids.

(2) Allows different configurations depending of the microplates height.

(3) Medium radius.

(4) Available adapters for cryotubes.

(5) Please check tubes features.

(6) Fitting these tubes the rotor can not be closed with the lid.

orto alresa

About centrifugation

Álvarez Redondo S.A.
Edition: January 2019.
Subject to modifications.

info@ortoalresa.com
www.ortoalresa.com
+34 91 884 40 16

Made in Spain (UE)