

Technical specification

FUNCTIONS	Transitions & Effects	Manual T-bar/ AUTO/ CUT/ Wipe/ Mix/ Fade/ FTB / Color Bar
	Streaming	USB type-C uncompressed capture, Comply with UVC & UAC
	Keys & Layouts	Luma Key/ Chroma Key/ PiP/ PoP/ Multiview
	Audio Mixer	Following/Mixing
	LCD Display	15.6 inch, 1920×1080 resolution
	Record	SD card, H.264, record for PGM up to 1080p60
INPUTS	Video Inputs	SD/HD/3G-SDI(75Ω)×4, HDMI2.0 type-A(100Ω)×2, DVI-I(VGA-compatible)×2
	USB Media Player	USB type-A×2
	Analog Audio Inputs	TRS(L/R)×1
OUTPUTS	PGM Streaming Output	USB type-C×1
	PGM Outputs	HD/3G-SDI(75Ω)×2, HDMI type-A(100Ω)×2
	AUX Output (PGM/PVW)	HD/3G-SDI(75Ω)×1
	Multiview Output	HDMI type-A×1
	Analog Audio Output	TRS(L/R)×1
DATA INTERFACES	LAN	Synchronize local time
	Tally	GPIO
STANDARDS	SDI Input Format Support	1080p 60/59.94/50/30/29.97/25/24/23.98 1080psF 30/29.97/25/24/23.98 1080i 60/59.94/50 720p 60/59.94/50/30/29.97/25/24/23.98 625i 50 PAL, 525i 59.94 NTSC
	HDMI Input Format Support	4K 60/50/30, 2K 60/50/30 1080p 60/59.94/50/30/29.97/25/24/23.98/23.976 1080i 50/59.94/60 720p 60/59.94/50/30/29.97/25/24/23.98 576i 50, 576p 50
	SDI & HDMI Scaling Output	1080p 60/50/30/25/24, 1080i 60/50
	Multiview HDMI Output	1080p 60
	SDI Compliance	SMPTE 292M / SMPTE 259M / SMPTE 424M
	USB Capture	Compatible with USB3.0 and USB 2.0, up to 1080p60hz
	Dimension(LWD)	375 × 271.5 × 43.7mm
	Weight	4.0kg
	Power Supply	DC 12V 2.8A, 33W

Accessories



Carry-on Suitcase



12V 5A Power Adapter



Tally Connector