



Home

About Us

Products

Contact us


Order

Downloads

Single Piece PMMA IOL



S101
12.00 mm
5.0 mm Optic
Modified C
Co-Convex
Catenary 3.5°
O Holes
10.00 - 30.00
A Constant: 118.2
AC Depth: 4.9




S104
12.50 mm
6.5 mm Optic
Modified C
Co-Convex
Catenary 3.5°
2 Suture Holes
10.00 - 30.00
A Constant: 118.2
AC Depth: 4.9




S110
13.50 mm
6.5 mm Optic
Modified C
Bi-Convex
Step Vault 2.5°
O Holes
-5.00 - 30.00
A Constant: 118.2
AC Depth: 4.8



S118
12.00 mm
5.5 mm Optic
Modified C
Co-Convex
Catenary 3.5°
O Holes
10.00 - 30.00
A Constant: 118.2
AC Depth: 4.9



S102/S102-2
13.0 mm
6.0 mm Optic
Modified C
Bi-Convex
Step Vault
O/2 Holes
10.00 - 30.00
A Constant: 118.2
AC Depth: 4.8



S106
12.50 mm
6.0 mm Optic
Modified C
Bi-Convex
Step Vault
O Holes
-5.00 - 30.00
A Constant: 118.2
AC Depth: 4.8




S110-2
13.50 mm
6.5 mm Optic
Modified C
Bi-Convex
Step Vault 2.5°
2 Holes
10.00 - 30.00
A Constant: 118.2
AC Depth: 4.8



S120
12.00 mm
5.5 mm Optic
Modified C
CO-Convex
O Holes
10.00 - 30.00
A Constant: 118.0
AC Depth: 4.7



S103-2
12.50 mm
6.5 mm Optic
Modified C
Co-Convex
Catenary 3.5°
2 Holes
-5.00 - 30.00
A Constant: 118.2
AC Depth: 4.9



S106-2
12.50 mm
6.0 mm Optic
Modified C
Bi-Convex
Step Vault
2 Holes
-5.00 - 30.00
A Constant: 118.2
AC Depth: 4.8



S116
12.50 mm
5.5 mm Optic
Modified C
Co-Convex
Catenary 3.5°
O Holes
-5.00 - 30.00
A Constant: 118.2
AC Depth: 4.9



S121
12.50 mm
5.5 mm Optic
Modified C
CO-Convex
O Holes
10.00 - 30.00
A Constant: 118.0
AC Depth: 4.7

