

| | | | |
|---|---|-------------------|-------------------------------|
| Motor ventilator unitate interioara | Model | | ZKFP-58-8-1-5 |
| | lesire | W | 58.0 |
| | Condensator | uF | / |
| | Viteza (Hi/Mi/Lo) | r/min | 1130 / 900 / 800 |
| Serpentina unitate interioara | a. Numar de randuri | | 2.0 |
| | b. Pas tub(a)x pas rand(b) | mm | 21x13.37 |
| | c. Distanta aripioare | mm | 1.3 |
| | d. Tip aripioare (cod) | | Aluminiu hidrofilic |
| | e. Diametru ext. tub si tip | mm | Φ7, canal interior tub |
| | f. Lungime x inaltime x latime serpentina | mm | 780x210x26.74+780x105x26.74 |
| | g. Numar circuite | | 4 |
| Debit aer unitate interioara (Hi/Mi/Lo) | | m ³ /h | 980/817/662 |
| Nivel zgomot unitate interioara (Hi/Mi/Lo/Si) | | dB(A) | 45/40.5/36 |
| Nivel zgomot unitate interioara (Hi) | | dB(A) | 59 |
| Unitate interioara | Dimensiuni(W*D*H) | mm | 1040x220x327 |
| | Ambalare (W*D*H) | mm | 1120x405x315 |
| | Masa neta/bruta | Kg | 12.3/15.8 |
| Motor ventilator unitate interioara | Model | | ZKFN-80-8-3 |
| | lesire | W | / |
| | Condensator | uF | / |
| | Viteza (Hi/Mi/Lo) | r/min | 830/700/550 |
| Serpentina unitate exterioara | a. Numar de randuri | | 1.6 |
| | b. Pas tub(a)x pas rand(b) | mm | 21x13.37 |
| | c. Distanta aripioare | mm | 1.3 |
| | d. Tip aripioare (cod) | | Aluminiu hidrofilic |
| | e. Diametru ext. tub si tip | mm | Φ7, canal interior tub |
| | f. Lungime x inaltime x latime serpentina | mm | 900*44*609 |
| | g. Numar circuite | | 5 |
| Debit aer unitate exterioara | | m ³ /h | 3500 |
| Nivel zgomot unitate exterioara | | dB(A) | 59 |
| Nivel max. zgomot unitate exterioara | | dB(A) | 67 |
| Unitate exterioara | Dimensiuni(W*D*H) | mm | 890x342x673 |
| | Ambalare (W*D*H) | mm | 995x398x740 |
| | Masa Neta/bruta | Kg | 42.9/45.9 |
| Refrigerant | tip | | R32 |
| | GWP | | / |
| | Cantitate incarcare | Kg | 1.42 |
| Presiune proiectata | | MPa | 4.3/1.7 |
| Conducte refrigerant | Lateral lichid/ lateral gaz | mm (inch) | 9.52mm (3/8in)/15.9mm (5/8in) |
| | Lungime max. conducta refrigerant | m | 50 |
| | Diferenta max. de nivel | m | 25 |
| Conexiuni cablaj | | | 2.5x5// |
| Tip stecher | | | //fara |
| Tip termostat | | | Comanda de la distanta |
| Temperatura lucru | Unitate interioara(racire/ incalzire) | ℃ | 17~32/0~30 |
| | Unitate exterioara(racire/ incalzire) | ℃ | -15~50/-15~30 |
| Domeniu aplicare | | m ² | 32~47 |

Caracteristici principale

-  **Racire si incalzire**
-  **Control prin WIFI**
-  **Funcție Follow me**
-  **Auto curatare**
-  **Auto restart**
-  **Mod noapte (Sleep mode)**

CONTER

breeze

POWERED BY

Midea®

ISO 9001
BUREAU VERITAS
Certification

