

SPECIFICAȚII TEHNICE

[Acest tabel va fi completat de către ofertant în coloanele 2, 3, 4, 6, 7, iar de către autoritatea contractantă – în coloanele 1, 5,]

Numărul procedurii de achiziție: ocds-b3wdp1-MD-1711711093598 din: 29.03.2024
Obiectul achiziției: Echipament în cadrul proiectului Erasmus+ Nr. LOLOBL797, Dezvoltarea și îmbunătățirea abilităților STEAM ale studenților și profesorilor pentru inovarea curriculară și dezvoltarea durabilă a instituțiilor de învățământ superior și a întreprinderilor locale - REPETAT

Denumirea bunurilor și/sau a serviciilor	Modelul articolului	Țara de origine	Producătorul	Specificarea tehnică deplină solicitată de către autoritatea contractantă	Specificarea tehnică deplină propusă de către ofertant	Standarde referențiale
1	3	4	5	6	7	8
Lot 1						
Video conferencing system	Rally PLUS Ultra HD (1 buc) + Mic Pod Mount (2 buc)	China China	Logitech Logitech	Specificatii tehnice minime solicitate: Video and Audio Conferencing System - Black with Mounting Kit (PTZ camera with ceiling installations) and 2x Mic ceiling Mount. Production date: min. 2022Y, non-refurbished. Compatible software: Video noise reduction, Low-light saturation optimization, Renders natural skin tones for each participant on camera, Human figure detection, Auto-frame participants at meeting, Auto-reframe participants during meetings, able to distinguish human speech from other sounds, Acoustic Echo Cancellation, Voice Activity Detector, Background noise suppression, Auto-level loud and soft voices, low distortion. Camera: 1xCamera, PTZ imaging system, USB 3.0 Type-C cable min. 2m, Power adapter with regional plugs, Power splitter & case, Camera mount with mounting hardware, supports: 4K, 1440p, 1080p. Slow motorized tilt, turn and zoom: min. turn ±90°, min. Tilt: +50° / -90°, min. 15X HD zoom, min. 90° field of view. Automatic inversion detection to correct image orientation and camera controls when mounted upside down,	Video and Audio Conferencing System (960-001225) and 2x Mic Pod Mount (952-000002). Production date: 2023Y, non-refurbished. Compatible software: Video noise reduction, Low-light saturation optimization, Renders natural skin tones for each participant on camera, Human figure detection, Auto-frame participants at meeting, Auto-reframe participants during meetings, able to distinguish human speech from other sounds, Acoustic Echo Cancellation, Voice Activity Detector, Background noise suppression, Auto-level loud and soft voices, low distortion. Camera: 1xCamera, PTZ imaging system, USB 3.0 Type-C cable 2m, Power adapter with regional plugs, Power splitter & case, Camera mount with mounting hardware, supports: 4K, 1440p, 1080p. Slow motorized tilt, turn and zoom: turn ±90°, Tilt: +50° / -90°, 15X HD zoom, 90° field of view. Automatic inversion detection to correct image orientation and camera controls when mounted upside down, Autofocus, 3 camera presets. Microphone: 2x Microphones	

				Autofocus, min. 3 camera presets. Microphone: min. 2x Microphones with cable connection. Pickup Range: min. 4 m diameter, omnidirectional microphones, Acoustic Echo Cancellation, Voice Activity Detector, Background noise suppression, Mute button with LED status indicator. Speaker: min. 2x Speaker High-performance, suspension system that eliminates camera shake from vibrations and audio interference, min. 7.5W. Accessories: Mount kit All components compatible from the same manufacturer and sold as a set from the manufacturer Warranty: for all components 2 years	with cable connection. Pickup Range: 4 m diameter, omnidirectional microphones, Acoustic Echo Cancellation, Voice Activity Detector, Background noise suppression, Mute button with LED status indicator. Speaker: 2x Speaker High-performance, suspension system that eliminates camera shake from vibrations and audio interference, 7.5W. Accessories: Mount kit All components compatible from the same manufacturer and sold as a set from the manufacturer Warranty: for all components 2 years
Wireless Document Camera	DC556	China	Optoma	Specificatii tehnice minime solicitate: 13 megapixel camera Wireless connectivity and casting images using Miracast2 Supports 17x optical zoom Frame rate – min. up to 60fps Shooting area min. 297 x 420 mm Output resolution min. 3840 x 2160 Focus Auto/Manual With image capture and video recording Inputs: min. 1 x HDMI, min. 1 x VGA, min. 1 x Audio 3.5mm Outputs: min. 1 x HDMI, min. 1 x VGA, min. 1 x USB-A, min. 1 x USB-B, min. 1 x Audio 3.5mm, min. 1 x SD card Control: min. 1 x RS232 Accessories in the box: Power cord (EU), Power Adapter, HDMI Cable, USB/2 Cable, Microscope Adapters (Ø28mm, Ø31mm, Ø33mm, and Ø34mm eyepieces), Remote Control, Anti-glare Sheet Production date: min. 2022Y, non-refurbished. Warranty: min 2 years	13MP High definition camera with 4K video preview Supports 17x optical zoom Frame rate – up to 60fps Shooting area A3 landscape (297 x 420 mm) Output resolution 3840 x 2160 Focus Auto/Manual With image capture and video recording Inputs: 1 x HDMI, 1 x VGA, 1 x Audio 3.5mm Outputs: 1 x HDMI, 1 x VGA, 1 x USB-A, 1 x USB-B, 1 x Audio 3.5mm, 1 x SD card Control: 1 x RS232 Accessories in the box: Power cord (EU), Power Adapter, HDMI Cable, USB/2 Cable, Microscope Adapters (Ø28mm, Ø31mm, Ø33mm, and Ø34mm eyepieces), Remote Control, Anti-glare Sheet Production date: 2022Y, non-refurbished. Warranty: 2 years
Electronic digital standing desk (presidium) (Smart Podium)	TM23S	Turcia	TEMAS	Specificatii tehnice minime solicitate: Speaker display (horizontal display) size minimum 22" Multitouch; Front display minim. 32" with built in media player; Microfon minim. 1 pcs Length 18" Gooseneck with condensator LAN Connection, startup indicator LED Front display specifications: Resolution: minim. 1920×1080 FHD Luminosity: minim. 350 cd/m2 Format 16:9 Display type min. IPS Front part player: Digital Signage Media Player built in; Software available	Tribuna digitala multimedia interactiva, mobila. Ecranul vorbitorului (ecran orizontal) diagonala de 22" Multitouch; Ecran frontal 32" cu media player încorporat; Specificațiile ecranului frontal Samsung DM32E Rezoluție 1920×1080 FHD Luminozitate 400 nit Raport Aspect 16:9 Tip panou IPS

				<p>for management of the contentment of the front pannel; Resolution: minim. 1920×1080 FHD Luminosity: minim. 250 cd/m2 Display type min. IPS Format 16:9 Touch capacitive technology Minimum 10 simultaneous touch points Specifications for the speaker's panel: CPU minimum 11th Generation CPU RAM minimum 16 GB DDR4 HDD minimum 240 GB SSD 1x Audio in, 1x Audio out; OS minimum Windows 10 IoT (Embedded), compatible with Miracast Timer and Stopwatch Display size minim. 3,5" Available clock Touch: minim. one touch In ports (in the speaker's pannel) Minim. 1xUSB 2.0; 1xUSB 3.0 Out ports (inferior part of the podium); Min. 1x HDMI; Min. 1x Ethernet; Warranty: 3 years, without keeping original packaging</p>	<p>Digital Signage Media Player incorporat; Software disponibil de gestionare a conținutului pe panoul frontal; Specificațiile ecranului vorbitorului Rezoluție 1920×1080 FHD Luminozitate 250 cd/m2 Tip panou IPS Raport Aspect 16:9 Tehnologie Touch capacitivă Recunoaste 10 puncte de atingere Specificații PC pentru panoul vorbitorului PC încorporat pentru ecranul vorbitorului CPU Intel i5-11400F, Kingston 16GB 3200MHz DDR4 RAM, Netac SA500 256GB 2.5 SSD, MS Windows 11 Pro FQC-10528 64BIT ENG; Microfon: - 1 buc, incastrat cu lungime de 18", conector de ieșire RJ45 Temporizator, Ceas si Cronometru cu dimensiunea ecranului de 3,5", tip touch Porturi intrări (in panoul vorbitorului) 1xUSB 2.0; 1xUSB 3.0 Porturi ieșiri (Partea inferioară a podiumului); HDMI – 1 buc; Ethernet – 1 buc (RJ45); RJ45 pentru microfon – 1 buc 1x USB 2.0 (pentru PC intern) Alimentare: 230V 50Hz Consum de energie : 450W (max) Garanție: 36 luni.</p>	
--	--	--	--	---	--	--

Semnat: _____

Numele, prenumele: RUDENCO EugeniuÎn calitate de: DirectorOfertantul: GENIAL INVEST SRL

Adresa: or.Chisinau, str. Alexandru Hajdeu 106