

## ANUNȚ DE PARTICIPARE

privind achiziționarea *Camerele video cu tripod și accesorii*  
prin procedura de achiziție *Licitație deschisă*

1. **Denumirea autorității contractante:** *IP Compania „Teleradio – Moldova”*
2. **IDNO:** *1004600050558*
3. **Adresa:** *str. Miorița 1, mun. Chișinău, MD – 2028*
4. **Numărul de telefon/fax:** *022721047, 022723352, 068088984*
5. **Adresa de e-mail și pagina web oficială ale autorității contractante:** [trm@trm.md](mailto:trm@trm.md),  
[www.trm.md](http://www.trm.md)
6. **Adresa de e-mail sau pagina web oficială de la care se va putea obține accesul la documentația de atribuire:** *documentația de atribuire este anexată în cadrul procedurii în SIA RSAP*
7. **Tipul autorității contractante și obiectul principal de activitate (dacă este cazul, mențiunea că autoritatea contractantă este o autoritate centrală de achiziție sau că achiziția implică o altă formă de achiziție comună):** *Instituție Publică*
8. **Cumpărătorul invită operatorii economici interesați, care îi pot satisface necesitățile, să participe la procedura de achiziție privind livrarea bunuri:**

Cod CPV	Denumirea bunurilor	Can.	Uni t.m.ăș.	Descrierea bunurilor și specificarea tehnică (cerințe minime)	Valoarea estimată fără TVA (pentru fiecare lot în parte)
<b>Camere video cu tripod și accesorii</b>					
32240000-7	<b>Lotul nr. 1 Camera (set)</b>	2	buc	Camera: Imaging Sensor Resolution - Actual: 20.9 Megapixel; Effective: 14 Megapixel; Image Sensor - 13.2 x 8.8 mm (1"-Type) CMOS; Image Stabilization - Optical in Integrated Lens Digital Built-In ND Filter - 2 to 7 Stop Electronic ND Filter Capture Type - Video Only; <b>Exposure Control</b> Shutter Type - Electronic Rolling Shutter; Shutter Speed - 1/8000 to 64 Seconds; ISO Sensitivity Range - 250 to 16,000 Gain - -3 to 36 dB Shutter Angle - 5.6 to 360° Minimum Illumination - 1.2 Lux White Balance - 2000 to 15,000K Presets: ATW, Auto Lens Focal Length - 7.71 to 154.21mm (35mm Equivalent:24 to 480mm) Optical Zoom Ratio - 20x Max Digital Zoom - 1.5x ( in UHD 4K), 2x ( in 1080p) Maximum Aperture - f/2.8 to 4.5 Minimum Focus Distance - 0.4" / 1.0 cm Filter Size - 72 mm Focus Control – Autofocus, Manual Focus Video Capture Internal Recording Modes XAVC HS-L 3840 x 2160 at 23.98/50/59.94/100/120 fps [30 to 280 Mb/s]; XAVC S-L 1920 x 1080p at 23.98/25/29.97/50/59.94/100/120/150/180/200/240 fps XAVC S-I 1920 x 1080p at 23.98/25/29.97/50/59.94/100/120/150/180/200 fps	<b>250 000,00</b>

**External Recording Modes**

SDI/BNC 3840 x 2160 at 23.98/25/29.97/50/59.94/100/120 fps  
1920 x 1080p at 23.98/25/29.97/50/59.94/100/120 fps  
1920 x 1080i at 50/59.94/100/120 fps; 1920 x 1080PsF at

23.98/25/29.97 fps

Fast-/Slow-Motion Support

Gamma Curve - HDR-HLG, Rec709, S Cinetone, Sony S-Log 3

Broadcast Output - NTSC/PAL

Built-In Microphone - Stereo

Audio Recording - 4-Channel 24-Bit 48 kHz LPCM Audio

Interface

Media/Memory Card Slot - Dual Slot: CFexpress Type A/SD (UHS-II)

Video I/O - 1x BNC (12G-SDI) Output, 1x HDMI (Unspecified Signal) Output

Audio I/O - 1x 1/8" / 3.5 mm TRS Stereo Input, 2x XLR 3-Pin

Input, 1x 1/8" / 3.5 mm TRRS Headphone/Mic Headphone Output

Power I/O - 1x USB-C

Other I/O - 1x BNC (Timecode) Input/Output, 1x 2.5 mm Sub-Mini (Remote) Control, 1x RJ45 (LAN) Control, 1x USB-C (USB 3.2 / 3.1 Gen 1)

Wireless - 2.4 / 5 GHz Wi-Fi 5 (802.11ac)

Display Type - Articulating Touchscreen LCD, Size - 3.5"

Include: AC Adapter, Power Cord, Battery Charger, Battery Pack, LCD Hood, Lens Hood, Eyecup, Microphone Holder, Cold Shoe Kit

\* Memory card: 80GB CFexpress Type A (4 pcs)

\* CFexpress Type 2 and UHS-II SD Card Reader

\* Dual BP-U100 Lithium-Ion Batteries with 2 x D-Tap ports, 1 x USB port (6800mAh) + Dual Charger (compatible with camcorder)

\* Aluminum Tripod Kit + Video Head Camera (2 pcs)

Legs

Head Mount Type - 75 mm Bowl

Primary Material - Carbon Fiber

Leg Lock - Flip Lock

Leg Sections - 3

Independent Leg Spread

Leg Positions - Continuously Adjustable

Foot Features - Wide Feet, Spiked, Removable

General

Load Capacity - 25 kg

Spreader Support - Mid-Level (Included)

Weight - 3.7 kg

Camera Attachment

Camera Mounting Screw - 1x 1/4"-20 Male with Locating Pin, 1x 3/8"-16 Male with Locating Pin

Camera Plate - Quick Release w/ Sliding Balance Plate: 501PL Head

Head Type - Fluid Head

Base Mount - 75 mm Half Ball

Counter Balance - Continuous

Head Dimensions - Base Diameter: 75.00 mm, Height: 140.00 mm

Pan & Tilt

Drag Control

Independent Tilt Locks

Vertical Tilt - +90° to -60°

General

Load Capacity - 10 kg

Accessory Mounting - 2x Pan Handle Fitting, 1x 1/4"-20 Female Thread

Bubble Level

Weight - 1.2 kg

			<p>Include: Carbon fiber Tripod, Half Ball Tie-Down with 3/8"-16 Screw, Allen Key  Carrying Bag, Video head (75mm Flat Base), 501PL Plate, Extendable Pan Handle,  1/4"-20 Camera Screw, 3/8"-16 Camera Screw, Allen Key.  * Hendheld Mic SET Camera-Mount Digital Wireless Omni Lavalier Mic System with Black Outdoor Kit: Camera-Mount Digital Wireless Receiver, Digital Wireless Bodypack Transmitter, Omnidirectional Lavalier Microphone with Locking 3.5mm Connector, SKM-S Digital Wireless Handheld Transmitter with Mute Switch, 835 Cardioid Dynamic Capsule for Handheld Transmitters, TRS Locking 3.5mm TRS to 3.5mm TRS Coiled Cable, XLR Right-Angle Locking 3.5mm TRS to XLR Male Coiled Output Cable, USB-C Charging Cable, BA 70 Rechargeable Battery Pack, Mounting Kit (Cheeseplate, Cold Shoe, Beltclip, Screws), Bubblebee Industries Windbubble Miniature Imitation-Fur Windscreen, 2 x The Microphone Foam for Lavalier, The Cable Saver, The Mic Accessory Case</p> <p>Wireless Technology - Digital UHF  Included Transmitters - 1x Bodypack, 1x Plug-On  RF Channel Scanning - Auto-Scan  Max Operating Range - 100 m (Line of Sight)  Built-In Recorder  Sample Rate/Resolution - 24-Bit  Latency - 1.9 ms  Dynamic Range - 134 dB  Receiver Type - Camera-Mount  Mounting Options - Belt Clip, Shoe-Mount, 1/4"-20 Female (with Included Hardware)  Antenna - 2x 1/4 Wave Rod, Fixed  Number of Audio Channels - 1  Audio I/O - 1x 1/8" / 3.5 mm TRS Female Unbalanced Output (Locking), 1x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output (Locking)  Audio Output Level - 1/8" / 3.5 mm Output: 2 dBV (Max, Unbalanced)  Frequency Response - 20 Hz to 20 kHz ±3 dB  USB/Lightning Connectivity - 1x USB-C Female (Bus Power, Charging)  Display &amp; Indicators - 1x Backlit OLED (AF Level, Frequency, Mute, RF Level, Transmitter Battery Status)  Transmitter Type - Bodypack  Audio I/O - 1x 1/8" / 3.5 mm TRS Female Input (Locking)  Sync Method - Bluetooth  Antenna - 1x Flexible Whip, Fixed (Beltpack)  Battery Type - 2x AA (Included)  1x Sennheiser Battery Pack (Included, Replaceable)  Display &amp; Indicators - 1x LED (Mute), 1x LED (Sync)  Housing - Metal  Microphone Type - Lavalier  Color - Black  Sound Field - Mono  Capsule - Electret Condenser  Polar Pattern - Omnidirectional  Frequency Range - 50 Hz to 18 kHz  Equivalent Noise Level - 32 dB  Maximum SPL - 130 dB SPL  Sensitivity - 17 mV/Pa at 1 kHz  Output Connector - 1x 1/8" / 3.5 mm TRS Male (Locking)  Cable Length - 5.2' / 1.6 m  Transmitter 2  Transmitter Type - Handheld</p>	
--	--	--	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--

			<p>RF Output Power - 10 mW (ERP); Up to 10 mW (EIRP)  Muting - Mute Switch  Audio Input Level - 2 to 4.35 V RMS  Frequency Response - 20 Hz to 20 kHz  Sync Method - Bluetooth  Antenna - 1x Internal (Handheld)  Power Requirements – Battery  Include: MMD 835 cardioid capsule  * Mic Flag (2 Pcs.)  For mics, ø19.0 mm to ø32.0 mm - all vanes fitted  For mics, ø32.0 mm to ø38.0 mm - remove every other vane  Dimensions: 67 mm Square H 55 mm  Printable Area for label: 4 sides of W 57.0 x H 48.0 mm  Color Black  * Foam windscreen (2Psc)  Foam windscreen for Reporter  Microphone 35-45 mm  Color Black  * Closed-Back Studio Monitor Headphones (2Psc)  Wearing Style - Dual Ear with Headband; Foldable; Earpiece Swivel  Open/Closed-Back - Closed-Back  Frequency Response - 20 Hz to 20 kHz  Audio Connector - 1x 1/8" / 3.5 mm TRS  Included Adapter - 1/4" TRS  * Backpack (equivalent Tenba Cineluxe Backpack 21)  Camera Gear Capacity Professional camcorders, cinema cameras and ENG rigs up to 18 inches (46 cm) long, with matte box and other accessories attached.  Fast Doctor Bag Opening Extra wide opening allows unobstructed access to gear through only one quick zipper down the middle. Camera can be stored with baseplate, microphone and/or matte box attached.  Expedition-Grade Harness Pivot-Fit shoulder harness with Airflow channels and padded hip belt provide comfort and support when carrying large camera systems, and high-density foam padding won't compress or break down over time or with heavy use. Hip belt is easily removable when not needed.  Flex-Core Dividers Tenba's exclusive dividers made with aluminum reinforcement are both rigid and flexible, providing a secure separation between cameras and lenses while also being bendable and repositionable.  Protective Pouch and Wraps Soft padded wraps and zippered pouch protect lenses and delicate accessories and allow them to be safely stored alongside camera rigs to maximize the interior storage space.  Warranty: 3 years.</p>	
	<b>Lotul nr. 2</b>			<b>850 000,00</b>

32240000-7	<b>2.1.Camera (set)</b>	4	buc. <p>Camera Imaging  Sensor Resolution - Actual: 12.9 Megapixel; Effective: 10.2 Megapixel  Image Sensor - Full-Frame CMOS  Image Stabilization - Supplies Stabilization Metadata  Built-In ND Filter - 2 to 7 Stop Electronic ND Filter  Capture Type - Video Only  Exposure Control  Shutter Type - Electronic Rolling Shutter  Shutter Speed - 1/8000 to 1 Second  ISO Sensitivity Range - 800 to 12,800 (Extended: 409,600)  Gain - -3 to 30 dB (Native)  Shutter Angle - 5.6 to 360°  Advertised Dynamic Range - 15 Stops  White Balance - 2000 to 15,000K; Presets: ATW, Set A, Set B  Video Capture  Internal Recording Modes  XAVC-I DCI 4K (4096 x 2160) up to 59.94 fps [240 to 600 Mb/s VBR] UHD 4K (3840 x 2160) up to 59.94/100/120 fps [240 to 600 Mb/s VBR]  1920 x 1080p up to 59.94/100/120/150/200/240 fps [89 to 223 Mb/s VBR]  XAVC-L UHD 4K (3840 x 2160) up to 59.94/100/120 fps [100 to 150 Mb/s] 1920 x 1080p up to 59.94/100/120/150/200/240 fps [35 to 50 Mb/s]  External Recording Modes  Raw 16-Bit via SDI/BNC 4096 x 2160 at 23.98/24.00/25/29.97/50/59.94 fps 3840 x 2160 at 23.98/24.00/25/29.97/50/59.94 fps  Raw 16-Bit via HDMI 4264 x 2408 at 23.98/25/29.97/50/59.94 fps 4240 x 2385 at 23.98/25/29.97/50/59.94 fps  Fast-/Slow-Motion Support  Gamma Curve - HDR-HLG, Rec709, S Cinetone, Sony S-Log 3, Standard  Built-In Microphone - Mono  Audio Recording - 4-Channel 24-Bit 48 kHz LPCM Audio Interface  Media/Memory Card Slot - Dual Slot: CFexpress Type A / SD  Video I/O - 1x BNC (12G-SDI) Output, 1x HDMI 1.0 Output  Audio I/O - 2x XLR 3-Pin Mic/Line (+48 V Phantom Power) Input on Included Handle, 1x 1/8" / 3.5 mm TRS Stereo Microphone Output  Power I/O - 1x Barrel (19.5VDC) Input  Other I/O - 1x USB-C (USB 3.2 / 3.1 Gen 1), 1x Multi/Micro-USB Data, 1x BNC (Timecode), 1x 2.5 mm Sub-Mini Control, 1x 1/8" / 3.5 mm Control, 1x Proprietary  Wireless - 2.4 / 5 GHz Wi-Fi 5 (802.11ac), NFC  Monitor  Display Type - Included External Touchscreen LCD, Size - 3.5" Resolution - 1280 x 720 (2,760,000 Dot)  Include: Handle Unit, 3.5" LCD Monitor, Grip Remote Control, BC-CU1 Battery Cradle, AC Adapter, Power Cord, USB Type-C Cable, Cold Shoe Kit, Lens Mount Cap, Handle Connector Cap  * Mirrorless Lens  Focal Length - 24 to 70mm  Maximum Aperture - f/2.8  Lens Mount - Sony E  Lens Format Coverage - Full-Frame  Focus Type - Autofocus  Filter Size - 82 mm (Front)  * Mirrorless Lens</p>	818 000,00
------------	-------------------------	---	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------

			<p>Focal Length - 70 to 200mm  Maximum Aperture - f/2.8  Lens Format Coverage - Full-Frame  Focus Type - Autofocus  Image Stabilization  Filter Size - 77 mm (Front)  * Memory card: 80GB CFexpress Type A (4 pcs)  * CFexpress Type 2 and UHS-II SD Card Reader  * Dual BP-U100 Lithium-Ion Batteries with 2 x D-Tap ports, 1 x USB port (6800mAh) + Dual Charger (compatible with camera)  * Aluminum Tripod Kit + Video Head Camera(1 pcs)  Legs Head Mount Type - 75 mm Bowl  Primary Material - Carbon Fiber  Leg Lock - Flip Lock  Leg Sections - 3  Independent Leg Spread  Leg Positions - Continuously Adjustable  Foot Features - Wide Feet, Spiked, Removable</p> <p>General  Load Capacity - 25 kg  Spreader Support - Mid-Level (Included)  Weight - 3.7 kg  Camera Attachment  Camera Mounting Screw - 1x 1/4"-20 Male with Locating Pin, 1x 3/8"-16 Male with Locating Pin  Camera Plate - Quick Release w/ Sliding Balance Plate: 501PL  Head  Head Type - Fluid Head  Base Mount - 75 mm Half Ball  Counter Balance - Continuous  Head Dimensions - Base Diameter: 75.00 mm, Height: 140.00 mm</p> <p>Pan &amp; Tilt  Drag Control  Independent Tilt Lock  Vertical Tilt - +90° to -60°</p> <p>General  Load Capacity - 10 kg  Accessory Mounting - 2x Pan Handle Fitting, 1x 1/4"-20 Female Thread  Bubble Level  Weight - 1.2 kg  Include: Carbon fiber Tripod, Half Ball Tie-Down with 3/8"-16 Screw, Allen Key  Carrying Bag, Video head (75mm Flat Base), 501PL Plate, Extendable Pan Handle, 1/4"-20 Camera Screw, 3/8"-16 Camera Screw, Allen Key.  * Kit1: Handheld mic SET Camera-Mount Digital Wireless Omni Lavalier Mic System with Black Outdoor Kit: Camera-Mount Digital Wireless Receiver, Digital Wireless Bodypack Transmitter, Omnidirectional Lavalier Microphone with Locking 3.5mm Connector, SKM-S Digital Wireless Handheld Transmitter with Mute Switch, 835 Cardioid Dynamic Capsule for Handheld Transmitters, TRS Locking 3.5mm TRS to 3.5mm TRS Coiled Cable, XLR Right-Angle Locking 3.5mm TRS to XLR Male Coiled Output Cable, USB-C Charging Cable, BA 70 Rechargeable Battery Pack, Mounting Kit (Cheeseplate, Cold Shoe, Beltclip, Screws), Bubblebee Industries Windbubble Miniature Imitation-Fur Windscreen, 2 x The Microphone Foam for Lavalier, The Cable Saver, The Mic Accessory Case  Wireless Technology - Digital UHF  Included Transmitters - 1x Bodypack, 1x Plug-On  RF Channel Scanning - Auto-Scan</p>	
--	--	--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--

			<p>Max Operating Range - 100 m (Line of Sight)  Built-In Recorder  Sample Rate/Resolution - 24-Bit  Latency - 1.9 ms  Dynamic Range - 134 dB  Receiver Type - Camera-Mount  Mounting Options - Belt Clip, Shoe-Mount, 1/4"-20 Female (with Included Hardware)  Antenna - 2x 1/4 Wave Rod, Fixed  Number of Audio Channels - 1  Audio I/O - 1x 1/8" / 3.5 mm TRS Female Unbalanced Output (Locking), 1x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output (Locking)  Audio Output Level - 1/8" / 3.5 mm Output: 2 dBV (Max, Unbalanced)  Frequency Response - 20 Hz to 20 kHz ±3 dB  USB/Lightning Connectivity - 1x USB-C Female (Bus Power, Charging)  Display &amp; Indicators - 1x Backlit OLED (AF Level, Frequency, Mute, RF Level, Transmitter Battery Status)  Transmitter Type - Bodypack  Audio I/O - 1x 1/8" / 3.5 mm TRS Female Input (Locking)  Sync Method - Bluetooth  Antenna - 1x Flexible Whip, Fixed (Beltpack)  Battery Type - 2x AA (Included)  1x Sennheiser Battery Pack (Included, Replaceable)  Display &amp; Indicators - 1x LED (Mute), 1x LED (Sync)  Housing - Metal  Microphone Type - Lavalier  Color - Black  Sound Field - Mono  Capsule - Electret Condenser  Polar Pattern - Omnidirectional  Frequency Range - 50 Hz to 18 kHz  Equivalent Noise Level - 32 dB  Maximum SPL - 130 dB SPL  Sensitivity - 17 mV/Pa at 1 kHz  Output Connector - 1x 1/8" / 3.5 mm TRS Male (Locking)  Cable Length - 5.2' / 1.6 m  Operating Voltage - 7.5 V</p> <p>Transmitter 2  Transmitter Type - Handheld  RF Output Power - 10 mW (ERP); Up to 10 mW (EIRP)  Muting - Mute Switch  Audio Input Level - 2 to 4.35 V RMS  Frequency Response - 20 Hz to 20 kHz  Sync Method - Bluetooth  Antenna - 1x Internal (Handheld)  Power Requirements – Battery  Include: MMD 835 cardioid capsule  *Kit2: SET Camera-Mount Digital Wireless Omni Lavalier Mic System with Black Outdoor Kit.  Include Camera-Mount Digital Wireless Receiver, Digital Wireless Bodypack Transmitter, Omnidirectional Lavalier Microphone with Locking 3.5mm Connector, TRS Locking 3.5mm TRS to 3.5mm TRS Coiled Cable, XLR Right-Angle Locking 3.5mm TRS to XLR Male Coiled Output Cable, USB-C Charging Cable, BA 70 Rechargeable Battery Pack, Mounting Kit (Cheeseplate, Cold Shoe, Beltclip, Screws), Bubblebee Industries Windbubble Miniature Imitation-Fur Windscreen, 2 x The Microphone Foam for Lavalier, The Cable Saver, The Mic Accessory Case</p> <p>Wireless Technology - Digital UHF</p>	
--	--	--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--

			<p>Included Transmitters - 1x Bodypack, 1x Plug-On  RF Channel Scanning - Auto-Scan  Max Operating Range - 100 m (Line of Sight)  Built-In Recorder  Sample Rate/Resolution - 24-Bit  Latency - 1.9 ms  Dynamic Range - 134 dB  Receiver Type - Camera-Mount  Mounting Options - Belt Clip, Shoe-Mount, 1/4"-20 Female (with Included Hardware)  Antenna - 2x 1/4 Wave Rod, Fixed  Number of Audio Channels - 1  Audio I/O - 1x 1/8" / 3.5 mm TRS Female Unbalanced Output (Locking), 1x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output (Locking)  Audio Output Level - 1/8" / 3.5 mm Output: 2 dBV (Max, Unbalanced)  Frequency Response - 20 Hz to 20 kHz ±3 dB  USB/Lightning Connectivity - 1x USB-C Female (Bus Power, Charging)  Display &amp; Indicators - 1x Backlit OLED (AF Level, Frequency, Mute, RF Level, Transmitter Battery Status)  Transmitter Type - Bodypack  Audio I/O - 1x 1/8" / 3.5 mm TRS Female Input (Locking)  Sync Method - Bluetooth  Antenna - 1x Flexible Whip, Fixed (Beltpack)  Battery Type - 2x AA (Included)  1x Sennheiser Battery Pack (Included, Replaceable)  Display &amp; Indicators - 1x LED (Mute), 1x LED (Sync)  Housing - Metal  Microphone Type- Lavalier  Color - Black  Sound Field - Mono  Capsule - Electret Condenser  Polar Pattern - Omnidirectional  Frequency Range - 50 Hz to 18 kHz  Equivalent Noise Level - 32 dB  Maximum SPL - 130 dB SPL  Sensitivity - 17 mV/Pa at 1 kHz  Output Connector - 1x 1/8" / 3.5 mm TRS Male (Locking)  Cable Length - 5.2' / 1.6 m  Operating Voltage - 7.5 V  *Mic Flag(2 Pcs.)  For mics, ø19.0 mm to ø32.0 mm - all vanes fitted  For mics, ø32.0 mm to ø38.0 mm - remove every other vane  Dimensions: 67 mm Square H 55 mm  Weight 94 grams  Printable Area for label: 4 sides of W 57.0 x H 48.0 mm  Color Black  * Foam windscreen (2Psc.)  Foam windscreen for Reporter  Microphone 35-45 mm  Color Black  * Closed-Back Studio Monitor Headphones (2 pcs.)  Wearing Style - Dual Ear with Headband; Foldable; Earpiece Swivel.  Open/Closed-Back - Closed-Back  Impedance - 32 Ohms  Frequency Response - 20 Hz to 20 kHz  Audio Connector - 1x 1/8" / 3.5 mm TRS  Included Adapter - 1/4" TRS  * Zoom &amp; Focus Control</p>	
--	--	--	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--



			<p>Remote controller for video camcorders that connects to the camera's LANC port. The remote control can be attached to a tripod handle and be used to control zoom, focus and start/stop. This added functionality is ideal for live event coverage such as concerts and sports.</p> <p>* Backpack (equivalent Tenba Cineluxe Backpack 21) (2 pcs.) Camera Gear Capacity Professional camcorders, cinema cameras and ENG rigs up to 18 inches (46 cm) long, with matte box and other accessories attached.</p> <p>Fast Doctor Bag Opening Extra wide opening allows unobstructed access to gear through only one quick zipper down the middle. Camera can be stored with baseplate, microphone and/or matte box attached.</p> <p>Expedition-Grade Harness Pivot-Fit shoulder harness with Airflow channels and padded hip belt provide comfort and support when carrying large camera systems, and high-density foam padding won't compress or break down over time or with heavy use. Hip belt is easily removable when not needed.</p> <p>Flex-Core Dividers Tenba's exclusive dividers made with aluminum reinforcement are both rigid and flexible, providing a secure separation between cameras and lenses while also being bendable and repositionable.</p> <p>Protective Pouch and Wraps Soft padded wraps and zippered pouch protect lenses and delicate accessories and allow them to be safely stored alongside camera rigs to maximize the interior storage space.</p> <p>Warranty: 3 years.</p>		
32240000-7	<b>2.2. LED Light</b>	1	buc.	<p>Production 8-Light Kit CCT 2,000K-10,000K; CRI-96; TLCI-96; CQS-95; SSI (D56)-72; SSI (Tungsten)-82; TM-30 RF (Average) - 94; TM-30 RG (Average) - 103 Lumens - 563 lm Max Power Output (Fixture) - 5W; Max Power Output (Case) - 100W; Max Power Consumption (Fixture) - 7W; Max Power Consumption (Case) - 129W. Max Operating Current - 0.84A; Operating Current (Fixture) - 0.84A; Operating Current (Case) - 1.8A. Operating Voltage (Fixture) 3.0-4.2V; Operating Voltage (Case) 12-28V. Charging Input USB Type-C (5V/2A), Contact Charger AC Input Voltage 100-240V, 50/60Hz Lithium-Polymer Battery 4,200mAh / 3.7-4.2V, 15.5Wh Battery Life (Fixture) Approx. 120 Mins @ Max Output Charge Time Approx. 90 Mins (5V/2A) IP Rating IP65 Operating Temperature -20°C~45°C Dimming 0-100% Screen Type TFT Cooling Method Passive Cooling Include: 8x LED Light Panel 8x LED Light Panel Flat Diffuser 8x LED Light Panel Dome Diffuser 8x LED Light Panel 30° Light Control Grid 4x Cold Shoe Ball Head 4x 1/4-20in Screw to Magnetic Plate Adapter 4x 1/4-20in Screw to Baby Pin Adapter 2x 1/4-20in Articulating Arm to Clamp Adapter 2x USB Type-C Charging Cable 32x Adhesive Magnetic Plate 1x Locking IEC C13 AC Power Cable</p>	32 000,00

				<p>1x D-Tap to D-Tap Power Cable  1x LED Light Panel 8-Light Charging Case  Warranty: 3 years.</p>	
32240000-7	<b>Lotul nr. 3 Camera (set)</b>	1	buc	<p>Camera  Imaging  Sensor Resolution - Actual: 12.1 Megapixel; Effective: 10.2 Megapixel  Image Sensor - 35.6 x 23.8 mm (Full-Frame) CMOS  Crop Factor - 1x  Image Stabilization - Sensor-Shift, 5-Axis  Capture Type - Stills &amp; Video  Exposure Control  Shutter Type - Mechanical Focal Plane Shutter and Electronic Rolling Shutter  Shutter Speed - 1/8000 to 1/4 Second in Movie Mode; 1/8000 to 1/60 Second in Auto Mode; 1/8000 to 30 Seconds in Manual Mode  Bulb/Time Mode - Bulb Mode  ISO Sensitivity Range – Video 80 to 102,400 in Manual Mode (Extended: 80 to 409,600)  Advertised Dynamic Range - 15 Stops  Exposure Modes - Aperture Priority, Auto, Manual, Program, Shutter Priority  Metering Range - -3 to 20 EV  White Balance - 2500 to 9900K Presets: Auto, Cloudy, Custom, Daylight, Flash, Fluorescent, Incandescent, Shade, Underwater  Continuous Shooting - Up to 10 fps  Video Capture  Internal Recording Modes  XAVC Proxy 1920 x 1080 [9 to 16 Mb/s], 1280 x 720 [6 Mb/s]  MPEG-4 AVC/XAVC S 4:2:0 8-Bit, 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [60 to 200 Mb/s]; 1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120/200/240 fps [16 to 100 Mb/s]  H.265 Long GOP/XAVC HS 4:2:2 10-Bit, UHD 4K (3840 x 2160) at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [50 to 280 Mb/s]  H.265 Long GOP/XAVC HS 4:2:0 10-Bit 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [30 to 150 Mb/s]  MPEG-4 AVC/XAVC S 4:2:2 10-Bit, 3840 x 2160 at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120 fps [100 to 280 Mb/s]; 1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120/200/240 fps [50 Mb/s]  MPEG-4 AVC/XAVC S-I 4:2:2 10-Bit, 4096 x 2160 at 1/2/3/6/12/23.98/24.00/29.97/48.00/59.94 fps  UHD 4K (3840 x 2160) at 1/2/3/4/6/8/12/15/23.98/25/29.97/59.94/100/120 fps [240 to 600 Mb/s]; 1920 x 1080p at 1/2/3/4/6/8/12/15/23.98/25/29.97/50/59.94/100/120/200/240 fps [89 to 222 Mb/s]  External Recording Modes  Raw 16-Bit via HDMI; 4264 x 2408 at 23.98/25/50/59.94 fps; 3840 x 2160 at 23.98/25/50/59.94 fps; 1920 x 1080p at 23.98/25/50/59.94 fps; 1920 x 1080i at 50 fps  Fast-/Slow-Motion Support  Gamma Curve - HDR-HLG, S Cinetone, Sony S-Log 2, Sony S-Log 3, Standard  Built-In Microphone - Stereo  Audio Recording - 4-Channel 24-Bit LPCM Audio, 2-Channel 24-</p>	<b>167 500,00</b>

32240000-7

Bit LPCM Audio Interface  
Media/Memory Card Slot - Dual Slot: CFexpress Type A / SD  
Video I/O - 1x HDMI (Unspecified Signal) Output  
Audio I/O - 2x XLR / 1/4" TRS Combo Mic/Line Input on Included Handle, 1x 1/8" / 3.5 mm TRS Stereo Microphone Input on Camera Body, 1x 1/8" / 3.5 mm TRS Stereo Headphone Output on Camera Body  
Power I/O - 1x USB-C Input  
Other I/O - 1x USB-C (Ethernet, USB 3.2 / 3.1 Gen 1) (Shared with Power Input), Multi/Micro-USB  
Wireless - 2.4 / 5 GHz Wi-Fi 5 (802.11ac), Bluetooth, NFC  
Monitor  
Display Type - Articulating Touchscreen LCDm Size - 3"  
Resolution - 1,440,000 Dot  
Include: XLR Handle Unit, Accessory Shoe Cap, Accessory Shoe Kit, Battery Charger, Body Cap, Handle Shoe Cap, Power Cord, Rechargeable Lithium-Ion Battery, USB Type-A to Type-C Cable (USB 3.2)  
\* Dual Battery Charger + 2 Rechargeable Lithium-Ion Battery (compatible with camera)  
\* Mirrorless Lens  
Focal Length - 12 to 24mm  
Maximum Aperture - f/4  
Lens Mount - Sony E  
Lens Format Coverage - Full-Frame  
Focus Type - Autofocus  
\* Mirrorless Lens  
Focal Length - 70 to 200mm  
Maximum Aperture - f/2.8  
Lens Mount - Sony E  
Lens Format Coverage - Full-Frame  
Focus Type - Autofocus  
Image Stabilization  
Filter Size - 77 mm (Front)  
\* Memory card: 80GB CFexpress Type A (4 pcs)  
\* CFexpress Type 2 and UHS-II SD Card Reader  
\* Aluminum Tripod Kit + Video Head Camera Attachment  
Camera Mounting Screw - 1x 1/4"-20 Male, 1x 3/8"-16 Male  
Camera Plate - Quick Release: 504PLONG  
Head Type - Fluid Head  
Base Mount - Flat Base with 3/8"-16 Female  
Counter Balance - Fixed (8.82 lb / 4 kg)  
Head Dimensions - Base Diameter: 2.95" / 7.49 cm, Height: 5.12" / 13.00 cm  
Vertical Tilt - +90° to -80°  
Load Capacity - 22 lb / 10 kg  
Accessory Mounting - 1x 3/8"-16 Female Thread, 2x Pan Handle Fitting  
Bubble Level  
Weight - 1.69 kg  
\* Video Assist 5" 12G-SDI/HDMI HDR Recording Monitor  
Display  
Panel Type - IPS-Type LCD, Touchscreen  
Display Size - 5.0" / 12.7 cm  
Native Resolution - 1920 x 1080  
Aspect Ratio - 16:9  
Maximum Brightness - 2500 nits / cd/m2  
Color Support - 1.07 Billion Colors (10-Bit)  
HDR Support - HDR10/Hybrid Log Gamma  
Pixels Per Inch (ppi) - 440 ppi  
Color Gamut - 100% Rec. 709, 100% Rec. 2020

			<p>LUT Support Image Controls - Histogram, Picture-in-Picture, RGB Parade, Vectorscope, Waveform Inputs / Outputs Video I/O - 1x HDMI 2.0a Input, 1x Micro BNC (12G-SDI) Input, 1x HDMI 2.0a Output, 1x Micro BNC (12G-SDI) Output Embedded Audio - HDMI: 8-Channel, SDI: 16-Channel Audio I/O - 1x 1/8" / 3.5 mm Headphone Output Built-In Speaker - Mono Power I/O - 1x Barrel (12 VDC) Input Other I/O - 1x USB-C Media/Memory Card Slot - Single Slot: SD/SDHC/SDXC (UHS-II) Video Format SDI (10-Bit 4:2:2 RGB), UHD 4K: 60/59.94/50/30/29.97/25/24/23.98; 1080p: 60/59.94/50/30/29.97/25/24/23.98; 1080i: 60/59.94/50 HDMI (10-Bit) UHD 4K: 60/59.94/50/30/29.97/25/24/23.98; 1080p: 60/59.94/50/30/29.97/25/24/23.98; 1080i: 60/59.94/50 Gamma Curve - HDR-HLG, Rec709, Rec2020 * Backpack (equivalent Shootout 14L Slim Backpack) Camera Gear Capacity – 1-2 Mirrorless or compact DSLR cameras with 3-5 lenses (up to 70-200mm 2.8). Secure Rear Camera Access – Camera gear is secured up against the user's back so that nothing can be removed from the front or sides of the pack while traveling. Rear access also allows the pack to be swung around to the front to exchange gear without ever removing the pack from your body. Pivot-Fit™ Airflow Harness – Straps automatically adjust to different shoulder and body shapes for a custom fit. Body contact points covered in ventilated, moisture-wicking 3D air mesh for all-day carrying comfort. Durability and Weather Resistance – Built with the finest materials and hardware, including water-repellent nylon, YKK® zippers and clips, and heavily-reinforced stitching. Warranty: 3 years.</p>	
			<b>Valoarea estimativă fără TVA</b>	<b>1 267 500,00</b>

9. În cazul procedurilor de preselecție se indică numărul minim al candidaților și, dacă este cazul, numărul maxim al acestora. *nu se aplică*
10. În cazul în care contractul este împărțit pe loturi un operator economic poate depune oferta (se va selecta): *Pentru mai multe loturi;*
11. Admiterea sau interzicerea ofertelor alternative: *nu se admite*
12. Termenii și condițiile de livrare/prestare solicitați: *până la data de 27.12.2024*
13. Termenul de valabilitate a contractului: *31.12.2024*
14. Contract de achiziție rezervat atelierelor protejate sau că acesta poate fi executat numai în cadrul unor programe de angajare protejată (după caz): *nu se aplică*
15. Prestarea serviciului este rezervată unei anumite profesii în temeiul unor legi sau al unor acte administrative (după caz): *nu se aplică*
16. Scurta descriere a criteriilor privind eligibilitatea operatorilor economici care pot determina eliminarea acestora și a criteriilor de selecție/de preselecție; nivelul minim (nivelurile minime) al (ale) cerințelor eventual impuse; se menționează informațiile solicitate (DUAE, documentație):

Nr. d/o	Descrierea criteriului/cerinței	Mod de demonstrare a îndeplinirii criteriului/cerinței:	Nivelul minim/Obligativitatea
1.	(DUAE) – Documentul unic de achiziții european (în cazul în care	Semnat electronic de către operatorul economic	Obligativiu

	<i>operatorul economic participă la procedura de achiziții publice împreună cu alți operatori economici, toți participanții urmează să completeze DUAЕ separat)</i>		
2.	Oferta - specificații tehnice și de preț (conform Anexelor nr. 22 și nr. 23 la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021)	<b>Semnată electronic de către operatorul economic</b>	<b>Obligatoriu</b>
3.	Garanția pentru ofertă - 1% din valoarea ofertei fără TVA,	a) Garanția pentru ofertă (emisă de o bancă comercială), conform Anexei nr. 9 la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021 sau b) Transfer la contul (ordin de plată) <b>IP Compania „Teleradio-Moldova:</b> <i>Denumirea Băncii: BC „Moldindconbank” SA</i> <i>Codul fiscal: 1004600050558</i> <i>IBAN: MD47ML00000002251206328</i> <i>Cod bancar: MOLDM2X306</i> Termenul de valabilitate al garanției să fie valabil pe perioada de valabilitate a ofertei. <b>semnată electronic de către operatorul economic</b>	<b>Obligatoriu</b>
4.	Intenția de participare în cadrul procedurii de achiziție	Cerere de participare completată, conform <u>Anexei nr. 7</u> la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021, <b>semnată electronic de către operatorul economic</b>	<b>Obligatoriu</b>
5.	Menținerea valabilității ofertei pentru o durată de 60 de zile ( <i>calculată din momentul termenului-limită de depunere a ofertei</i> )	Declarație privind valabilitatea ofertei, completată conform <u>Anexei nr. 8</u> la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021, <b>semnată electronic de către operatorul economic</b>	<b>Obligatoriu</b>
6.	Confirmarea identității beneficiarilor efectivi și neîncadrarea acestora în situația condamnării pentru participarea la activități ale unei organizații sau grupări criminale, pentru corupție, fraudă și/sau spălare de bani ( <i>formularul Declarației va fi publicat pe SIA „RSAP” (MTender)</i> )	Declarație pe proprie răspundere - <u>în termen de 5 zile după data comunicării rezultatelor</u> procedurii de achiziție publică, ofertantul desemnat câștigător va prezenta această Declarație autorității contractante și Agenției Achiziții Publice, <b>semnată electronic de către operatorul economic</b>	<b>*Obligatoriu</b>
7.	Experiență specifică în livrarea bunurilor similare ( <i>art. 22 alin. (1) lit. a) din Legea 131/2015 privind achizițiile publice</i> )	Declarație privind lista principalelor livrări/prestări efectuate în ultimii 3 ani de activitate, completată conform Anexei nr. 12 la Documentația standard aprobată prin Ordinul Ministrului Finanțelor nr. 115 din 15.09.2021. Prestarea serviciilor se confirmă prin prezentarea unor certificate / documente (facturi fiscale) emise sau contrasemnate de către beneficiarii de livrări, <b>semnate electronic de către operatorul economic.</b>	<b>Obligatoriu</b>
8.	Demonstrarea conformării reglementărilor Legii nr. 209/2016 privind deșeurile	Prezentarea numărului de înregistrare din „ <i>Lista producătorilor de produse supuse reglementărilor de responsabilitate extinsă a producătorului</i> ”, în conformitate cu Regulamentul privind deșeurile de echipamente electrice și electronice, aprobat prin Hotărârea Guvernului nr. 212 din 07.03.2018 ( <a href="https://siamd.gov.md/portal/deee.html">https://siamd.gov.md/portal/deee.html</a> ) - <b>copia</b>	<b>*Obligatoriu</b>

		<b>semnată electronic de către operatorul economic</b>	
9.	Situație financiară	Raportul financiar în original/copie pentru ultimul an, aprobat de către Direcția Generală pentru Statistică sau însoțite de recipisa de primire de către Direcția Generală pentru Statistică, <b>semnat electronic de către operatorul economic</b>	<b>*Obligatoriu</b>
10.	Certificat/Decizie de înregistrare a întreprinderii și Extrasul din registrul de Stat	Copie – <b>semnată electronic de către operatorul economic</b>	<b>Obligatoriu</b>
11.	Certificat de atribuire a contului bancar	Eliberat de banca deținătoare de cont, <b>semnat electronic de către operatorul economic</b>	<b>*Obligatoriu</b>
12.	Informația privind îndeplinirea obligațiilor de plată a impozitelor, taxelor și contribuțiilor de asigurări sociale	Confirmarea lipsei restanțelor față de bugetul public național, <b>semnată electronic de către operatorul economic</b>	<b>*Obligatoriu</b>
13.	Garanția de bună execuție a contractului - 5% din valoarea contractului, inclusiv TVA	Transfer la contul I.P. Compania „Teleradio-Moldova” Beneficiarul plății: I.P. Compania „Teleradio-Moldova” Denumirea Băncii: B.C., Moldindconbank” SA Codul fiscal: 1004600050558 Contul de decontare: MD47ML00000002251206328 Contul bancar: MOLDMD2X306	<b>*Obligatoriu (se va prezenta până la semnarea contractului)</b>

**\*În cazul în care IP Compania „Teleradio-Moldova”, potrivit prevederilor art. 20 alin. (8) din Legea nr. 131/2015 privind achizițiile publice, va solicita prezentarea anumitor documente justificative, operatorul economic este obligat să le prezinte în termen de 3 zile lucrătoare, conform prevederilor DUAE și cadrului normativ în vigoare. În cazul neprezentării documentelor justificative în termenul-limită stabilit, operatorul economic va fi descalificat.**

- 17. Garanția pentru ofertă, după caz - Da, cuantumul de 1%, din valoarea ofertei fără TVA.**
- 18. Garanția de bună execuție a contractului, după caz - Da, cuantumul 5% din valoarea contractului, inclusiv TVA, transfer la contul I.P. Compania „Teleradio-Moldova”.**
- 19. Motivul recurgerii la procedura accelerată (în cazul licitației deschise, restrânse și a procedurii negociate), după caz: nu se aplică.**
- 20. Tehnici și instrumente specifice de atribuire (dacă este cazul specificați dacă se va utiliza acordul-cadru, sistemul dinamic de achiziție sau licitația electronică): Licitație electronică, 3 runde, valoarea pasului minim 1%.**
- 21. Condiții speciale de care depinde îndeplinirea contractului (indicați după caz): nu se aplică.**
- 22. Ofertele se prezintă în valuta LEI MDL**
- 23. Criteriul de evaluare aplicat pentru atribuirea contractului: prețul cel mai scăzut**
- 24. Termenul limită de depunere/deschidere a ofertelor: conform SIA RSAP**
- 25. Adresa la care trebuie transmise ofertele sau cererile de participare: Ofertele sau cererile de participare vor fi depuse electronic prin intermediul SIA RSAP**
- 26. Termenul de valabilitate a ofertelor: 60 zile**
- 27. Locul deschiderii ofertelor: SIA RSAP**  
**Ofertele întârziate vor fi respinse.**
- 28. Persoanele autorizate să asiste la deschiderea ofertelor:**  
*Ofertanții sau reprezentanții acestora au dreptul să participe la deschiderea ofertelor, cu excepția cazului când ofertele au fost depuse prin SIA RSAP.*
- 29. Limba sau limbile în care trebuie redactate ofertele sau cererile de participare: Română**

- 30. Respectivul contract se referă la un proiect și/sau program finanțat din fonduri ale Uniunii Europene: nu se aplică.**
- 31. Denumirea și adresa organismului competent de soluționare a contestațiilor:**  
*Agenția Națională pentru Soluționarea Contestațiilor*  
*Adresa: mun. Chișinău, bd. Ștefan cel Mare și Sfânt nr.124 (et.4), MD 2001;*  
*Tel/Fax/email:022-820 652, 022 820-651, contestatii@ansc.md*
- 32. Data (datele) și referința (referințele) publicărilor anterioare în Jurnalul Oficial al Uniunii Europene privind contractul (contractele) la care se referă anunțul respectiv (dacă este cazul): nu se aplică.**
- 33. În cazul achizițiilor periodice, calendarul estimat pentru publicarea anunțurilor viitoare: nu se aplică**
- 34. Data publicării anunțului de intenție sau, după caz, precizarea că nu a fost publicat un astfel de anunț:** BAP cu nr. 86 din 29.10.2024 link:  
[https://tender.gov.md/ro/system/files/bap/2014/bap\\_nr\\_86 .pdf](https://tender.gov.md/ro/system/files/bap/2014/bap_nr_86.pdf)
- 35. Data transmiterii spre publicare a anunțului de participare: Conform SIA RSAP**
- 36. În cadrul procedurii de achiziție publică se va utiliza/accepta:**
- | Denumirea instrumentului electronic                              | Se va utiliza/accepta sau nu |
|------------------------------------------------------------------|------------------------------|
| Depunerea electronică a ofertelor sau a cererilor de participare | da                           |
| Sistemul de comenzi electronice                                  | nu                           |
| Facturarea electronică                                           | da                           |
| Plățile electronice                                              | da                           |
- 37. Contractul intră sub incidența Acordului privind achizițiile guvernamentale al Organizației Mondiale a Comerțului (numai în cazul anunțurilor transmise spre publicare în Jurnalul Oficial al Uniunii Europene): nu se aplică.**

**Președintele grupului de lucru:**

**Galina Blanaru**

