

# CERTIFICATE

## The company

**VITAFOAM MAGYARORSZÁG Kft.**  
Hrsz. 8806/2 (Ipari Park)  
7030 Paks, HUNGARY

is granted authorisation according to STANDARD 100 by OEKO-TEX® to use the STANDARD 100 by OEKO-TEX® mark, based on our test report 2/397-2022



## for the following articles:

**Polyurethane polyether foam (including types treated with flame-retardant product accepted by OEKO-TEX®), white or coloured, in grades standard (VH, VS, WH, NF), viscoelastic (VA, WA), high resilience (HR) and combustion modified high resilience (CH) up to the thickness of 20 cm.**

The results of the inspection made according to STANDARD 100 by OEKO-TEX®, Annex 6, **product class I** have shown that the above mentioned goods meet the human-ecological requirements of the STANDARD 100 by OEKO-TEX® presently established in Annex 6 for baby articles.

The certified articles fulfil requirements of Annex XVII of REACH (incl. the use of azo colourants, nickel release, etc.), the American requirement regarding total content of lead in children's articles (CPSIA; with the exception of accessories made from glass) and of the Chinese standard GB 18401:2010 (labelling requirements were not verified).

The holder of the certificate, who has issued a conformity declaration according to ISO 17050-1, is under an obligation to use the STANDARD 100 by OEKO-TEX® mark only in conjunction with products that conform with the sample initially tested. The conformity is verified by audits.

**The certificate 25.3.0122 is valid until 31.08.2023**

Budapest, 31.08.2022

Mrs Kitti Sütőné Maróczy  
OEKO-TEX® Officer

Dr. Livia Kokas Palicska  
CEO





**The Vita Group – Vita Hungary**  
 Vitafoam Magyarország Kft. 7030 Paks  
 Ipari Park · HRSZ 8806/2 · Hungary

t: +36 75 510 128  
 f: +36 75 519 719  
 e: info-vfh@thevitagroup.com

[www.thevitagroup.com](http://www.thevitagroup.com)



## RUGALMAS HAB STANDARD FOAM

Date of issue: 08/08/2019

This edition replaces all the previous

Fizikai tulajdonságok Foam properties Caratteristiche Fisico-Meccaniche	NF1830	Alkalmazott szabvány Test method Norme
Blokk sűrűség max. Block Density max. Blocco Densità max.	20	ISO 845:1988
Sűrűség [kg/m <sup>3</sup> ] Piece Density [kg/m <sup>3</sup> ] Pezzo Densità [kg/m <sup>3</sup> ]	16-19	ISO 845:1988
Keménység, CLD, 40% [kPa] Hardness 40% [kPa] Sforzo in compressione, CV 40	2,5-3,5	ISO 3386/1:1986
Szakítószilárdság, minimum [kPa] Tensile strength, minimum [kPa] Carico di rottura [kPa]	80	ISO 1798:1997
Szakadási nyúlás, minimum [%] Elongation at break, minimum [%] Allungamento a rottura [%]	150	ISO 1798:1997
Rugalmasság minimum (%) Ball rebound min. (%) Resa elastica (%)	35	ISO 8307:1990
Maradandó összenyomódás 75% maximum [%] Compression set 75% maximum [%] Deformazione residua dopo compressione 75% [%]	10	ISO 1856:2000
<b>Standard szín Standard colour Colore</b>		<b>FEHÉR WHITE BIANCO</b>

The given figures are average values to which our tolerances apply, susceptible to alterations.