

**CAIET DE SARCINI**  
 pentru achiziția echipamentului audio  
 IP Compania „Teleradio-Moldova”

Nr d/o	Cod CPV	Denumirea bunului	Un. de m	Cant	Descrierea bunurilor și specificarea tehnică (cerințe minime tehnice)
1	32323100-4	Digital Audio Mixer	set	1	<p><b>48-Channel Digital Mixer</b>                      19" Rack mountable                      With 96 kHz FPGA processing                      17 Faders / 6 Layers                      12 x Stereo mixes (perfect for in-ear monitoring setups) + LR                      3 x Stereo matrix                      8 x Internal stereo FX engines with stereo returns                      DEEP processing enables the integration of plug-ins directly into the mixer inputs and mix channels                      7" Touch screen                      SLink port for remote audio networking                      64ch I/O port for audio networking                      32 x 32 USB audio interface                      SQ-Drive direct recording to USB                      AES output                      Chromatic channel metering                      Integrated LED illumination per fader                      Dedicated physical controls                      8 assignable SoftKeys                      Channel LCD displays                      Include SLink Network Interface Card                      Include tablet (equivalent Tab S8+)                      Size 12.4" inches                      Super AMOLED, 120Hz                      Resolution 2800 x 1752 pixels, 16:10 ratio (~266 ppi density)                      Protection Corning Gorilla Glass 5                      Chipset Qualcomm SM8450 Snapdragon 8 Gen 1 (4 nm)                      CPU Octa-core, GPU Adreno 730                      Internal min 128GB 8GB RAM                      stereo speakers (4 speakers)                      Wi-Fi 802.11 a/b/g/n/ac/ax 2.4G+5GHz+6GHz, HE160, MIMO, 1024-QAM                      Bluetooth 5.2, A2DP, AVRCP, DI, HFP, HID, HOGP, HSP, MAP, OPP, PAN, PBAP                      Positioning GPS, Glonass, Beidou, Galileo, QZSS                      USB Type-C 3.2                      Sensors Accelerometer, Fingerprint Sensor, Gyro Sensor, Geomagnetic Sensor, Hall Sensor.                      BATTERY 10090 mAh.                      Stylus, 6.2ms latency (Bluetooth integration, accelerometer, gyro)                      Colors Graphite                      Include tablet case book, gray or black color, magnetic closure.                      Include Cat5e Cable                      Length: 50 m                      On cable reel with winding assistance                      2x RJ45 Hirose connector with Neutrik NE8MX1                      4x 2x AWG26 / 7 double shielded with foil metal braided shield                      Cable can be unwound completely                      Housing / Bushing shielded by contact with metal plug                      Warranty hardware 2 years</p>
2	32323100-4	Combo de chitară electrică	buc.	1	<p><b>Combo for Electric Guitar</b>                      Power: 40 W @ 5 Ohm                      Equipped with: 1x 10" Speaker                      Valvetronix tube preamp                      11 Amp models (20 when using Tone Room - editor/librarian software): Deluxe CL, Tweed 4x10, Vox AC30, Boutique OD, VOX AC30TB, Brit 800, Brit OR MKII, Double Rec, Boutique CL.                      Effects: Pedal 1-type: 4 (Comp, Chorus, Overdrive, Distortion)                      Pedal 2-type: 4 (Flanger, Phaser, Tremolo, Delay)                      Reverb type: 4 (Room, Spring, Hall, Plate)                      Memory slots: 33 (60 when using Tone Room - editor/librarian software)                      User programs: 8 (2 banks x 4 channels)                      6.3 mm Jack input, AUX in                      Headphone connector                      Foot pedal connector                      Mini USB port (type B)                      Including power adapter                      Warranty hardware 2 years</p>
3	32323100-4	Combo de chitară electrică	buc.	1	<p><b>Bass Combo</b>                      Power: 25 Watt                      1x 8" Loudspeaker                      15 Amplifier models                      20 Effects, 50 Factory and 30 user presets</p>

					Gain, Bass, Mid, Treble, Master controls Preset Select, Back, Save Button, Menu Button, Tap Tempo/Tuner Button USB Output for recording and firmware updates Stereo aux Headphone output Foot-switch connection Warranty hardware 2 years
4	32323100-4	Combo de chitară electrică	buc.	1	<b>Electric Guitar Modelling Combo 40 W</b> Speaker configuration: 1x 10" 5 Amp voicings, incl. Clean, Crunch, Lead, OD1 and OD2 4 Fully programmable presets Multi-FX DSP with 5 individual digital effects: Reverb, Delay, Chorus, Tremolo and Phaser, each with adjustable parameters Controls for gain, volume, treble, mid, bass and FX as well as a master volume Mini-jack connection for aux line and headphones Bluetooth audio receiver for playing backing tracks from an external source Digital guitar tuner with LED display Output for external speaker 240 V 50/60 HZ switching power supply 12 mm wooden cabinet Warranty hardware 2 years
5	32323100-4	Microfon set pentru tobe	Set	1	<b>Drum microphone set</b> PG Alta Series 1x PGA52 bass drum microphone 3x PGA56 snare / tom microphones 1x PGA57 snare microphone 2x PGA81 overhead microphones 3x Tom mounts 7x 4.6 m XLR cables Case Warranty hardware 2 years
6	32323100-4	Microfon dinamic	Buc.	2	<b>Dynamic large diaphragm vocals microphone</b> (Equivalent EV ND76) Polar pattern: Cardioid Frequency range: 70 - 17,000 Hz Max. SPL: 140 dB 2.4 mV / Pascal Impedance: 350 Ohm Black zinc diecast housing ABS polycarbonate Incl. microphone holder and bag Warranty hardware 2 years
7	32323100-4	Microfon vocal	Buc.	2	<b>Vocal Microphone</b> (Equivalent EV RE520) Working principle: Condensor Directional characteristic: Supercardioid Frequency range: 40 - 20,000 Hz Max. Sound pressure level: 150 dB Output impedance: 200 ohms Sensitivity: 5.6 mV / Pa (-45 dBV / Pa) @ 1 kHz Requires +48 V phantom power Includes bag Warranty hardware 2 years
8	32323100-4	Microfon vocal	Buc.	2	<b>Microphone</b> (Equivalent XS1) Form Factor - Handheld Sound Field - Mono Capsule - 1 x Dynamic Polar Pattern - Cardioid Orientation - End Address High-Pass Filter - None On-Board Controls - Mic Mute <b>Performance</b> Frequency Range - 55 Hz to 16 kHz Impedance - 300 Ohms Load Impedance - 1 KiloHms Sensitivity - 1.8 mV/Pa <b>Connectivity</b> Output Connectors (Analog) - 1 x XLR Mounting - Mic Clip/Stand Adapter (Included) Construction Material - Metal Warranty hardware 2 years
9	32323100-4	Microfon vocal	Buc.	6	<b>Condenser vocal microphone</b> (Equivalent Beta87A) -Supercardioid polar pattern -Linear transmission range for precise, detailed and true to original song and speech. -Extremely precise supercardioid characteristic over the entire frequency range for the greatest possible feedback resistance with maximum amplification. -Built-in, three-layer wind protection minimizes pop and breathing noises. -Operation with phantom power -Frequency range: 50 Hz - 20 kHz

					<ul style="list-style-type: none"> <li>-Output impedance: 100 ohms</li> <li>-Idle sensitivity: -54 dBV / Pa (2 mV)</li> <li>-Maximum sound pressure level: 140.5 dB SPL</li> <li>-Inherent self-noise (equivalent sound pressure): 23.5 dB (A)</li> <li>-Includes microphone clip and storage bag</li> <li>Warranty hardware 2 years</li> </ul>
10	32323100-4	Cablu Multicore	Buc.	1	<b>Studio Multicore Cables</b> 4x Female XLR in the stagebox 4x Balanced 6.3 mm female jack (socket) in stagebox 4x Male XLR on fanout cable 4x Balanced 6.3 mm male jack (plug) in the fanout cable Length: 10 m
11	32323100-4	Cablu pentru instrument muzical	Buc.	6	Double sided 6.3mm mono jack Metal connectors Textile coated Colour: Black Length: min 9 m
12	32323100-4	Saundcard USB	Buc.	1	<b>4-Channel audio Interface</b> (Equivalent Universal Audio Volt 476) 24 bit / 192 kHz 2 microphone preamps +48 V phantom power Switchable air function 2 Mic/Instrument/Line inputs: XLR/6.3 mm jack combo balanced 2 Line inputs: 6.3 mm jack 4 Line outputs: 6.3 mm jack balanced Stereo headphone output: 6.3 mm jack MIDI input and output USB-C connection <i>Incl. USB cable (type C to A)</i> <i>Include brand computer, Small Form Factor</i> Minimum requirements: Operating System: Windows 11 Pro 64-bit English; Processor: 6C/12T, up to 4.6 GHz Cache: 18MB, equivalent i5-12500; Memory: 16 GB DDR4; Hard Drive: SSD 512 GB for System; Graphics Card: Integrated Graphics; Network interface: Integrated 10/100/1000 Gigabit Ethernet LAN, Bluetooth; External I/O Ports: Front: 2 USB2.0 port, 1 USB3.2, 1 USB3.2 Type-C® port, 1 audio jack; Rear: 3+1 USB3.2 ports, 2 USB2.0 ports, 2 DisplayPort1.4 ports, 1 line-out/in audio port, 3 SATA3.0 slots for 3.5/2.5-inch HDD, and optical drive, 1 PCIe x16 slot, 1 PCIe x4 slot; Keyboard: USB Wireless Mouse and Keyboard (Eng/Ru); Optical drive, SD card slot; Warranty: 2 years.
13	32323100-4	Microfon	Buc.	4	<b>Microphone</b> (Equivalent SM7B) <ul style="list-style-type: none"> <li>- Dynamic Speaker and Recording Microphone</li> <li>- Polar pattern: Cardioid</li> <li>- Frequency range: 50 – 20,000 Hz</li> <li>- Sensitivity -59.0 dB (1.12 mV)</li> <li>- Bass roll-off switch</li> <li>- Mid-boost switch</li> <li>- Impedance: 150 ohms</li> <li>- Shielding against electromagnetic interference</li> <li>- Swivel mount</li> <li>- XLR connector</li> <li>- Includes switch cover plate and windscreen</li> </ul> <b>Microphone Arm</b> (Equivalent Gator Frameworks Deluxe) <ul style="list-style-type: none"> <li>- Table microphone arm with cable guide</li> <li>- Cables up to 8mm in diameter can be attached to the underside of the arms with a clip system</li> <li>- Aluminium construction</li> <li>- Locking centre joint</li> <li>- 3/8» Rhreaded connection with 5/8» adapter</li> <li>- Table clamp up to 56 mm or table feed-through up to 45 mm (20 mm hole)</li> <li>- Length upper arm: 43 cm</li> <li>- Length lower arm: 43 cm</li> <li>- Colour: Black</li> <li>- <b>Microphone Cable</b> Length: 3 m (equivalent Mogami xlr cable)</li> </ul>
14	32323100-4	Microphone Stand	Buc.	1	Microphone Stand (Equivalent Roadworx Mic Stand Round Base Boom) With boom arm and round metal base Length from approx. 92 to 150 cm Boom arm length: 70 cm Threads: 3/8" with 5/8" adapter Base diameter 290 mm Weight: 3.7 kg
15	32323100-4	Level Amplifier	Buc.	1	<b>1-Channel Level Amplifier</b> (Equivalent cloudlifter) +25 dB for dynamic or passive ribbon microphones To be used in conjunction with a microphone amplifier with standard phantom power on mixers/preamplifiers/audio interfaces with mic input Requires phantom power

					<p>XLR input and output Metal casing included band for fixing to microphone stand Warranty hardware 2 years.</p>
16	32323100-4	Portable Speaker	Set	2	<p><b>Portable Speaker</b> (Equivalent Boombox 3) Transducers: 189 x 114mm Subwoofer, 2 x 80.9 x 80.9mm Midrange/2 x 2.75 inch, 2 x 20mm Tweeter/2 x 0.75 inch. Output power: 1 x 80W RMS-subwoofer + 2 x 40W RMS-midrange + 2 x 10W RMS-tweeter (AC mode), 1x60W RMS-subwoofer + 2x30W, RMS-midrange + 2x8W RMS-tweeter, (Battery mode) Frequency response: 40Hz – 20kHz Signal-to-noise ratio: &gt;80dB Battery type: Li-ion polymer 72.6Wh Connection ports: AC-in, USB-A, Aux-in USB charge out: 5V/2A Bluetooth® version: 5.3. IP67 dust and water proof, black.</p> <p><b>Portable Speaker</b> (Equivalent Charge 5) Transducer: 52mm x 90mm woofer, 20mm tweeter; Rated output power: 30W RMS for woofer, 10W RMS for tweeter Frequency response: 60Hz – 20kHz Signal-to-noise ratio: &gt;80dB Battery type: Li-ion polymer 27 Wh USB port: Type C USB rating: 5V/2A Bluetooth® version: 5.1 IP67 dust and water proof, black. Warranty 2 years.</p>
17	32323100-4	Microfon	Buc.	6	<p><b>General Specifications</b> (Equivalent AKG C417 PP) Type Pre-polarized condenser microphone Polar Pattern Omnidirectional Audio frequency bandwidth 20 - 20000 Hz Equivalent noise level 34 dB-A Sensitivity 7 mV/Pa Signal to Noise 60 dB-A Electrical impedance 200 Ohms Recommended load impedance 1000 Ohms Cable length 1.5 m (5 ft.) Type XLR Gender Female Contacts 3-pin Current 2 mA Warranty hardware 2 years.</p>
18	32323100-4	Microfon	Buc.	3	<p><b>OMNIDIRECTIONAL CONDENSER MICROPHONE (equivalent OMNI1)</b> Technical specifications: Type: Condenser microphone (permanently biased 10mm capsule) Polar pattern: Omni Frequency response: 20-20000Hz +-1dB Phantom power: 12 - 48V Current consumption: 4 mA Impedance: &lt;100 Ohm Sensitivity: 8mV/PA -42dB S/N ratio (DIN A-weighted/CCIR): 76dB/66dB Noise level: 18dB(A) Max SPL: 133dB @0.5% THD (130dB@24V, 120dB @ 12V) Connector: XLR Warranty hardware 2 years</p>
19	32323100-4	Microfon	Buc.	6	<p><b>CARDIOID CONDENSER MICROPHONE (equivalent CM4)</b> Technical specifications: Type: Condenser microphone (permanently biased capsule) Polar pattern: Cardioid (slightly wide cardioid) Frequency response: 20-20000Hz (100-16000Hz+-1dB on axis, at 1m, 23C, MLS noise stimuli, 1/12 oct narrow smoothing) Phantom power: 12 - 48V current consumption: &lt;4 mA Impedance: &lt;100 Ohm Sensitivity: 8mV/PA -42dB S/N ratio (DIN A-weighted/CCIR): 78dB/68dB Noise level: 16dB(A) Max SPL: 140dB, 135dB@ 0.5% THD (130dB@24V, 120dB @ 12V) Connector: XLR Warranty hardware 2 years</p>
20	32323100-4	Microfon	Buc.	4	<p><b>Condenser Microphone</b> (equivalent AKG C414 XLII) Microphone Frequency Range - 20 Hz to 20 kHz Primary Applications - Live Sound, Studio Recording Form Factor - Large Diaphragm Mic / Stand/Boom Mount Intended Sound Sources - Vocals, Instrument</p>

					<p>Sound Field - Mono  Operating Principle - Pressure Gradient  Capsule - Condenser  Diaphragm - 1" / 25.4 mm  Polar Pattern - Cardioid, Figure-8, Hypercardioid, Omnidirectional, Subcardioid/Wide  Pattern Selection - Switched  Orientation - Side Address  Circuitry - Solid-State  Pad - -6 dB, -12 dB, -18 dB  High-Pass Filter - 40 Hz, 12 dB/Octave, 80 Hz, 12 dB/Octave, 160 Hz, 6 dB/Octave  Indicators - 13 x Single LED  On-Board Controls - High-Pass Filter, Pad, Polar Pattern  Windscreens - Foam (Included)  Output Connectors (Analog) - 1 x XLR 3-Pin Male (on Mic)  Mounting - Shockmount (Included)  Included Case - Hard Case  Included Filters - Pop Filter  Construction Material – Metal  Warranty hardware 2 years</p>
21	32323100-4	Microfon	Buc.	6	<p><b>Mic type small diaphragm condenser</b> (Equivalent Oktava MK-012-01)  Polar Pattern Cardioid  Freq. Response 20-20000Hz  Phantom voltage required 48 +- 2V  Full impedance, module less than 300 ohms  Weighted SPL 18 dBA  Maximum SPL in 250-8000Hz range, (less than 0.5% THD) 130 db  Free field sensitivity at 1KHz 10 mV/Pa  Free field sensitivity roll off from 40Hz to 20KHz should not exceed +- 3 db  Length, mm 128  Max diameter/width, mm 23  Shockmount  Warranty hardware 2 years</p>
22	32323100-4	Căști Monitor	Buc.	10	<p><b>Monitor Headphones</b> (equivalent DT-770 M)  TECHNICAL SPECIFICATIONS  Transducer type - Dynamic  Operating principle - Closed  Nominal frequency response - 5 - 30,000 Hz  Nominal impedance - 80-250 Ω per cartridge  Nominal SPL - 105 dB SPL  Nominal T.H.D. - &lt; 0.2%  Power handling capacity - 100 mW  Sound coupling to ear - Circumaural  Ambient noise isolation - approx. 35 dB(A)  Nominal headband pressure - approx. 6.5 N  Length and type of cable - 3 m / straight cable  Cable with in-line volume control  Connection - Gold plated mini stereo jack plug (3.5 mm) and 1/4" adapter (6.35 mm)  Warranty hardware 2 years</p>
23	32323100-4	Microfon fără fir, bluetooth	Buc	1	<p><b>Wireless Mics (Pair) for Smartphones/DSLR</b> (Equivalent Sabinetek Smartmike+)  Wireless Technology - Digital Bluetooth  RF Channel Scanning - Auto-Scan  Max Transmitters per Band - 2  Bluetooth - 5.0  Sample Rate/Resolution - 44.1 kHz  Latency - 60 to 100 ms  Transmitter Type Clip-On with Microphone  Audio I/O - 1 x 3.5 mm TRRS Female Output  Power Requirements - Battery, Bus Power (USB)  Internal Battery Capacity - 110 mAh  USB/Lightning I/O - 1 x Micro-USB (Bus Power, Charging)  Display &amp; Indicators - LED (Recharging)  Microphone Type - Integrated  Color - Black  <i>Include bluetooth Earbuds</i> (equivalent Buds 2 Pro)  Speaker custom Coaxial 2-way (Tweeter + Woofer)  24bit Hi-Fi, 360 Audio with Direct Multi-Channel  ANC + High SNR Microphone (2 outer + 1 inner)  Voice Detect  Up to 5 hours / Total up to 18 hours (ANC on) play time  Up to 8 hours / Total up to 29 hours (ANC off) play time  Battery Capacity Case 515 mAh  Bluetooth 5.3, Auto Switching  IPX7 water resistance  Sensors Accelerometer, Gyro Sensor, Hall Sensor, Proximity Sensor, Touch Sensor, VPU  Color: Graphite  Warranty - 2 years</p>

24	32323100-4	Microfon fără fir, bluetooth	Buc	1	<p><b>Wireless Mics (Pair) for Smartphones/DSLR</b> (Equivalent Sabinetek Smartmike+)</p> <p>Wireless Technology - Digital Bluetooth  RF Channel Scanning - Auto-Scan  Max Transmitters per Band - 2  Bluetooth - 5.0  Sample Rate/Resolution - 44.1 kHz  Latency - 60 to 100 ms  Transmitter Type Clip-On with Microphone  Audio I/O - 1 x 3.5 mm TRRS Female Output  Power Requirements - Battery, Bus Power (USB)  Internal Battery Capacity - 110 mAh  USB/Lightning I/O - 1 x Micro-USB (Bus Power, Charging)  Display &amp; Indicators - LED (Recharging)  Microphone Type - Integrated  Color - White</p> <p><i>Include bluetooth Earbuds</i> (equivalent Buds 2 Pro)  Speaker custom Coaxial 2-way (Tweeter + Woofer)  24bit Hi-Fi, 360 Audio with Direct Multi-Channel  ANC + High SNR Microphone (2 outer + 1 inner)  Voice Detect  Up to 5 hours / Total up to 18 hours (ANC on) play time  Up to 8 hours / Total up to 29 hours (ANC off) play time  Battery Capacity Case 515 mAh  Bluetooth 5.3, Auto Switching  IPX7 water resistance  Sensors Accelerometer, Gyro Sensor, Hall Sensor, Proximity Sensor, Touch Sensor, VPU  Color: White    Warranty - 2 years</p>
25	32324300-3	Teleprompter	set	2	<p>Teleprompter for fixing the tablet or phone  Articulating Arm:  Load Capacity Up to 2.72 kg  Construction Durable aluminum construction  Length, Fully Extended 28 cm  Weight 0.2 kg  Arm Length 21.1 cm (joint-to-joint length)  Mount Compatibility Top: 1/4"-20 male screw  Bottom: cold shoe  1/4"-20 female thread (with spacer piece attached)  1/4"-20 male screw (with spacer removed)  TAB GRABBER universal tablet cradle for ultralight teleprompters  Compatible Display 23 cm to 30 cm (9.25 to 11.75")  Include Remote control  Wireless remote control (teleprompter pad remote)  Wireless remote (application with IOS/Android included)  WIRELESS BLUETOOTH REMOTE FOR TELEPROMPTER APPLE/ANDROID  Work distance 10 meter  Include Battery  <i>Include phone</i> (equivalent S23)  Size 6.1 inches  Dynamic AMOLED 2X, 120Hz, HDR10+, 1200 nits (HBM), 1750 nits (peak)  Resolution 1080 x 2340 pixels, 19.5:9 ratio (~425 ppi density)  Protection Corning Gorilla Glass Victus 2  Always-on display  Chipset Qualcomm SM8550-AC Snapdragon 8 Gen 2 (4 nm)  CPU Octa-core, GPU Adreno 740  Internal min 256GB 8GB RAM  MAIN CAMERA 50 MP, f/1.8, 24mm (wide), 1/1.56", 1.0µm, Dual Pixel PDAF, OIS  10 MP, f/2.4, 70mm (telephoto), 1/3.94", 1.0µm, PDAF, OIS, 3x optical zoom 12 MP, f/2.2,  13mm, 120° (ultrawide), 1/2.55" 1.4µm, Super. Video 8K@24/30fps, 4K@30/60fps,  1080p@30/60/240fps, 1080p@960fps, HDR10+, stereo sound rec., gyro-EIS.  Wi-Fi 802.11 a/b/g/n/ac/6e, tri-band, Wi-Fi Direct  Bluetooth 5.3, A2DP, LE  USB Type-C 3.2, OTG  BATTERY 3900 mAh  Colors Black  Warranty hardware 2 years</p>
26	32324300-3	Tablet	buc	1	<p>Tablet (equivalent Galaxy Tab S8 8/128GB)  Network GSM/HSPA/LTE/5G  Dimensions 253.8 x 165.3 x 6.3 mm  Stylus, 6.2ms latency (Bluetooth integration, accelerometer, gyro)  DISPLAY TFT LCD, 120Hz  Size 11.0 inches  Resolution 1600 x 2560 pixels, 16:10 ratio (~274 ppi density)  Protection Corning Gorilla Glass 5  PLATFORM OS Android 12  Chipset Qualcomm SM8450 Snapdragon 8 Gen 1 (4 nm)  CPU Octa-core (1x3.00 GHz Cortex-X2 &amp; 3x2.50 GHz Cortex-A710 &amp; 4x1.80 GHz Cortex-A510)  GPU Adreno 730</p>

					<p>MEMORY Card slot microSDXC (dedicated slot)  Internal min 128GB 8GB RAM  MAIN CAMERA Dual 13 MP, f/2.0, 26mm (wide), 1/3.4", 1.0µm, AF 6 MP, f/2.2, (ultrawide)  Features LED flash, HDR, panorama  Video 4K@30/60fps, 1080p@30fps  SELFIE CAMERA Dual 12 MP, f/2.4, 120° (ultrawide)  Features HDR  Video 4K@30/60fps, 1080p@30fps  SOUND Loudspeaker Yes, with stereo speakers (4 speakers)  3.5mm jack No  COMMS WLAN Wi-Fi 802.11 a/b/g/n/ac/6e, dual-band, Wi-Fi Direct  Bluetooth 5.2, A2DP, LE  Positioning GPS, GLONASS, BDS, GALILEO  USB USB Type-C 3.2, magnetic connector  FEATURES Sensors Fingerprint (side-mounted), accelerometer, gyro, proximity, compass  BATTERY Type Li-Po 8000 mAh  Color: Graphite  Charging 45W wired  <i>Include Remote control</i>  Wireles remote control (teleprompter pad remote)  Wireless remote (application with IOS/Android included)  WIRELESS BLUETOOTH REMOTE FOR TELEPROMPTER APPLE/ANDROID  Work distance 10 meter  Include Battery</p>
27	32323100-4	Microfon radio	Buc.	3	<p><b>System Microfon</b> (Equivalent EW 135P G4-E)  Wireless Technology Analog UHF  Number of RF Channel Frequencies 1680  Included Transmitters 1 x Bodypack with Microphone  Diversity Antenna Diversity  RF Frequency Band 566 to 608 MHz  RF Bandwidth 42 MHz  Frequency Step Size 25 kHz  Max Operating Range 330' / 100.6 m (Line of Sight)  Max Transmitters per Band 12  Deviation 48 kHz (Peak)  Modulation Wideband FM  Receiver Type Camera-Mount  Mounting Options Shoe-Mount (with Included Hardware)  Antenna 1 x Flexible Whip, Fixed  Number of Audio Channels 1  Audio I/O 1 x 3.5 mm TRS Female Unbalanced Output (Lockable)  Gain Range 42 dB (6 dB Steps)  Audio Output Level +12 dBu  Squelch 5 to 25 dBµV  Adjacent Channel Isolation &gt;65 dB  Battery Type 2 x AA (Included)  Approx. Battery Life 8 Hours (Alkaline)  Display &amp; Indicators 1 x Backlit LCD (Battery Status, Output Level, RF Level)  Transmitter Type Handheld  RF Output Power 30 mW  Audio I/O None  Audio Input Level 3 V RMS (Max)  Gain Range 48 dB (6 dB Steps)  Frequency Response 80 Hz to 18 kHz (Mic)  80 Hz to 18 kHz (Line)  Sync Method IR  Antenna 1 x Internal  Battery Type 2 x AA (Included)  Approx. Battery Life 8 Hours (Alkaline)  Display &amp; Indicators 1 x Backlit LCD (Audio Level, Battery Status, Signal Strength)  Microphone  Microphone Type Handheld Capsule  Sound Field Mono  Capsule Dynamic  Polar Pattern Cardioid  Maximum SPL 154 dB SPL Peak  Sensitivity 2.1 mV/Pa  Warranty hardware 2 years</p>
28	32323100-4	Microfon pentru instrument	Buc.	4	<p><b>Microphone</b> (Equivalent Sennheiser MD 421-II)  Operating Principal Pressure Gradient  Capsule Dynamic  Polar Pattern Cardioid  Frequency Range 30 Hz to 17 kHz  Impedance 200 Ohms  Sensitivity in free field, no load (1kHz)  2 mV/Pa +- 3 dB</p>

					Connectivity Output Connectors (Analog) 1 x XLR 3-Pin Warranty hardware 2 years
29	32323100-4	Microfon	Buc	1	<b>Dynamic Podcast microphone</b> (Equivalent MV7B) Control of microphone gain, headphone level, monitor mixing, mute over touch panel interface Individual adjustments via the ShurePlus motif desktop app possible (e.g., amplification, compression and EQ presets) Internal shockmount Directional characteristics: unidirectional (cardioid) A / D converter: 16/24 bit, 44.1 / 48 kHz Frequency range: 50 - 16,000 Hz Adjustable gain: 0 to +36 DB Sensitivity: XLR -55 DBV / PA (1.78 mV) at 1 kHz USB -47 DBFS / PA at 1 kHz (with minimal reinforcement Flat Mode 1 Pa = 94 DB SPL) USB Maximum SPL 132 DB SPL DSP modes (presets): near / far, dark / natural / bright Power supply via USB or LIGHTNING connection MFI certified XLR output impedance: 314 ohms at 1 kHz 5/8" Thread XLR output Micro USB output 3.5 mm Jack headphone output Warranty hardware 2 years
30	32323100-4	Double Ear Intercom Headset	Buc.	10	Double Ear Intercom Headset (equivalent HMD685) Professional intercom headsets with flexible anti-vibration gooseneck boom microphones. The headset is lightweight, provides extra soft ear cushions and headband paddings for outstanding wearing comfort even during extra soft ear cushions Headset is provided with a dynamic vocal unidirectional patterned microphone, featuring excellent acoustic performance and a reliable noise suppression. HEADPHONE Transducer principle : dynamic, closed Ear coupling : Circumaural Frequency response : 20~20,000 Hz Impedance Double-ear: 200 Ω Sensitivity : 96 dB SPL at 1 kHz, 1 mW Max. Input Power : 100 mW Caliper pressure : approx. 4.5 N Connector : 1.5-meter (4.92') straight cord, 4-pin XLR female plug MICROPHONE Transducer principle : dynamic, cardioid Frequency response : 50~15,000 Hz Polar Pattern : cardioid Sensitivity : -64 dBV/Pa (0.6 mV/Pa) at 1 kHz Impedance : 250 Ω
31	32323100-4	Lavalier microphone system	set	2	<b>System</b> Wireless Technology - Digital UHF Number of RF Channel Frequencies - 2240 Included Receivers - 5 x Receivers Included Transmitters - 5 x Bodypack Included Splitters - 1 x Active Antenna Splitter Diversity - Intelligent Switching Diversity RF Channel Scanning - Auto-Scan Max Operating Range - 100 m (Line of Sight) Max Transmitters per Band - 90 Bluetooth - 5.1 Sample Rate/Resolution - 24-Bit <b>Receiver 5 pcs</b> (equivalent EW-D EM Y1-3) Frequency range U1/5: 1785.2-1799.8 MHz Receiver Type - Tabletop / Rackmount Mounting Options - Rackmount, Tabletop Rackmount Size - 1 RU (1/2 Rack) Antenna - 2 x 1/4 Wave Rod, BNC (Rear-Mount) Number of Audio Channels - 1 Audio I/O - XLR 3-Pin Male Balanced Output (Lockable), 1/4" TRS Female Unbalanced Output Gain Range - -3 to +42 dB (3 dB Steps) Audio Output Level-XLR Output:+18dBu (Balanced), 1/4"Output:+12 dB (Unbalanced) Frequency Response - 20 Hz to 20 kHz ±3 dB Power Requirements - AC/DC Power Adapter AC/DC Power Adapter - 11 to 13 VDC at 300 mA (Included) AC Input Power - 100 to 240 VAC, 50 / 60 Hz Display & Indicators - Backlit OLED (AF Level, Frequency, Mute, RF Level, Transmitter) <b>Transmitter 5 pcs</b> (EW-D SK) Transmitter Type - Bodypack RF Output Power - 10 mW (ERP) Audio I/O - 1 x 3.5 mm TRS Female Input (Lockable)



					<p>Muting - Mute Switch  Audio Input Level - 2 to 4.35 V RMS  Sync Method - Bluetooth  Antenna - 1 x Flexible Whip, Fixed (Beltpack)  Power Requirements - Battery  <b>Microphone 5 pcs</b> (equivalent ME-2)  Microphone Type Lavalier  Sound Field Mono  Capsule Electret Condenser  Polar Pattern Omnidirectional  Frequency Range 50 Hz to 18 kHz  Equivalent Noise Level 32 dB  Maximum SPL 130 dB SPL  Sensitivity 17 mV/Pa at 1 kHz  Output Connectors 1 x 1/8" / 3.5 mm TRS Male (Lockable)  Cable Length 5.2' / 1.6 m  Operating Voltage 7.5 V  <b>Active Antenna Splitter 1 pcs</b> (equivalent EW-D ASA X-Y)  Active Antenna Splitter (Dual 1:4) with DC Voltage Distribution  For the UHF-range from 1350-1805 MHz  Incl. 1x power supply NT 12-35 CS and 8x BNC connection cable  <b>Half-wave dipole rod antenna 2 pcs</b>  Frequency range - Y: 1785 - 1805 MHz  Connection – BNC</p>
32	32323100-4	Handheld Microphone System	set	1	<p><b>System</b>  Frequency range Y1-3: 1785.2 - 1799.8 MHz  Wireless Technology – Digital UHF  Number of RF Channel Frequencies – 2240  Included Transmitters – 3 x Handheld  Diversity - Intelligent Switching Diversity  RF Channel Scanning – Auto-Scan  Max Operating Range – 100 m  Max Transmitters per Band – 90  Bluetooth - 5.1  Sample Rate/Resolution – 24-Bit  <b>Receiver 3 pcs</b> (equivalent EW-D EM Y1-3)  Frequency range Y1-3: 1785.2 - 1799.8 MHz  Receiver Type - Tabletop / Rackmount  Mounting Options - Rackmount, Tabletop  Rackmount Size - 1 RU (1/2 Rack)  Antenna - 2 x 1/4 Wave Rod, BNC (Rear-Mount)  Number of Audio Channels - 1  Audio I/O-XLR 3-Pin Male Balanced Output (Lockable), 1/4" TRS Female Unbalanced  Gain Range - -3 to +42 dB (3 dB Steps)  Audio Output Level- XLR Output: +18 dBu (Balanced), 1/4" Output: +12 dB (Unbalanced)  Frequency Response - 20 Hz to 20 kHz ±3 dB  Power Requirements - AC/DC Power Adapter  AC/DC Power Adapter - 11 to 13 VDC at 300 mA (Included)  AC Input Power - 100 to 240 VAC, 50 / 60 Hz  Display &amp; Indicators - 1 x Backlit OLED (AF Level, Frequency, Mute, RF Level).  <b>Transmitter 3 pcs</b> (equivalent EW-D SKM-S)  Transmitter Type – Handheld  RF Output Power - 10 mW (ERP)  Muting - Mute Switch  Audio Input Level - 2 to 4.35 V RMS  Auto-Level Control - No  Antenna - 1 x Internal (Handheld)  Power Requirements - Battery  Battery Type - 2 x AA (Included)  Display &amp; Indicators - 1 x LED (Mute); 1 x LED (Sync)  <b>Microphone 6 pcs</b> (equivalent MMD 835 capsule)  Microphone Type - Handheld Capsule  Sound Field - Mono  Capsule - Dynamic  Polar Pattern - Cardioid  Equivalent Noise Level - 32 dB  Maximum SPL - 154 dB SPL  Sensitivity - 2.1 mV/Pa  <b>Active Antenna Splitter 1 pcs</b> (equivalent EW-D ASA X-Y)  Active Antenna Splitter (Dual 1:4) with DC Voltage Distribution  For the UHF-range from 1350-1805 MHz  Incl. 1x power supply NT 12-35 CS and 8x BNC connection cable</p>

				<b>Half-wave dipole rod antenna 2 pcs</b> Frequency range - Y: 1785 - 1805 MHz Connection – BNC Include EW-D Color Coding Set
--	--	--	--	--