



Nanchang Micare Medical Equipment Co.,Ltd



Add: No. 666 Yaohu West 5th Road, Hi-Tech Zone,
Nanchang, Jiangxi, China

Website: www.micare-med.com





Specification model E700/500 Ceiling mounted Surgical Light

Light Intensity At (1M)	60,000-180,000/40,000-160,000 lux
LED Bulb Quantity	61PCS/39PCS
Bulb Life (HRS)	≥ 80,000
Color Temperature Adjustable	3500 ~5500K
Color Rendering Index (Ra)	> 96
Color rendering index R9	98
Light Beam Depth (MM)	1300
Diameter of Spot (MM)	150-350
Light Adjust Range	0% - 100% (10 Steps)
Rotating Angle of Arm	540°
Temperature rise (surgical field)	≤1°C
Working distance (MM)	700 -1400
Vertical movement (MM)	≥800
Light head freedom of movement	≥ 4°
Voltage	95~245V, 50/60HZ
Power Consumption	105W
Flower design lamp heads for Laminar Air Flow Compliancy	YES
Antibacterial coating	YES
LCD Touch Screen 3.7 Inches	YES
Internal / External Sony Camera (20X)	Optional
Monitor With Extra Arm (22 Inches/27 Inches)	Optional
Ceiling Height (M)	3 - 4