



KÖKSAL®
TARIM MAKİNALARI A.Ş.

Declaratin No: KT 22

AT UYGUNLUK BEYANI
EC DECLARATION OF CONFIRMITY

2006/42/AT Makina Emniyeti Direktifi'ne göre
according to Machinery Directive 2006/42/EEC

Üretici:

Manufacturer:

Ekrem Köksal Tarım Makinaları İmalat ve Ticaret A.Ş.
Merkez Mah. Sakarya Cad. No:44/1 Kaynarca / SAKARYA / TÜRKİYE

Beyan:

Declaration:

Kendi sorumluluğumuz altında beyan ederiz ki, aşağıda belirtilen ürünler
Herewith we declare under our own responsibility that the products designated below

Ürünler:

Products:

Tipi Su Tankeri , Santrafüjlü , Pompalı 3,5 Ton, 1 Dingil, 2 Lastik

Agricultural Water Tanks With Centrifuge pomp 3,5 tons, single axles, 2 tires

MARKA	HUMMEL
TİPİ / MODEL	TN1230 / 2021
SERİ NUMARASI	20210282
ÜRETİM YILI	2021
BRAKE	Hydraulic
TYRES	10.75-15.3

Directives:

2006/42/AT Makina Emniyeti Direktifi ve revizyonları
Machinery Directive **2006/42/EEC** including their amendments.

Harmonize Standartlar: TS 585, TS 3413, TS 1169 ISO 303, TS 1305, TS EN 1853+A1, TS ISO 11407, TS EN ISO 12100:2010

Harmonised Standards: TS 585, TS 3413, TS 1169 ISO 303, TS 1305, TS EN 1853+A1, TS ISO 11407, TS EN ISO 12100:2010

Ekrem KÖKSAL
Managing Director



EKREM KÖKSAL TARIM
MAKİNALARI İML. VE TİC. A.Ş.

Tel: 0264 871 32 21 - 871 43 51 / 0264 871 43 52
Merkez Mh. Seyfettin Salim Çelebi Cad. No: 44/1 Kaynarca / SAKARYA
Ali Fuat Cebesoy V.D.: 3330131000001012561 No: 23895
Mersis No.: 0330 0532 0100 0009 Şirket Yılı: 2.305,200,00 TL

Sakarya, 2021

Tn1230 3 Ton Single Axle Two Tire Galvanized Water Tanker With Centrifugal Pump



Permitted Total Weight	3800 KG
Loading Capacity	3000 KG
Empty Weight	800 KG
Tank Capacity	3000 LT
Tank Length	2500 MM
Tank Diameter	1260 MM
Tank Plate Thickness	3 MM

Dimensions (Length, Width, Height)	4115 / 1862 / 1952 MM
Tanker Mounting	MOUNTING ON CHASSIS
Filling System / Discharge System	2" CENTRIFUGAL PUMP
Wheel Track Length	1600 MM
Suspension	LEAF SPRING
Brake Systems	HYDRAULIC
Hitch-Ring Load	600 KG
Tires	10,0 / 75 - 15.3 / 750 / 16
Maximum Speed	25 KM / H
Maximum Tractor Power Requirement	45 HP / 33 KW
Pto Range	300 RPM
Maximum Compressor Efficiency	36 TON / HOUR

