## **EC DECLARATION of CONFORMITY**

### "CE" COMPLIANCE DECLARATION



# We are agriculturel equipment manufacturer.

# Bark Metal Endüstrisi A.Ş (CO.)

Adress: İncesu OSB Web: www.barktarim.com Trade Registry: 48133

1.cadde NO:5 E-mail: bark.tarim@gmail.com

İncesu/Kayseri/TÜRKİYE Telephone: +90 532 562 6884

We hereby declare that the products, whose name, type or model and serial numbers are given below, are produced to meet the requirements of directive 2006/42/EC in accordance with the specified standarts( or relevant documents).

### **Information Regarding the product (Drawbar Series):**

Type / Model	BRKD				
Chassis No	NR9BRKD10PK325233				
<b>Production Year</b>	2023				

Directives Complying for Product Specifications: Related Documents, Standards

DIRECTIVE 'Machine Directive' 2006/42/EC

Standard: TS ISO 11684

BARK METAL ENDÜSTRI A.S.
Sullensen O.S.B. Mah. O.S.B. 1. Cd. Not SIA
Incesu / KAYSERI
Incesu V.D. NO: 1420703742
Mersis No: 0142070374200001
Fic. Sic. No: 48133

### **EC DECLARATION OF CONFIRMITY**

#### 1. Manufacturer

1.1. Make (trade name of the manufacturer)

1.2. Type

Variant

Version

:BARK
:T1
:10

1.2.1. Commercial name :BRKD10
1.3. Category, subcategory and speed index of vehicle :R3a

1.4. Company name and address of manufacturer:

BARK METAL ENDÜSTRİSİ ANONİM ŞİRKETİ Sultan sazı Osb. Mahallesi Osb. 1. Cadde. No:5 İNCESU / KAYSERİ / TURKEY

1.5. Location of the manufacturer's statutory plate(s):

On the right hand-side of the chassis

1.5.1. Method of attachment of the manufacturer's statutory plate(s):

Rivets or by sticking

1.6. Location of the vehicle identification number on the chassis:

Front right-hand side of the chassis

2. Vehicle identification number(VIN No) :NR9BRKD10PK325233

Conforms in all respects to the type described in EU type-approval (e13\*167/2013\*00404\*00) issued on (Machinery Safety Directive 2006/42/EC) and can be permanently registered in Member States having right/left hand traffic and using metric units for the speedometer.

Here with we declare under our own responsibility that the products designated above EU Directive Machinery Safety Directive, which is manufactured in compliance with health, safety and the safety rules.

BARK METAL EN

Directives: Machinery Safety Directive 2006/42/EC

Place: İncesu / Kayseri / TÜRKİYE Date:28.07.2023

### **VEHICLE CATEGORY R / S (COMPLETE VEHICLES)**

#### 3. General Construction Characteristics

3.1. Number of axles and wheels : 2 axles and 4 wheels

3.2. Number and position of axles with twinned wheels
3.3. Number and position of steered axles
3.4. Number and position of braked axles
3.5. Type of chassis: drawbar/rigid drawbar/other
3.6. Declared maximum design vehicle speed
3.7. N.A.
3.8. Lype of chassis: drawbar/rigid drawbar/other
3.9. Declared maximum design vehicle speed
3.1. N.A.
3.2. P.A.
3.3. Drawbar
3.4. Drawbar
3.5. Declared maximum design vehicle speed
3.6. Declared maximum design vehicle speed

#### 4. Masses

4.1. Unladen mass(es) in running order : 2450 kg 4.2. Technically permissible maximum laden mass(es) : 8600 kg

4.3. Technically permissible maximum mass(es) per axle

Axle 1 : 40 km/h=4300 kg Axle 2 : 40km/ h=4300 kg

#### 4.4. Mass(es) and tyre(s)

Tyre combi - nation No	Axle No	Tyre dimension including load capacity index and max speed	Rolli ng radiu s [mm]	Tyre Load ratin g per tyre [kg]	Maximum permissible mass per axle [kg]	Maximum permissible mass of the vehicle [kg]	Maximum permissibl e vertical load on the coupling point [kg]	Track width [mm]
1	1 and 2	11.5/80-15.3 Max:40 km/h	-	2600	5200	10400	-	Min:1500 Max:2140

#### 5. Main Dimensions

5.1. Length for on-road use : 6200 mm
5.2. Width for on-road use : 2200 mm
5.3. Height for on-road use : 2030 mm
5.4. Wheelbase : 2420 mm
5.5. Distance between the coupling point and the first axle : 2420 mm
5.6. Distance between the coupling point and the last axle : 5300 mm
5.7. Track width : 2000 mm

#### 6. Braking

- 6.1. Electronic braking system: : NO
- 6.2. Towed vehicle braking control system technology: Hydraulic / Pneumatic / Electric / Inertia / None
  - : pneumatic 300-60
- 6.3. Connections type: two-lines / Single-line / none
  - : pneumatic
- 6.4. Electrical control line: yes/no :NO

Brief description of the support devices for service and maintenance:

# **See Operator Manual !!!!**



Bark Metal Endüstrisi A.Ş (CO)

**İncesu OSB 1.Cadde NO:5** 

**İncesu/KAYSERI-TURKIYE**