

		Key features	
		<ul style="list-style-type: none"> ★ 5MP IR Network Bullet Camera with audio input ★ 2.8mm lens brings everything back to life ★ Efficient H.265+ compression technology ★ Built-in microphone for real-time audio security ★ Up to 100ft night vision with EXIR 2.0 ★ Clear day and night vision with 3D DNR and 120DB WDR ★ IP67 Dust and Waterproof Rating ★ Support PoE (Power over Ethernet)&DC12V 	
Model Number		I51DL*4	
IP Camera			
Camera	Image Sensor	1/3" Progressive Scan CMOS	
	Main Stream Max. Frame Rate	50 Hz: 20 fps (2592 X 1944, 2560*1440), 25 fps (2304 X 1296, 1920 X 1080, 1280 X 720) 60 Hz: 20 fps (2592 X 1944, 2560*1440), 30 fps (2304 X 1296, 1920 X 1080, 1280 X 720)	
	Substream Max. Frame Rate	50 Hz: 25 fps (640 X 480, 640 X 360, 320 X 240) 60 Hz: 30 fps (640 X 480, 640 X 360, 320 X 240)	
	Video Compression	H.265+/H.265/H.264+/H.264	
	Video Bitrate	32 Kbps - 8 Mbps	
	Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC	
	Audio Input	Built-in Microphone	
	Lens	2.8 mm	
	Min. Illumination	Color: 0.028 Lux @(F2.0, AGC On)	
	Angle of View	horizontal FOV 98°, vertical FOV 53°, diagonal FOV 115°	
	Number of Infrared LEDs	2 pcs	
	Night Vision Distance	Up to 100 ft/30 m	
	DNR	3D DNR	
	Wide Dynamic Range	120 dB WDR	
	ONVIF	Support	
	IR-Cut Filter	Yes	
Ethernet	RJ45 X1 (10 M/100 M)		
General	Housing	Metal & Plastic	
	Color	White	
	Storage	Built-in microSD/SDHC/SDXC Slot, up to 256 GB	
	Hardware Reset	Yes	
	Operating Power	DC 12 V; PoE (802.3af)	
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C	
	Indoor/Outdoor Use	Indoor/Outdoor	
	Interface Protection	IP67, TVS 2000 V Lightning Protection, Surge Protection and Voltage Transient Protection	
	Dimension (L X W X H)	7.0" X 2.6" X 2.7"/177.6 X 66.2 X 67.8 mm	
	Weight	0.6 lb./270 g	
Packaging Contents			
Camera	4		
Ethernet Cable	60 ft/18 m X2; 100 ft/30 m X2		
Mounting Screw Bag	4		
User Manual for Camera	1		

