



**ALLIANCE
CONSTRUCTION &
INDUSTRIAL**

TRA: L-4
Speed Rating: A8

Alliance 202 has a unique tread pattern that offers superior tire life even while operating in severe conditions. The deep tread pattern of the tire enhances traction and provides resistance to puncture. The presence of the reinforced sidewall of the tire leads to better handling and stability. Alliance 202 also comes with an enhanced load carrying capacity coupled with better riding comfort.

Backhoe Loader - 12.5/80-18NHS

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								Backhoe Application						
								Static kmph	5 kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
12.5/80-18 NHS	W9 X 18	305	965	452	2861	14 132A8	4.3	4700	2800	2500	2180	2080	2000	1820

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
		SW mm	OD mm					Speed	
								Cyclic Application	
								10 kmph	15 kmph
12.5/80-18 NHS	W9 X 18	305	965	452	2861	14 132A8	2.55	3000	2680

