

Eaton EVMIF316X

Eaton Metered Input G4 Rack PDU, 0U, 39U, IEC-60309 input, 3m cord, 3ph, 11kW, 16A, 415/240V, 42 outlets (24)C13, (18)C39



General specifications

PRODUCT NAME	Eaton Rack PDU G4
CATALOG NUMBER	EVMIF316X
EAN	3553340697111
PRODUCT LENGTH/DEPTH	1730 mm
PRODUCT HEIGHT	53 mm
PRODUCT WIDTH	52 mm
PRODUCT WEIGHT	3.8 kg
COMPLIANCES	CB LVD Directive RoHS Directive WEEE Directive Packaging Directive EMC Directive
CERTIFICATIONS	IEC 62368-1 EN IEC 63000 CE EAC UKCA Cm Ukr IEC/EN 61000-6-2 IEC/EN 61000-6-4 EN 61000-3-2 EN 61000-3-3 CISPR 35/EN 55035
MODEL CODE	PDU G4 MI 0U 309 16A 3P 24xC13,18xC39

Specificații produs

SPECIAL FEATURES

- Remote Site Management
- Versatile C39 outlet supports C14 or C20 power cord plug
- High retention outlets designed to securely fit standard power cords and support P-Lock power cords
- Cybersecurity standards UL 2900-1 and IEC 62443-4-2
- Hot-Swap network control module
- Network Cascading, connect up to 32 PDUs via network loop
- Power sharing between two network modules PDUs ensures constant access to PDU data & sensors
- 1% IEC Class 1 billing grade measurement accuracy
- Gigabit network card with 2x Gb ports
- Support protocols RestAPI, Modbus TCP, SNMP, LDAP, HTTPS
- Optional sensor Temperature/Humidity

Resurse

DECLARATIONS OF
CONFORMITY

[EU declaration of
conformity Rack PDU G4](#)

TYPE	Metered input Rack PDU
------	------------------------

FORM FACTOR	0U (Vertical)
-------------	---------------

OUTLET CONTROL	No
----------------	----

ACCESSORIES

- Rack PDU
- Rack mounting accessories
- Quickstart guide
- Safety Instructions

OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)
--------------------------	---------------------------

MOUNTING DIRECTION	Vertical
-----------------------	----------

COLOR	Black
-------	-------

MATERIAL	Aluminium
----------	-----------

INPUT CONNECTION	IEC-60309 16A 3ph
------------------	-------------------

CORD LENGTH	3m
-------------	----

WATTAGE	11 kW max
AMPERAGE RATING	16A
INPUT VOLTAGE	240/415V
PHASE	Three-phase
FREQUENCY RATING	50/60 Hz
OUTLETS	(24) C13, (18) C39
NUMBER OF OUTPUTS C13	24
NUMBER OF OUTPUTS C19	18
NUMBER OF OUTPUTS (OTHER)	18
NUMBER OF OUTLETS WITH EARTH PIN	42
SNMP	Yes
ETHERNET INTERFACE	Yes
SERIAL INTERFACE	Yes
MASS CONFIGURATION	Yes
ELECTRICAL CONNECTION	Connecting cord with plug
EVALUATION	At distance
MOUNTING DIMENSION (METRICAL)	52
MOUNTING DIMENSION (STANDARDIZED)	Metric
SWITCHABLE	No
OVER VOLTAGE CATEGORY	2
SERIES	G4

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Irlanda
Eaton.com

© 2025 Eaton. Toate drepturile rezervate

Follow us on social media to get the latest product and support information.

