



Description

Halogen airfield lamp with integrated reflector

Features/Benefits

- High and constant lumen output
- Long-Lifetime (LL)
- Excellent optical adjustment
- Strong focus light

Application

- Approach and threshold lights
- Runway and taxiway lights
- Stopbar and touch-down zone lights

HALOGEN AIRFIELD LAMPS DICHROIC REFLECTOR

Type	Current A	Wattage W	Base	Axial light intensity kcd	Average life hrs.	Figure	Part number
58300	2,2	20	cable flat female connector ³⁾	min. 6,0	1000	2	58300
6144	6,6	30	cable flat female connector ³⁾	min. 16	1000	2	58334
58380	6,6	30	cable flat male connector ²⁾	min. 16	1000	2	58380
6137	6,6	35	GZ4	min. 4,5	1500	3	58314
6102	6,6	40	cable round female connector ¹⁾	min. 10,5	1500	1	58302
6102 K	6,6	40	cable round female connector ^{1) 7)}	min. 10,5	1500	1	58385
6104	6,6	40	cable flat male connector ²⁾	min. 10,5	1500	1	58303
6110	6,6	40	cable flat female connector ³⁾	min. 10,5	1500	1	58301
6110 K	6,6	40	cable flat female connector ^{3) 7)}	min. 10,5	1500	1	58383
6145LL	6,6	45	cable flat female connector ³⁾	min. 19,0	3000	2	58381
6146LL	6,6	45	cable round female connector ¹⁾	min. 19,0	3000	2	58382
6101LL	6,6	48	cable flat female connector ³⁾	min. 20,0	3000	2	58304
6106LL	6,6	48	cable flat male connector ²⁾	min. 20,0	3000	2	58305
6107LL	6,6	48	cable round female connector ¹⁾	min. 20,0	3000	2	58306
6143	6,6	48	cable flat female connector ⁶⁾	min. 23,0	1000	2	58333
58340	6,6	48	cable flat male connector ²⁾	min. 23,0	1500	2	58340
58356	6,6	48	cable flat female connector ³⁾	min. 23,0	1500	2	58356
6138	6,6	48	cable flat male / flat female ⁵⁾	min. 25,0	500	2	58317
6141	6,6	62	cable flat female connector ^{3) 4)}	**	1500	2	58335
6142	6,6	62	GX5,3	**	1500	**	58336
6103	6,6	105	cable round female connector ¹⁾	min. 30,0	1000	2	58307
6105	6,6	105	cable flat female connector ³⁾	min. 30,0	1000	2	58308
6108	6,6	105	cable flat male connector ²⁾	min. 30,0	1000	2	58310

¹⁾ 4 mm diameter

²⁾ flat male connector, complying with DIN 46248

³⁾ flat female connector, complying with DIN 46247

⁴⁾ 16" cable length

⁵⁾ with 60 mm sleeve

⁶⁾ with rectangular female connector

⁷⁾ with ceramic plate

