

Cable marker - US-WMT (30X4) GN CUS



0829998

<https://www.phoenixcontact.com/ro/produse/0829998>

Vă rugăm să țineți cont de faptul că datele afișate în acest document PDF au fost generate din catalogul nostru online. Datele complete sunt disponibile în documentația pentru utilizator. În cazul descărcărilor, se aplică Termenii și condițiile generale de utilizare ale companiei noastre.

Cable marker, can be ordered: by card, green, labeled according to customer specifications, mounting type: insert, cable diameter range: 1.5 ... 14 mm, lettering field size: 30 x 4 mm, Number of individual labels: 42



Avantajele dumneavoastră

- The US-WMT ... UniSheet labeling range includes markers for conductor marking with marking collars from the PATG/PATO ... system
- Labeling service: Phoenix Contact can custom-label all UniSheet markers according to your requirements

Date comerciale

Număr articol	0829998
Unitate de ambalare	1 Bucată
Cantitate minimă pentru comandă	1 Bucată
Indicație	Produs la comandă (nereturnabil)
Cod produs	BG8129
Pagina de catalog	Pagina 189 (C-5-2013)
GTIN	4046356613224
Greutate pe bucată (inclusiv ambalajul)	12,31 g
Greutate pe bucată (fără ambalaj)	12,31 g
Cod tarifar vamal	49119900
Țara de origine	PL

Cable marker - US-WMT (30X4) GN CUS



0829998

<https://www.phoenixcontact.com/ro/produse/0829998>

Date tehnice

Product properties

Product type	Labeled conductor marker
--------------	--------------------------

Marking

Number of individual labels	42
Number of individual labels per row	14

Marking technology

Device	5146464 THERMOMARK CARD
Ink ribbon	5146451 THERMOMARK CARD-US-MAG1 0801371 THERMOMARK-RIBBON 110-TC
Printability	Thermal transfer

Ambient conditions

Ambient temperature (operation)	-30 °C ... 80 °C
Recommended storage conditions	10 ... 30 °C / 40 ... 70 % relative humidity. Storage in the original packaging is recommended prior to processing.

Mounting

Mounting type	insert
---------------	--------

Material specifications

Color	green
Material	PVC
Flammability rating according to UL 94	V0
Components	Silicone-free

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

	VW PV 3.10.7:2005-02
Result	Test passed

UV resistance

Specification	Following ISO 4892-2:2013-03
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-30 °C ... 80 °C
Recommended storage conditions	10 ... 30 °C / 40 ... 70 % relative humidity. Storage in the original packaging is recommended prior to processing.
Recommended ambient temperature (storage/transport)	10 °C ... 30 °C
Recommended humidity (storage/transport)	40 % ... 70 %

Cable marker - US-WMT (30X4) GN CUS



0829998

<https://www.phoenixcontact.com/ro/produse/0829998>

Dimensions

Width	30 mm
Length	4.3 mm

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Cable marker - US-WMT (30X4) GN CUS



0829998

<https://www.phoenixcontact.com/ro/produse/0829998>

Clasificări

ECLASS

ECLASS-9.0	27400629
ECLASS-11.0	27281106
ECLASS-10.0.1	27400629

ETIM

ETIM 8.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39131700
-------------	----------

Phoenix Contact 2022 © - Toate drepturile rezervate

<https://www.phoenixcontact.com>

PHOENIX CONTACT România

Splaiul Unirii 165 Timpuri Noi Square TNO1, Etaj 1

Bucuresti 030133

+40 21 350 88 12 - 3

sales.ro@phoenixcontact.com