Overview

HP 250 G10 Notebook PC



- 1. Internal Dual Digital Microphone (2)
- 2. Webcam
- 3. Camera Shutter
- 4. Webcam LED
- 5 Clickpad

Left

- 6. Audio Combo Jack
- 7. SuperSpeed USB Type-C[®] 5Gbps signaling rate1 (Supports data transfer only and does not support charging or external monitors)
- 8. HDMI Port (Cable Sold Separately)
- **9.** SuperSpeed USB Type-A 5Gbps signaling rate1 port (USB 3.2 Gen 1)



Overview



Right

- 1. Power Button
- 2. Power Connector

- 3. SuperSpeed USB Type-A 5Gbps signaling rate1 port (USB 3.2 Gen 1)
- 4. Fingerprint Reader (Select Models)



Overview

At a Glance

- Preinstalled with Windows 11 Pro, Windows Home or FreeDOS
- Choice of 13th generation Intel[®] Core[™], Intel[®] Pentium[®], or Intel[®] Celeron[®] processors
- Choice of 39.62 cm (15.6") diagonal HD and Ultra Wide Viewing Angle FHD 300 nit display
- NVIDIA[®] GeForce[®] MX550 (2 GB GDDR6 dedicated) (Optional)
- Optimize your video calls with an FHD camera(optional) and temporal noise reduction that adjusts the lighting to your environment.
- Fast dual channel DDR4 SODIMM memory up to 32 GB
- Enhanced security features including discrete TPM 2.0 for RPL, Firmware TPM for ADL-N and optional Fingerprint reader.
- Weight with basic configurations starting at 3.3 lb / 1.52 kg
- Support wireless options for connectivity on the go including gigabit-speed up to Wi-Fi® 6
- Supports fast charging (50% in 45 minutes) with no impact on battery recharge cycles
- Full size, optional backlit keyboard and spill resistant, clickpad with Precision Touchpad Supported certified
- Camera shutter door to ensure privacy
- Undergoes MIL-STD 810H tests¹

1. MIL-STD 810H is not intended to demonstrate fitness of U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

NOTE: See important legal disclosures for all listed specs in their respective features sections.



PRODUCT NAME

HP 250 G10 Notebook PC

OPERATING SYSTEMS

Preinstalled

Windows 11 Pro¹ Windows 11 Pro Education¹ Windows 11 Home – HP recommends Windows 11 Pro for business¹ Windows 11 Home Single Language – HP recommends Windows 11 Pro for business¹ Windows 11 Home Education – HP recommends Windows 11 Pro for business¹ FreeDOS

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See http://www.windows.com.

PROCESSORS

		Number	Number		L3	Max Turbo I	Frequency	Base Free	uency
Processor ^{1,2,3,4}	Cores	of P-cores		Threads Cache	P-cores	E-cores	P-cores	E-cores	
Intel® Core™ i7-1360P	12	4	8	16	18 MB	5.0 GHz	3.7 GHz	2.2 GHz	1.6 GHz
Intel® Core™ i7-1355U	10	2	8	12	12 MB	5.0 GHz	3.7 GHz	1.7 GHz	1.2 GHz
Intel® Core™ i5-1340P	12	4	8	16	12 MB	4.6 GHz	3.4 GHz	1.9 GHz	1.4 GHz
Intel® Core™ i5-1335U	10	2	8	12	12 MB	4.6 GHz	3.4 GHz	1.3 GHz	0.9 GHz
Intel® Core™ i5-1334U	10	2	8	12	12 MB	4.6 GHz	3.4 GHz	1.3 GHz	0.9 GHz
Intel [®] Core™ i3-1315U	6	2	4	8	10 MB	4.5 GHz	3.3 GHz	1.2 GHz	0.9 GHz

Processor ^{1,2,3,4}	Comos	Thursda	L3	Max Frequency				Base
Processor """	Cores	Threads	Cache	Max 1-core Turbo (GHz)	Max 2-core Turbo (GHz)	Max 4-core Turbo (GHz)	Max 8-core Turbo (GHz)	Frequency
Intel® Core™ Core i3-N305	8	8	6 MB	3.8GHz	3.7GHz	3.5GHz	3.0GHz	1.8GHz
Intel® Pentium® N200	4	4	6 MB	3.7GHz	3.6GHz	3.2GHz	N/A	1.0GHz
Intel [®] Celeron [®] N100	4	4	6 MB	3.4GHz	3.4GHz	2.9GHz	3.0GHz	0.8GHz



Technical Specifications

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

5. Intel[®] Turbo Boost performance varies depending on hardware, software and overall system configuration. See www.intel.com/technology/turboboost for more information.

6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on http://www.support.hp.com.

CHIPSET

Chipset is integrated with processor

GRAPHICS

Integrated Intel[®] Iris[®] X^e Graphics ^{7,8}

Intel[®] UHD Graphics⁸

Discrete

NVIDIA® GeForce® MX550 (2 GB DDR6 dedicated) 9

Supports

Support HD decode, DX12, HDMI 1.4b⁸

7. Intel[®] Iris[®] X^e Graphics capabilities require system to be configured with Intel[®] Core[™] i5 or i7 processors and dual channel memory. Intel[®] Iris[®] X^e Graphics with Intel[®] Core[™] i5 or 7 processors and single channel memory will only function as UHD graphics.

8. HD content required to view HD images.

9. Integrated graphics depends on processor. NVIDIA® Optimus[™] technology requires an Intel processor, plus an NVIDIA® GeForce® discrete graphics configuration and is available on Windows 10 Pro OS. With NVIDIA® Optimus[™] technology, full enablement of all discrete graphics video and display features may not be supported on all systems (e.g. OpenGL applications will run on the integrated GPU or the APU as the case may be).



DISPLAY

Non-Touch

39.6 cm (15.6") diagonal FHD UWVA eDP + PSR anti-glare Low Blue Light, narrow bezel bent, 300 nits, 100% sRGB (1920 x 1080) ^{8,10,11}

39.6 cm (15.6") diagonal FHD UWVA edp anti-glare, narrow bezel bent, 250 nits, 45% NTSC (1920x1080) ^{8,10,11} 39.6 cm (15.6") diagonal FHD SVA edp anti-glare, narrow bezel bent, 250 nits, 45% NTSC (1920x1080) ^{8,10,11} 39.6 cm (15.6") diagonal HD SVA eDP anti-glare, narrow bezel bent, 250 nits, 45% NTSC (1366 x 768) ^{8,10,11}

HDMI

Port supports resolutions up to 1920 x 1200 external resolution @60 Hz

Display Size (Diagonal) 15.6" 39.6 cm (15.6")

8. HD content required to view HD images.

10. Sold separately or as an optional feature.

11. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

STORAGE AND DRIVES

Primary M.2 Storage

1 TB PCIe[®] NVMe[™] M.2 QLC Solid State Drive ¹² 1 TB PCIe[®] Gen4x4 NVMe[™] M.2 SSD TLC^{,12,13} 512 GB PCIe[®] NVMe[™] M.2 QLC Solid State Drive ¹² 256 GB PCIe[®] NVMe[™] M.2 QLC Solid State Drive ¹² 128 GB PCIe[®] NVMe[™] M.2 TLC M.2 Solid State Drive¹²

12. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.
13. Available only to HK (Hong Kong), TW(Taiwan) and CN (China).



MEMORY

Maximum Memory 32 GB DDR4-3200 MT/s SDRAM ^{14,15}

Memory

32 GB DDR4-3200 MT/s SDRAM (2 X 16 GB) ^{14,15} 16 GB DDR4-3200 MT/s SDRAM (1 X 16 GB) ^{14,15} 16 GB DDR4-3200 MT/s SDRAM (2 X 8 GB) ^{14,15} 8 GB DDR4-3200 MT/s SDRAM (1 x 8 GB) ^{14,15} 8 GB DDR4-3200 MT/s SDRAM (2 x 4 GB) ^{14,15} 4 GB DDR4-3200 MT/s SDRAM ^{14,15}

Memory Slots

2 SODIMM (RPL-Core i 3/5/7)^{14,15} All slots are customer non-accessible / non-upgradeable Support Dual Channel Memory 1 SODIMM (ADL-N i3/Pentium/Celeron)^{14,15} Support Single Channel Memory

14. All slots are non-accessible / non-upgradeable.

15. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.



NETWORKING/COMMUNICATIONS

WLAN

Realtek 8852BE-VS (1X1) Wi-Fi[®] 6 Bluetooth[®] 5.3 WLAN Wireless Card ¹⁶ Realtek 8852BE (2X2) Wi-Fi[®] 6 Bluetooth[®] 5.3 WW WLAN Wireless Card ¹⁶

Miracast

Compatible with Miracast-certified devices (For Win11)¹⁷

16. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 is backwards compatible with prior 802.11 specs.

17. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

AUDIO/MULTIMEDIA

Audio

2 Integrated stereo speakers Integrated Microphone

Camera

720p HD camera with Temporal Noise Reduction ⁸ 1080p FHD camera with Temporal Noise Reduction ⁸

8. HD content required to view HD images.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

Full Size Textured island-style Keyboard and optional Backlit and spill resistant ¹⁸

Pointing Device

Touchpad with multi-touch gesture support (PTP certified)

Function Keys

- F1 Open " How to get help in Windows 11" webpage
- F2 Brightness Down
- F3 Brightness Up
- F4 Display Switching
- F5 Blank
- F6 Mute
- F7 Volume Down
- F8 -Volume Up
- F9 Previous
- F10 Play/Pause
- F11 Next
- F12 Airplane mode



18. Backlit keyboard is an optional feature.

SOFTWARE AND SECURITY

Software

Express VPN Microsoft Office (Microsoft office sold separately. Internet access required for activation) WPS Office Dropbox Promotion ¹⁹ HP QuickDrop ²⁰ sMedio True DVD for HP MyHP Hp Support Assistant ²¹ HP PC Hardware Diagnostics Windows

Manageability Features

HP SSRM (HP Support Sent Recovery Media) ²² Windows Push Button Reset Recovery²³

Security Management

McAfee[®] LiveSafe^{™ 24}

19. 100 GB of free Dropbox storage for 12 months from date of registration. For complete details and terms of use, including cancellation policies, visit the Dropbox website at https://www.dropbox.com/help/space/hp-promotion . Internet service required and not included.

20. HP Quick Drop requires Internet access and Windows 10 and higher PC preinstalled with HP QuickDrop app and either an Android device (phone or tablet) running Android 7 or higher with the Android HP QuickDrop app, and /or an iOS device (phone or tablet) running iOS 12 or higher with the iOS HP QuickDrop app.

21. HP Sure Admin requires Windows 10 or 11 Pro or higher, HP BIOS, HP Manageability Integration Kit from http://www.hp.com/go/clientmanagement and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store.

22. Sold separately or as an optional feature.

23. Must activate within 180 days of Windows activation.

24. 30-day McAfee® LiveSafe™ trial included. Internet access required and not included. Subscription required after expiration. See http://www.McAfee.com for more details.



POWER

Power Supply

HP Smart 65 W External AC power adapter ²⁵ HP Smart 65 W EM External AC power adapter²⁵ HP Smart 45 W External AC power adapter ²⁵

Battery

HP Long Life 3-cell, 41 Wh Li-ion Polymer ^{26,27}

Power Cord 1M (3.28 feet) length power cord

Battery Life

Up to 8 hours and 24 minutes with 41 whr battery(HP Long Life 3-Cell, 41 Whr Polymaer, UMA graphic, Intel U15, display set to 200 nits, 8G memory, 256 GB SSD)²⁸

Battery Weight

1.85 lb 0.407kg

25. Availability may vary by country.

26. Battery is internal and not replaceable by customer. Serviceable by warranty.

27. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

28. MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.

WEIGHTS & DIMENSIONS

Product Weight Starting at 3.3 lb ²⁹ Starting at 1.52 kg²⁹

Product Dimensions (W x D x H)

14.17 x 9.29 x 0.73 in 36 x 23.6 x 1.86 cm

Packaging Dimensions (W x D x H) ³⁰

12-15" boxes (305mm height): 1200mm x 1000mm x 1080mm

29. Weight will vary by configuration. Does not include power adapter.

30. Product packaging size varies based on options chosen. Please contact your HP representative for your packaging size details. For detailed packaging information, access the HP Commercial Notebooks Packaging Guide.



PORTS/SLOTS

2 SuperSpeed USB Type-A 5Gbps signaling rate

1 SuperSpeed USB Type-C[®] 5Gbps signaling rate(Supports data transfer only and does not support charging or external monitors)

1 HDMI v1.4b ³¹

1 AC Power

1 Headphone/microphone combo jack

31. HDMI cable sold separately

SERVICE AND SUPPORT

1-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty. Refer to http://www.hp.com/support/batterywarranty/ for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: http://www.hp.com/go/cpc.³²

32. HP Care Packs are sold separately. Service levels and response ties for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)	
Nominal Operating Voltage Average Operating Power	19V 5.69W
Integrated graphics	
Discrete Graphics	Nvidia MX550 (Selected SKU)
Max Operating Power	ADL-N/RPL-U <45W RPL-P/RPL-U discrete <65W
Temperature	
Operating	32° to 95° F (0° to 35° C)
Non-operating	41° to 95° F (5° to 35° C) (writing optical)
Relative Humidity	
Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
Shock	
Operating	40 G, 2 ms, half-sine
Non-operating	200 G, 2 ms, half-sine
Random Vibration	
Operating	1.043 grams
Non-operating	3.5 grams
Altitude (unpressurized)	
Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Planned Industry Standard	
Certifications Regulatory Model Number	TPN-Q286
CSA/UL 62368-1	Yes
ENERGY STAR®	Certified ³³
EPEAT [®]	EPEAT [®] Gold in the United States ³⁴
FCC/ICES/CISPR/VCCI	Yes
CE MARKING	Yes
GS Mark	Yes
Related commodity should comply with	th ISO 9241 Standards.
China CCC/SRRC Taiwan BSMI/NCC	Yes Yes
Korea KCC/KC/KES	Yes
Ukraine NSoC/TEC	Yes
EAEU Compliance	Yes
Saudi Arabian Compliance	Yes
тсо	No
WW RoHS	Yes
Low Blue Light	Yes

33. Configurations of the HP 250 G10 Notebook PC that are ENERGY STAR[®] qualified are identified as HP 250 G10 Notebook PC ENERGY STAR on HP websites and on http://www.energystar.gov.



34. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit http://www.epeat.net for more information.

DISPLAYS

1. Actual brightness will be lower with touchscreen or HP Sure View.

NOTE: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

15.6 in FHD (1920 x 1080)	Outline Dimensions (W x H x D)	350.960 x 215.840 max.
Anti-Glare UWVA Low Blue	Active Area	344.160 x 193.590 typ.
Light sRGB NWBZ 300 eDP 1.4+PSR2 100 flat LCD	Weight	310g max.
Panel	Diagonal Size	15.6 inch
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	1000:1 typ
	Refresh Rate	60Hz
	Brightness	300 nits ¹
	Pixel Resolution - Format	1920 x 1080 (FHD)
	Backlight	WLED
	Pixel Resolution	RGB
	Color Gamut Coverage	sRGB 100%
	Color Depth	8
	Viewing Angle	UWVA 89 / 89 / 89 / 89
	Low Blue Light	Yes
	Power Consumption (W, EBL@ 150nits max/ 200nits max)	2.69 (max) / 3.4 (max)


Panel LCD 15.6-in FHD (1920x1080) Anti-Glare WLED SVA 45percent cq 250nits eDP 1.2 w/o PSR NWBZ ultraslim

Outline Dimensions (W x H)	350.960 x 216.750 max
Active Area	344.160 x 193.590 typ.
Weight	360g max
Diagonal Size	15.6 inch
Surface Treatment	Anti-Glare
Touch Enabled	No
Contrast Ratio	300:1 (typ)
Refresh Rate	60Hz
Brightness	250 nits ¹
Pixel Resolution - Format	1920 x 1080 (FHD)
Backlight	WLED
Pixel Resolution	RGB
Color Gamut Coverage	NTSC 45%
Color Depth	6
Viewing Angle	SVA 45/45/15/30

Not all configuration components are available in all regions/countries. c08479496 — DA17184 — Worldwide — Version 8 — August 9, 2024



Active Area344.160 x 193.590 typ.WLED UWVA 45percent cgWeight370g max250nits eDP 1.2 w/o PSR WWBZ slimDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio600:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel Resolution - Format86BColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@ 2.88 max / 3.54 maxPanel LCD 15.6-in HD (1366x768) Anti-GlareOutline Dimensions (W x H) Active Area351.030 x 216.750 max	rechnical Specific	alions	
TSOnits max/ 200nits max) Panel LCD 15.6-in FMD (1920x1080) Anti-Glare ZSOnits aDP 1.2 w/o PSR WWBZ slim Outline Dimensions (W x H) Artive Area 350.960 x 216.750 max. Artive Area Weight 370g max Diagonal Size 15.6 in ch Surface Treatment Anti-Glare Touch Enabled Koi Contrast Ratio 600:1 typ Refresh Rate 60Hz Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution Coverage NTSC 45% Color Gamut Coverage NTSC 45% Color Gamut Coverage 2.88 max / 3.54 max TSOnits max/ 200nits max) S51.030 x 216.750 max Artive Area 344.230 x 193.540 typ Wieght 370g max Stonits max/ 200nits max) S51.030 x 216.750 max Artive Area 344.230 x 193.540 typ Wieght 370g max Diagonal Size 15.6 inch Storits max/ 200nits max)<		Low Blue Light	No
1920x1080) Anti-Glare WLED UWA ASpercent (2) VUBZ slimActive Area344.160 x 193.590 typ.Weight370g maxJagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio600:1 typRefresh Rate60HzBrightness250nits 0P / 2Brightness250nits 1Pixel Resolution - Format1920 x 1080 (FHD)Pixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Gamut Coverage2.88 max / 3.54 maxTobits max/ 200nits max/351.030 x 216.750 maxActive Area344.230 x 193.540 typ.WBZ ultraslimNoContrast Ratio300:1 typBrightness15.6 inchSurface TreatmentAnti-GlareNue Surface TreatmentNoColor Gamut Coverage2.88 max / 3.54 maxStilbox 768) Anti-GlareYa4.230 x 193.540 typWBZ ultraslimNoPower Consumption (W, EBL@15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate250nits 1Brightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWIEDPixel		• • •	2.67 max / 3.33 max
WLED UWVA 4Spercent cg Sofits eDP 1.2 w/o PSR velopit 370 gmax Diagonal Size 15.6 inch Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio 600:1 typ Refresh Rate 60Hz Brightness 250nits 1 Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution RGB Color Gamut Coverage NTSC 45% Color Depth 6 Viewing Angle UWVA 85/85/855 Low Blue Light No Power Consumption (W, EBL@ 2.88 max / 3.54 max 150ints max / 200nits max) 351.030 x 216.750 max Active Area 344.230 x 193.540 typ WED SVA 4Spercent cg 250nits eDP 1.2 w/o PSR VBRE ultraslim Surface Treatment Anti-Glare Mutine Dimensions (W x H) 316 on:1 typ Refresh Rate Surface Treatment Anti-Glare VBRE ultraslim Surface Treatment Active Area 344.230 x 193.540 typ Veight 370 gmax Diagonal Size 15.6 inch Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio	Panel LCD 15.6-in FHD	Outline Dimensions (W x H)	350.960 x 216.750 max.
ZSOnits eDP 1.2 w/o PSR Weight 3/00 max WBZ slim Diagonal Size 15.6 inch WBZ slim Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio 600:1 typ Refresh Rate 60Hz Brightness 250nits 1 Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WED Pixel Resolution RGB Color Gamut Coverage NTSC 45% Color Gamut Coverage Color Gamut Coverage Viewing Angle UWVA 85/85/8/55/8/5 Low Blue Light No Power Consumption (W, EBL@) 2.88 max / 3.54 max 1366x768) Anti-Glare Mitto State WBZ ultraslim Outline Dimensions (W x H) 35.6 inch Surface Treatment Anti-Glare No WBZ ultraslim Surface Treatment Anti-Glare Mitto State WBZ ultraslim Golor Tapt Brightness 250 inits 0 ¹ Diagonal Size 15.6 inch Surface Treatment Anti-Glare ViBZ ultraslim No Contrast Ratio 300:1 typ Refresh Rate 60Hz Brightness 250nits 1 P	(1920x1080) Anti-Glare	Active Area	344.160 x 193.590 typ.
WBZ slimDiagonal Size15.6 inchSurface TreatmentNoti-GlareTouch EnabledNoContrast Ratio60HzBrightness250nits 1Pixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Gamut CoverageVWWA 85/85/855Low Blue LightNoPower Consumption (W, EBL@)250.354 (Sp.85)Stotis Softes S	WLED UWVA 45percent cg	Weight	370g max
Surface TreatmentAnti-GlareTouch EnabledNoContrast Ratio600:1 typRefresh Rate60/EBrightness250nits 1Pixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Low Blue LightNoPower Consumption (W, EBL@ 150nits max/ 200nits max)251.030 x 216.750 maxPrisel ResolutionS51.030 x 216.750 maxActive Area344.230 x 193.540 typVIED 51.6-in HD 1366X768) Anti-GlareNoPower Consumption (W, EBL@ 150nits max/ 200nits max)370 gmaxPanel LCD 15.6-in HD 1366X768) Anti-GlareNoVIED SVA 45perrent og Storits eD 1.2 w/0 PSNNoRefresh Rate300:1 typRefresh Rate306Color Gamut CoverageNiSC 45% <t< td=""><td></td><td>Diagonal Size</td><td>15.6 inch</td></t<>		Diagonal Size	15.6 inch
Contrast Ratio600:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel ResolutionRGBColor Gemut CoverageUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@2.88 max / 3.54 max 1.50nits max/ 200nits max)PaneLLCD 15.6-in HDActive AreaVILED 5VA ASPercent cg Vight351.030 x 216.750 max 344.230 x 193.540 typVILED 5VA ASPercent cg Vight351.030 x 216.750 max 344.230 x 193.540 typSurface TreatmentActive AreaNutlen Diagonal Size15.6 inchDiagonal Size15.6 inchDiagonal Size300:1 typRefresh Rate60HzTouch EnabledNoContrast Ratio300:1 typRefresh Rate60HzPixel Resolution - Format136 x 768 (HD)BacklightWLEDPixel Resolution - Format36 x 768 (HD)BacklightWLEDPixel Resolution - Format136 x 768 (HD)Pixel Resolution - Format136 x 768 (HD)Pixel Resolution - Format6Pixel Resolution - Format6Pixel Resolution - Format136 x 768 (HD)Pixel Resolution - Format136 x 768 (HD)<		Surface Treatment	Anti-Glare
Refresh Rate 60Hz Brightness 250nits ¹ Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution RGB Color Gamut Coverage NTSC 45% Color Opeth 6 Viewing Angle UWVA 85/85/855 Low Blue Light No Power Consumption (W, EBL@ 2.88 max / 3.54 max 1366x768) Anti-Glare Active Area 344.230 x 193.540 typ Vieght 370g max Diagonal Size 15.6 inch Diagonal Size 15.6 inch Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio 300:1 typ Refresh Rate 60Hz Brightness 250nits ¹ Pixel Resolution - Format 1366 x 768 (HD) Backlight WLED Pixel Resolution - Format 1366 x 768 (HD) Backlight WLED Pixel Resolution - Format 1366 x 768 (HD) Backlight WLED Pixel Resolution - Format 1366 x 768 (HD) Backlight <t< td=""><td></td><td>Touch Enabled</td><td>No</td></t<>		Touch Enabled	No
Brightness 250nits 1 Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution RGB Color Gamut Coverage NTSC 45% Color Depth 6 Viewing Angle UWVA 85/85/85/85 Low Blue Light No Power Consumption (W, EBL@ 2.88 max / 3.54 max 150nits max/ 200nits max) 2.88 max / 3.54 max Panel LCD 15.6-in HD Outline Dimensions (W x H) 351.030 x 216.750 max Active Area 344.230 x 193.540 typ WBZ ultraslim Weight 370 gmax Diagonal Size 15.6 inch Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio 300:1 typ Refresh Rate 60Hz Brightness 250nits 1 Pixel Resolution - Format 1366 x 768 (HD) Backlight WLED Pixel Resolution - Format 1366 x 768 (HD) Backlight WLED Pixel Resolution - Format 1366 x 768 (HD) Backlight WLED Pixel Resolution 6<		Contrast Ratio	600:1 typ
Parel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@ 150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare WLED SVA 45percent cg Sconits clar J. 2w/ oPSROutline Dimensions (W x H)351.030 x 216.750 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare MLED SVA 45percent cg Econits clar J. 2w/ oPSROutline Dimensions (W x H)351.030 x 216.750 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare MLED SVA 45percent cg Econits clar J. 2w/ oPSROutline Dimensions (W x H)351.030 x 216.750 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare MLED SVA 45percent cg Econits clar J. 2w/ oPSROutline Dimensions (W x H)351.030 x 216.750 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare MLED SVA 45percent cg Econits clar J. 2w/ oPSRSuffact Clare Active Area344.230 x 193.540 typWBZ ultraslimOutline Dimensions (W x H)351.030 x 216.750 maxSuffact Clare Active AreaMBZ ultraslimSuffact Clare Active Area340.230 x 193.540 typWBZ ultraslimFight State300:1 typRefresh Rate BightS00its 1Pixel Resolution - Format BacklightS166 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut Coverage Color Depth6Viewing AngleSVA 45/45/15/30 <td></td> <td>Refresh Rate</td> <td>60Hz</td>		Refresh Rate	60Hz
BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@ 150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HD NUED SVA 45percent g Sponits EDP 1.2 w/o PSROutline Dimensions (W x H)351.030 x 216.750 maxActive Area344.230 x 193.540 typWBZ ultraslimVieght370g maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel Resolution - Format6Viewing AngleSVA 45/45/15/30		Brightness	250nits ¹
Pixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@ 150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HD 1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR WWBZ ultraslimOutline Dimensions (W x H)351.030 x 216.750 maxActive Area344.230 x 193.540 typWuBZ ultraslimOutline Dimensions (W x H)370g maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format366 x 768 (HD)BacklightWLEDPixel Resolution - Format366 x 768 (HD)BacklightWLEDPixel Resolution - Format366 x 768 (HD)BacklightMISC 45%Color Gamut CoverageNTSC 45%Color Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Pixel Resolution - Format	1920 x 1080 (FHD)
Color Gamut CoverageNTSC 45%Color Depth6Viewing AngleUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@)2.88 max / 3.54 max130its max/ 200nits max)351.030 x 216.750 maxPanel LCD 15.6-in HDOutline Dimensions (W x H)351.030 x 216.750 max1366x768) Anti-GlareActive Area344.230 x 193.540 typVLED SVA 45percent ogWeight370g max250nits eDP 1.2 w/o PSRNo15.6 inchWAZ ultrastimSurface TreatmentNoContrast Ratio300:1 typRefresh Rate60HzRofresh Rate300:1 typRefresh Rate50nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel Resolution - Format366 x 768 (HD)BacklightWLEDPixel Resolution - Format1366 x 768 (HD)BacklightMLEDPixel Resolution6Color Depth6Viewing AngleSVA 45/45/15/30		Backlight	WLED
Color Depth6Viewing AngleUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@2.88 max / 3.54 max150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HDActive Area344.230 x 193.540 typ/1366x768) Anti-GlareActive Area344.230 x 193.540 typWLED SVA 45percent cgWeight370g maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Pixel Resolution	RGB
Viewing AngleUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@ 150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HD 1366x768) Anti-GlareS1.030 x 216.750 maxActive Area344.230 x 193.540 typWLED SVA 45percent cg 250nits eDP 1.2 w/o PSR WBZ ultraslimMeightJiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Color Gamut Coverage	NTSC 45%
Low Blue LightNoPower Consumption (W, EBL@ 1366x768) Anti-Glare NLED SVA 45percent cg 250nits eDP 1.2 w/o PSR351.030 x 216.750 maxActive Area344.230 x 193.540 typWBZ ultraslimWeight370g maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel Resolution StreageNTSC 45%Color Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Color Depth	6
Power Consumption (W, EBL@ 150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare NLED SVA 45percent cg 250nits eDP 1.2 w/o PSR WBZ ultraslimOutline Dimensions (W x H)351.030 x 216.750 maxActive Area344.230 x 193.540 typWeight370g maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Viewing Angle	UWVA 85/85/85
Panel LCD 15.6-in HD Outline Dimensions (W x H) 351.030 x 216.750 max Active Area 344.230 x 193.540 typ Wight 370g max Diagonal Size 15.6 inch Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio 300:1 typ Refresh Rate 60Hz Brightness 250nits 1 Pixel Resolution - Format 1366 x 768 (HD) Backlight WLED Pixel Resolution and Coverage NTSC 45% Color Gamut Coverage NTSC 45% Color Depth 6 Viewing Angle SVA 45/45/15/30		Low Blue Light	No
Active Area344.230 x 193.540 typWLED SVA 45percent cg 250nits eDP 1.2 w/o PSR WBZ ultraslimActive Area344.230 x 193.540 typWieight370 g maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Viewing AngleSVA 45/45/15/30			2.88 max / 3.54 max
WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR WBZ ultraslimWeight370g maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30	Panel LCD 15.6-in HD	Outline Dimensions (W x H)	351.030 x 216.750 max
ZSOnits eDP 1.2 w/o PSR NWBZ ultraslimWeight370 maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)Pixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30	(1366x768) Anti-Glare	Active Area	344.230 x 193.540 typ
NWBZ ultraslimDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Viewing AngleSVA 45/45/15/30	WLED SVA 45percent cg	Weight	370g max
Surface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate6HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut Coverage6Color Depth6X4 54515/30		Diagonal Size	15.6 inch
Contrast Ratio300:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Surface Treatment	Anti-Glare
Refresh Rate60HzBrightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Touch Enabled	No
Brightness250nits 1Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Contrast Ratio	300:1 typ
Pixel Resolution - Format1366 x 768 (HD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Refresh Rate	60Hz
BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Brightness	250nits ¹
Pixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Pixel Resolution - Format	1366 x 768 (HD)
Color Gamut CoverageNTSC 45%Color Depth6Viewing AngleSVA 45/45/15/30		Backlight	WLED
Color Depth6Viewing AngleSVA 45/45/15/30		Pixel Resolution	RGB
Viewing Angle SVA 45/45/15/30		Color Gamut Coverage	NTSC 45%
		Color Depth	6
Low Blue Light No		Viewing Angle	SVA 45/45/15/30
		Low Blue Light	No





Power Consumption (W, EBL@ 150nits max/ 200nits max) 2.49 max / 2.98 max



STORAGE AND DRIVES

For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

		N 2 2220		
SSD 128GB 2230 PCIe NVMe QLC (SSD 128GB 2230 PCIe	Capacity	M.2 2230 128GB		
NVMe QLC)				
		QLC		
	Interface	PCIe NVMe		
	Logical Blocks	250,069,680		
	Features	Pyrite		
SSD 1TB 2280 PCIe NVMe	Form Factor	M.2 2280		
QLC (1TB 2280 PCIe NVMe	Capacity	M.2 2200 1TB		
QLC 2nd Solid State	NAND Type			
Drive)	Interface			
	Logical Blocks	PCIe NVMe 2,000,409,264		
	Features	Pyrite		
SSD 256GB 2280 PCIe	Form Factor	M.2 2280		
NVMe QLC (SSD 256GB	Capacity	256GB		
2280 PCIe NVMe QLC)	NAND Type	QLC		
	Interface	PCIe NVMe		
	Logical Blocks	500,118,192		
	Features	Pyrite		
SSD 512GB 2280 PCIe	Form Factor	M.2 2280		
NVMe QLC	Capacity	512GB		
	NAND Type	QLC		
	Interface	PCIe NVMe		
	Logical Blocks	1,000,215,216		
	Features	Pyrite		
SSD 1 TB 2280 PCIe NVMe	Form Factor	M.2 2280		
Value	Capacity	1TB		
	NAND Type	TLC		
	Interface	PCIe NVMe Gen4X4		
	Maximum Sequential Read	3200 MB/s ±20%		
	Maximum Sequential Write	2700 MB/s ±20%		
	Logical Blocks	2,000,409,264		
	Features	Pyrite 2.0; TRIM; L1.2		
1. Available only to HK (Hon	g Kong), TW (Taiwan) and CN (China).			



Technical Specifications

NETWORKING/COMMUNICATIONS

Realtek RTL8852BE 802.11ax 2x2 Wi-Fi + Bluetooth® 5.3 Wireless Card (802.11ax 2x2, supporting gigabit data rate) ¹	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	Interoperability	Wi-Fi certified modules
	Frequency Band	•802.11b/g/n/ax 2.402 – 2.482 GHz •802.11a/n/ac/ax 4.9 – 4.95 GHz (Japan) 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz
	Data Rates	 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: max 300Mbps 802.11ac : max 866.7Mbps 802.11ax : max 1201Mbps
	Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
	Security ²	 IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only AES-CCMP: 128 bit in hardware 802.1x authentication WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification WPA3 certification IEEE 802.11i WAPI
	Network Architecture Models	Ad-hoc (Peer to Peer)
		Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power ³	• 802.11b : +18.5dBm minimum • 802.11g : +17.5dBm minimum

Technical Specifications

	 802.11n HT40(2 802.11n HT20(2 802.11n HT20(2 802.11n HT40(2 802.11ac VHT8 802.11ac HE40 	dBm minimum 2.4GHz) : +15.5dBm minimum 2.4GHz) : +14.5dBm minimum 5GHz) : +15.5dBm minimum 5GHz) : +14.5dBm minimum 0(5GHz) : +11.5dBm minimum (2.4GHz) : +10dBm minimum (5GHz) : +10dBm minimum
Power Consumption	• Idle mode :50 m	2 W 180 mW (WLAN Associated) W (WLAN unassociated) dby/Modern Standby: 10mW
Power Management	-	ress compliant power management t power saving mode
Receiver Sensitivity ⁴	802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -84dBm maximum 802.11a/g, 6Mbps : -86dBm maximum 802.11a/g, 54Mbps : -72dBm maximum 802.11n, MCS07 : -67dBm maximum 802.11n, MCS15 : -64dBm maximum 802.11ac, MCS0 : -84dBm maximum 802.11ac, MCS9 : -59dBm maximum •802.11ax, MCS11(HE40): -57dBm maximum •802.11ax, MCS11(HE80): -54dBm maximum	
Antenna type	enclosure	ntenna with spatial diversity, mounted in the display
	support WLAN MI	ual band 2.4/5 GHz antennas are provided to the card to MO communications and Bluetooth communications
Form Factor	PCI-Express M.2 I	MiniCard
Dimensions	••	3 x 22.0 x 30.0 mm 7 x 12.0 x 16.0 mm
Weight	1. Type 2230 : 2.8 2. Type 126: 1.3g	-
Operating Voltage	3.3v +/- 9%	
Temperature	Operating Non-operating	14° to 158° F (–10° to 70° C) –40° to 176° F (–40° to 80° C)
Humidity	Operating Non-operating	10% to 90% (non-condensing) 5% to 95% (non-condensing)
Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Rac LED OFF – Radio (ON N
ith Bluetooth 4.0/4.1/4.2/5.0)/5.1/5.2/5.3 Wire	less Card

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Card

Bluetooth Specification 4.0/4.1/4.2/5.0/5.1 Compliant/5.2 Compliant/5.3 Compliant



Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.

1. Wi-Fi 6 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.

Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 (802.11ax) is backwards compatible with prior 802.11 specs.

2. Check latest software/driver release for updates on supported security features.

3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Realtek RTL8852BE-VS	Wireless LAN Standards	IEEE 802.11a
802.11ax 1x1 Wi-Fi 6+		IEEE 802.11b
Bluetooth [®] 5.3 Wireless		IEEE 802.11g
Card (802.11ax 1x1) ¹		IEEE 802.11n
		IEEE 802.11ac
		IEEE 802.11ax
		IEEE 802.11d
		IEEE 802.11e
		IEEE 802.11h
		IEEE 802.11i
		IEEE 802.11k
	Interoperability	Wi-Fi certified modules
	Frequency Band	•802.11b/g/n/ax
		2.402 – 2.482 GHz
		•802.11a/n/ac/ax
		4.9 – 4.95 GHz (Japan)
		5.15 – 5.25 GHz
		5.25 – 5.35 GHz
		5.47 – 5.725 GHz
		5.825 – 5.850 GHz
	Data Rates	• 802.11b: 1, 2, 5.5, 11 Mbps
		• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
		• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
		• 802.11n: max 150Mbps



	• 802.11ac : max 433Mbps • 802.11ax : max 600Mbps
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
Security ²	 IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only AES-CCMP: 128 bit in hardware 802.1x authentication WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification WPA3 certification IEEE 802.11i WAPI EAP
Network Architecture Models	Ad-hoc (Peer to Peer)
_ .	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power ³	 802.11b : +17dBm minimum 802.11g : +16dBm minimum 802.11a : +17dBm minimum 802.11a : +17dBm minimum 802.11n HT20(2.4GHz) : +14dBm minimum 802.11n HT40(2.4GHz) : +13dBm minimum 802.11n HT20(5GHz) : +14dBm minimum 802.11n HT40(5GHz) : +13dBm minimum 802.11ac VHT80(5GHz) : +10dBm minimum 802.11ax HE40(2.4GHz) : +10dBm minimum
Power Consumption	 Transmit mode :2.5 W Receive mode :2 W Idle mode (PSP) 180 mW (WLAN Associated) Idle mode :50 mW (WLAN unassociated) Connected Standby/Modern Standby: 10mW Radio disabled: 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity⁴	802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -84dBm maximum 802.11a/g, 6Mbps : -86dBm maximum 802.11a/g, 54Mbps : -72dBm maximum 802.11n, MCS07 : -67dBm maximum 802.11n, MCS15 : -64dBm maximum 802.11ac, MCS0 : -84dBm maximum 802.11ac, MCS9 : -59dBm maximum •802.11ax, MCS11(HE40): -57dBm maximum •802.11ax, MCS11(HE80): -54dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure



Form Factor		dual band 2.4/5 GHz antennas are provided to the card to IIMO communications and Bluetooth communications MiniCard	
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm		
Weight	1. Type 2230 : 2.8g 2. Type 126: 1.3g		
Operating Voltage	3.3v +/- 9%		
Temperature	Operating Non-operating	14° to 158° F (–10° to 70° C) –40° to 176° F (–40° to 80° C)	
Humidity	Operating Non-operating	10% to 90% (non-condensing) 5% to 95% (non-condensing)	
Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)	
LED Activity	LED Amber – Radio OFF; LED OFF – Radio ON		

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Technology Card

Bluetooth Specification	4.0/4.1/4.2/5.0/5.1 Compliant/5.2 Compliant/5.3 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.

1. Wi-Fi 6 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.

Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 (802.11ax) is backwards compatible with prior 802.11 specs.

2. Check latest software/driver release for updates on supported security features.

3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).



POWER

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors

HP 65W Smart AC adapter	Dimensions (H x W x D)	3.543 x 2.008 x 1.122 in (9.0 x 5.1 x 2.85 cm)		
	Weight	0.55 lb (250 g) max (Not including power cord. Power cord varies by country.)		
	Input	100-240Vac		
		Input Efficiency	88 % at 115 Vac and 89 % at 230Vac	
		Input frequency range	47-63 Hz	
		Input AC current	Max. 1.7 A at 90 Vac	
	Output	Output power	65W	
		DC output	19.5V	
		Hold-up time	100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input	
		Output current limit	< 11.0A	
	Connector	4.5mm Barrel Type		
	Environmental Design	Operating temperature	32ºF to 95ºF (0ºto 35ºC)	
		Non-operating (storage) temperature	-4°F to 185°F (-20°to 85°C)	
		Altitude	0 to 16,400 ft (0 to 5000m)	
		Humidity	20% to 95%	
		Storage Humidity	10% to 95%	
	EMI and Safety Certifications	Worldwide safety standar EN62368-1:2014+A11, UL Agency approvals - C-UL-L Class B, CISPR32 Class B, C and K-MEPS, NOM-001 and	with LVD and EMC directives ds - IEC60950-1 and IEC62368-1 : 2018, .62368-1 JS, TUV/GS, TUV/PSE, EN55032 Class B, FCC CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) d 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, ia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC	
HP 45W Smart AC adapter	Dimensions (H x W x D)	3.74 x 1.772 x 1.043 in (9.	5x4.5x2.65cm)	
	Weight	0.44 lb (200 g) max (Not ir country.)	ncluding power cord. Power cord varies by	
	Input	100-240Vac		
		Input Efficiency	87.74 % at 115 Vac and 88.4 % at 230Vac	
		Input frequency range	47-63 Hz	
		Input AC current	Max. 1.4 A at 90 Vac	
	Output	Output power	45W	
		DC output	19.5V	
		Hold-up time	100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input	
		Output current limit	< 8.0A	



Technical Spe	cifications			
	Connector	4.5mm Barrel Type		
	Environmental Design	Operating temperature	32ºF to 95ºF (0ºto 35ºC)	
		Non-operating (storage) temperature	-4°F to 185°F (-20°to 85°C)	
		Altitude	0 to 16,400 ft (0 to 5000m)	
		Humidity	20% to 95%	
		Storage Humidity	10% to 95%	
	EMI and Safety Certifications	Worldwide safety standar EN62368-1:2014+A11, UL Agency approvals - C-UL-I Class B, CISPR32 Class B, C and K-MEPS, NOM-001 an	with LVD and EMC directives ds - IEC60950-1 and IEC62368-1 : 2018, L62368-1 US, TUV/GS, TUV/PSE, EN55032 Class B, FCC CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) d 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, lia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC	
65W EM Adapter	Dimensions (H x W x D)	4.016 x 2.165 x 1.181 in (10.2x5.5x3cm)		
	Weight	0.58 lb (265 g) max (Not including power cord. Power cord varies by country.)		
	Input	100-240Vac		
		Input Efficiency	88 % at 115 Vac and 89 % at 230Vac	
		Input frequency range	47-63 Hz	
		Input AC current	Max. 1.7 A at 90 Vac	
	Output	Output power	65W	
		DC output	19.5V	
		Hold-up time	100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input	
		Output current limit	< 11.0A	
	Connector	4.5mm Barrel Type		
	Environmental Design	Operating temperature	32°F to 95°F (0°to 35°C)	
		Non-operating (storage) temperature	-4°F to 185°F (-20°to 85°C)	
		Altitude	0 to 16,400 ft (0 to 5000m)	
		Humidity	20% to 95%	
		Storage Humidity	10% to 95%	
	EMI and Safety Certifications	Worldwide safety standar EN62368-1:2014+A11, UL Agency approvals - C-UL-I Class B, CISPR32 Class B, C and K-MEPS, NOM-001 an	with LVD and EMC directives ds - IEC60950-1 and IEC62368-1 : 2018, L62368-1 US, TUV/GS, TUV/PSE, EN55032 Class B, FCC CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) d 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, lia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC	



HP 3-cell Long Life Li-Ion (41 Wh) ¹	Weight	0.185 kg (0.407 lb) 3cell Lithium-Ion Polymer cell / 515974		
	Cells/Type			
	Energy	Voltage	11.25V	
		Amp-hour capacity	3.648Ah	
		Watt-hour capacity ¹	41.04Wh	
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)	
		Operating (Discharging)	14° to 122° F (-10° to 60° C)	
		Optional Travel Battery Available	Νο	

AUDIO

HD Stereo Codec	Realtek ALC3247
Audio I/O Ports	Audio Jack at Left. Headset connector supports a CTIA and OMTP style headset and is re-taskable
	as a Line-in, Line-out, Microphone-in or Headphone-out port
Internal Speaker Amplifier	2W class D amplifier from ALC3247
Multi-streaming Capable	multi-streaming enable
Sampling	streams to be sent to/from the front and rear jacks or integrated speaker.
Wavetable Syntheses	DAC: 24bit, 48KHz
	ADC: 16bit; 48kHz
Analog Audio	DAC: 24bit, 48KHz
	ADC: 16bit; 48kHz
# of Channels on Line-Out	2
Internal Speaker	Yes

FINGERPRINT READER

Sensor vendor	ELAN EFSA80SW
Sensor type	Capacitive
DPI resolution	508 DPI
Scan area	80 x 80 pixels
False Rejection Rate	FRR=≤ 3%
False Acceptance Rate	< 1:100K
Mobile Voltage Operation	3.0V to 3.6V
Operating Temperature	-4°F ~ 176°F (-20°C ~ 80°C)
Current Consumption	50mA Peak
Image	
Low Latency Wait For	300uA
Finger	
Capture Rate	50 frame/ sec
ESD Resistance	IEC 61000-4-2 4B (+15KV)
Detection Matrix	508 DPI / 4 mm x 4mm

ENVIRONMENTAL DATA

ECO-Label Certifications &		or is in the process of being	certified to the following approvals and may		
declarations	This product has received or is in the process of being certified to the following approvals and ma be labeled with one or more of these marks:				
uccialacions					
	IT ECO declaration US ENERGY STAR®				
	-	y Management Program (FE			
	-		See http://www.epeat.net for registration		
	status in your co	•			
		nservation Program (CECP)			
		onmental Protection Admin	istration (SEPA)		
	Taiwan Green Ma	ark			
	Korea Eco-label				
	Japan PC Green la	abel*			
Sustainable Impact	Ocean-bound plastic in s	speaker			
Specifications	• 10% post-consumer rec	ycled plastic			
	 Low halogen 				
	Outside Box and corruga	ated cushions are 100% sust	ainably sourced and recyclable		
	 Molded Paper Pulp Cush 	ion inside box is 100% susta	ainably sourced and recyclable		
	Bulk packaging available				
System Configuration	-		nd Declared Noise Emissions data for the		
	Notebook model is based	on a "Typically Configured N	Notebook".		
Energy Consumption					
(in accordance with US					
ENERGY STAR [®] test					
method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz		
Normal Operation (Sort	7.068 W	7.332 W	7.092 W		
idle)					
Normal Operation (Long	1.464 W	1.536 W	1.452 W		
idle)					
Sleep	1.464 W	1.536 W	1.452 W		
Off	0.192 W	0.252 W	0.192 W		
	NOTE:				
	Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model				
	family. HP computers marked with the ENERGY STAR [®] Logo are compliant with the applicable U.S.				
	Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model				
	family does not offer ENERGY STAR [®] compliant configurations, then energy efficiency data listed is				
	for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a				
	Microsoft Windows [®] operation	ating system.			
Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz		
near Dissipation					
Normal Operation (Short					
	24.2 BTU/hr	25.1 BTU/hr	24.3 BTU/hr		
Normal Operation (Short		25.1 BTU/hr	24.3 BTU/hr		
Normal Operation (Short idle)		25.1 BTU/hr 5.3 BTU/hr	24.3 BTU/hr 5.0 BTU/hr		
Normal Operation (Short idle) Normal Operation (Long	24.2 BTU/hr				



Γ

Technical Specifications

Τ

	* NOTE: Heat attained for o		ed on the measured watts, as	suming the service level is
Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (L _{wad} , bels)	Sound P (L _{pAm} , de	
Typically Configured – Idle		2.4	16	.1
Fixed Disk – Random writes		2.4	16	.1
Optical Drive – Sequential reads		N/A	N/	Ά
Longevity and Upgrading	This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the			
	Spare parts a production.	re available throughout the	warranty period and or for up	to "5" years after the end of
Additional Information	 This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC. This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC. This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986). This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see www.epeat.net Plastics parts weighing over 25 grams used in the product are marked per IS011469 and IS01043. This product is 96.8% recycle-able when properly disposed of at end of life. 			
Packaging Materials	External:	PAPER/Corrugated		245 g
		PAPER/Paperboard		50 g
		PAPER/Molded Pulp		56 g
	Internal:	PLASTIC/Polyethylene low	v density - LDPE	10 g
	The plastic p	backaging material contains	at least 100.0% recycled cont	ent.
RoHS Compliance	 The corrugated paper packaging materials contains at least 35.6% recycled content. HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam. We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products. We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve. 			



Technical Specifications

	To obtain a copy of the HP RoHS Compliance Statement, see HP RoHS position statement.				
Material Usage	This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at				
	http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):				
	• Asbestos				
	Certain Azo Colorants				
	Certain Brominated Flame Retardants – may not be used as flame retardants in plastics				
	Cadmium				
	Chlorinated Hydrocarbons Chlorinated Daroffing				
	Chlorinated Paraffins Dis(2) Ethylpow() phthalate (DEUD)				
	 Bis(2-Ethylhexyl) phthalate (DEHP) Benzyl butyl phthalate (BBP) 				
	 Benzyl butyl phthalate (BBP) Dibutyl phthalate (DBP) 				
	 Disobutyl phthalate (DBP) Disobutyl phthalate (DBP) 				
	Formaldehyde				
	Halogenated Diphenyl Methanes				
	Lead carbonates and sulfates				
	Lead and Lead compounds				
	Mercuric Oxide Batteries				
	Nickel – finishes must not be used on the external surface designed to be frequently				
	handled or carried by the user.				
	Ozone Depleting Substances				
	Polybrominated Biphenyls (PBBs)				
	Polybrominated Biphenyl Ethers (PBBEs)				
	Polybrominated Biphenyl Oxides (PBBOs)				
	Polychlorinated Biphenyl (PCB)				
	Polychlorinated Terphenyls (PCT)				
	 Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has 				
	 been voluntarily removed from most applications. Radioactive Substances 				
	 Radioactive Substances Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO) 				
Packaging Usage					
. actuging Usuge	 HP follows these guidelines to decrease the environmental impact of product packaging: Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in 				
	packaging materials.				
	 Eliminate the use of ozone-depleting substances (ODS) in packaging materials. 				
	 Design packaging materials for ease of disassembly. 				
	Maximize the use of post-consumer recycled content materials in packaging materials.				
	• Use readily recyclable packaging materials such as paper and corrugated materials.				
	Reduce size and weight of packages to improve transportation fuel efficiency.				
	• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.				
End-of-life Management	HP offers end-of-life HP product return and recycling programs in many geographic areas. To				
and Recycling	recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest				
	HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible				
	manner.				



	The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.				
HP, Inc. Corporate Environmental	For more information about HP's commitment to the environment:				
Information	Global Citizenship Report				
	http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html Eco-label certifications				
	http://www8.hp.com/us/en/hp-information/environment/ecolabels.html ISO 14001 certificates:				
	http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842 and				
	http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf				
footnotes	Percentage of ocean-bound plastic contained in each component varies by product				
	• Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.				
	• External power supplies, WWAN modules, power cords, cables and peripherals excluded.				
	 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers. 				
	• Fiber cushions made from 100% recycled wood fiber and organic materials.				
	Plastic cushions are made from >90% recycled plastic.				

COUNTRY OF ORIGIN

China

Options and Accessories (Sold separately and availability may vary by country)

Туре	Description	Part Number
Audio	HP Wired USB-A Stereo Headset	428K6AA
	HP Wired 3.5mm Stereo Headset	428K7AA
Cases	HP 115 15.6 Laptop Backpack	8DV45AA#ACJ
	HP 215 15.6 Laptop Backpack	35L98AA#ACJ
	HP 225 15.6 Laptop Backpack	2P7U6AA#ACJ
	HP 235 15.6 Laptop Backpack	35M00AA#ACJ
	HP 315 15.6 Laptop Backpack	35L97AA#ACJ
	HP Prelude G2 15.6 Backpack	1E7D6AA
	HP Prelude G2 15.6 Top Load	1E7D7AA
	HP Prelude Pro Recycled 15.6 Backpack	1X644AA
	HP Prelude Pro Recycled 15.6 Top Load	1X645AA
	HP Renew Business 15.6 Laptop Bag	3E5F8AA
	HP Renew Business 17.3 Laptop Backpack	3E2U5AA
	HP Renew Business 17.3 Laptop Bag	3E2U6AA
	HP Renew Executive 16 Laptop Backpack	6B8Y1AA
	HP Renew Executive 16 Laptop Bag	6B8Y2AA
	HP Travel 18L 15.6 Iron Gray Laptop Backpack	6H2D9AA
	HP Travel 25L 15.6 Iron Gray Laptop Backpack	6H2D8AA
Adapter	HP USB-C to RJ45 Adapter G2	4Z527AA
	HP USB 3.0 to Gigabit RJ45 Adapter G2	4Z7Z7AA
	HP HDMI to VGA Adapter	H4F02AA
Keyboard/Combo	HP 125 WD USB Keyboard	266C9AA
	HP 320K WD USB Keyboard	9SR37AA
	HP 155 Wired Mouse and Keyboard Combo	5B8COAA#ACJ
	HP 225 Antimicrobial Wired Mouse and Keyboard Combo	286K3AA#AB2
	HP 225 Wired Mouse and Keyboard Combo	286J4AA
	HP 235 Wireless Mouse and Keyboard Combo	1Y4D0AA
	HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA
Mouse	HP 125 USB-A Wired Mouse	265A9AA
	HP 128 USB Laser Wired Mouse	265D9AA
	HP 155 USB-A Wired Mouse	5B8B7AA#ACJ
	HP 320M USB-A Wired Mouse	9VA80AA
	HP USB-A+Bluetooth Travel Bluetooth Mouse	6SP30AA
	HP USB Premium Wireless Mouse	1JR31AA
	HP 435 Bluetooth 5.0 + Wireless 2.4GHz Multi-Device Wireless Mouse	3B4Q5AA



Options and Accessories (Sold separately and availability may vary by country)

Power	HP 65W 4.5 mm Smart AC Power Adapter	H6Y89AA
Commodity	HP USB DVD-Writer EXT ODD	F2B56AA
Video	HP 325 FHD USB-A Webcam	53X27AA



Change Log

Date of change:	Version History:		Description of change:
March 21, 2023	V1 to V2	Added	Environmental Data and update call out in Overview section
March 30, 2023	V2 to V3	Updated	Ports and Slots section
April 19, 2023	V3 to V4	Updated	At a Glance section
May 18, 2023	V4 to V5	Updated	Storage and Drives section
April 24, 2024	V5 to V6	Updated	Memory Section
April 15, 2024	V6 to V7	Added	Processor Section
August 9, 2024	V7 to V8	Updated	Weights & Dimensions Section

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort[™] and the DisplayPort[™] logo are trademarks owned by the Video Electronics Standards Association (VESA[®]) in the United States and other countries. USB Type-C[®] and USB-C[®] are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

