

|                               |                                                    |
|-------------------------------|----------------------------------------------------|
| Type code                     | ACQ580-01-12A7-4+B056+E223+J429                    |
| Nominal voltage               | 400 V                                              |
| Typical motor power (PN)      | 5.5 kW                                             |
| Nominal output (IN) (PN)      | 12.6 A                                             |
| Maximum output current (Imax) | 14.1 A                                             |
| Light-overload use (ILD, PLD) | 12 A, 5.5 kW                                       |
| Frame Size                    | R1                                                 |
| Dimensions (HxWxD)            | 403x125x233 mm                                     |
| Net Weight                    | 4.8 kg                                             |
| Gross Weight                  | 7.3 kg                                             |
| Standard Features             | Wall mountable drive                               |
|                               | Drives for Water - Pump control program            |
|                               | Safe Torque Off, SIL 3 PL e                        |
|                               | Built-in DC choke                                  |
|                               | Conformal coated circuit boards                    |
|                               | Multilingual Quick installation and start-up guide |
|                               | Embedded Modbus, RTU                               |
|                               | Conduit box with cable lead thru entry             |
|                               | Standard warranty                                  |

#### Options

|      |                                                           |
|------|-----------------------------------------------------------|
| B056 | IP 55 (UL Type 12)                                        |
| E223 | EMC filter, category C1 for earthed network (R1-R5)       |
| J429 | Assistant control panel ACH-AP-W with Bluetooth interface |