

WATER STILL

WATER STILL

With Stainless Steel Chamber

M 4

Distillation water capacity
Cooling water consumption (max.)
Cooling water output temperature
Heater type
Safety measure

4 lt / hour
40 lt / hour
50 °C
Stainless steel tube resistance
Water level control , magnetic switch,
leakage current fuse

Casing material
Interior material
Connection materials
Water filter
Internal tank capacity

Stainless steel
Stainless steel
PVC and silicon hose
External

Fuse (automatic)
Power rating
Monitoring influent pressure
Power supply
Overall dimensions (w x h x d)
Net weight
Gross weight

8 lt.
25 Amps.
3000 W
With analog manometer
AC 190-240 V / 50-60 Hz
65 x 52 x 25 cm.
18 kg.
20 kg.

M 8

8 lt / hour
80 lt / hour
50 °C
Stainless steel tube resistance
Water level control , magnetic switch,
leakage current fuse

Stainless steel
Stainless steel
PVC and silicon hose
External

16 lt.
3x25 Amps.
3x2 kW
With analog manometer
AC 380 V / 50-60 Hz
72 x 66 x 34 cm.
32 kg.
35 kg.

M 12

12 lt / hour
120 lt / hour
50 °C
Stainless steel tube resistance
Water level control , magnetic switch,
leakage current fuse

Stainless steel
Stainless steel
PVC and silicon hose
External

24 lt.
3x25 Amps.
3x2,4 kW
With analog manometer
AC 380 V / 50-60 Hz
72 x 66 x 34 cm.
32 kg.
35 kg.



 elektro-mag®

Ikitelli O.S.B. Demirciler Sitesi, B7 Blok No:153 Basaksehir, 34490 - Istanbul / TURKEY

Tel: +90 212 549 55 25 Fax: +90 212 549 52 09

export@elektro-mag.com www.elektro-mag.com

