

ASKIR C30_{BR} ON CASTORS

A surgical suction unit indicated for professional use especially in environments where there is no connection to power line, such as field hospitals.

Thanks to its powerful aspiration and to the double collection system it finds application in general surgery.

The device is suitable for nasal, oral and endotracheal aspiration of bodily fluids (mucus or catarrh) from adults and children.

MAIN FEATURES

Non-stop operation

24h In order to guarantee the best performance, engine can work without interruption 24/24h.

Easy to maneuvre

Conveniently placed on a 5-castors stand to make its displacement easier.

High-quality materials

The chassis is made of UL94-VO durable, flame retardant, corrosion resistant and rust-proof ABS plastic.

Long lasting accessories

All accessories are made in resistant, autoclavable materials to guarantee safety and hygiene over time.

Universal use

Operates with 100-240 V~ 50/60 Hz AC/DC adapter or rechargeable battery.

INCLUDED ACCESSORIES

2 REUSABLE JARS OR DISPOSABLE SYSTEM

depending on configuration

REUSABLE SILICONE TUBES

Ø 8/14 mm

BI-CONICAL CONNECTORS

Ø 10/11/12 mm

ANTIBACTERIAL & HYDROPHOBIC FILTER

UNIVERSAL AC/DC POWER ADAPTER

with European plug

Best Seller configuration

ASKIR C30BR +2000 mL reusable jar in Makrolon Polycarbonate (121°C)

Product code: RE 410251

Select your configuration at page 46

The warranty lapses immediately if the unit is used without all the required accessories or with non-original CA-MI accessories.



APPLICATIONS

CE 0123

GENERAL SURGERY	NEUROSURGERY
FIELD HOSPITAL	OBSTETRICS
OPERATING THEATRE	DENTAL PRACTICE

TECHNICAL DATA

MOTOR	Oiless and maintenance-free piston pump
POWER FEEDING	
Power adapter	IN: 100-240 V~ 50/60 Hz 100 VA OUT: 14 V == 4,29 A
Lead Battery	12 V == 4 A
BATTERY AUTONOMY	60 min after 4 h recharge
ISO 10079-1	High vacuum / High flow
CLASSIFICATION	
MAX VACCUM	-0,80 Bar -80 kPa -600 mmHg value at sea level different altitudes may affect it
FREE AIR FLOW RATE	36 L/min
NOISE LEVEL	65,5 dB(A)
DUTY CYCLE	Non-stop operation (by mains only)
WEIGHT	8 Kg
DIMENSIONS	32 x 30 x 90 cm
WARRANTY	2 years
SHIPPING CARTON	1 unit
MANUFACTURING COUNTRY	Italy

NEW BR HOSPIVAC ON CASTORS

A surgical suction unit indicated for professional use especially in environments where there is no connection to power line, such as field hospitals.

Thanks to its powerful special design it finds application during rescue, emergency or patient transfers.

The device is suitable for nasal, oral and endotracheal aspiration of bodily fluids (mucus or catarrh) from adults and children.

MAIN FEATURES

Non-stop operation

24h In order to guarantee the best performance, engine can work without interruption 24/24h.

Change-over system

Allows operator to switch to the next jar without interrupting suction.

3+ Safety protection

3 protection systems against internal reflux.

Multi-Purpose Rail System

Flexible rail that allows the rapid change of containers.

INCLUDED ACCESSORIES

2 REUSABLE JARS OR DISPOSABLE SYSTEM

depending on configuration

2 SET OF AUTOCLAVABLE SILICONE TUBES

Ø 8/14 mm

2 ANTIBACTERIAL & HYDROPHOBIC FILTER

single-patient

2 SAFETY TRAP BOTTLE

220 mL

2 BI-CONICAL CONNECTOR

Ø 10/11/12 mm

2 JAR ACCOMODATION RINGS

size depending on the model

2 AIR SUCTION INLET

1 POWER CORD WITH SCHUKO PLUG

1 FOOT-SWITCH CONTROL

with intermittent or continuous operation

CHANGE-OVER SYSTEM

from jar to jar by soft-touch keys

Best Seller configuration

NEW HOSPIVAC BR +2x 2000 mL reusable jar in Makrolon Polycarbonate (121°C)

Product code: RE 410400

Select your configuration at page 46

The warranty lapses immediately if the unit is used without all the required accessories or with non-original CA-MI accessories.



APPLICATIONS

CE 0123

FIELD HOSPITAL	GENERAL SURGERY
NEUROSURGERY	GINECOLOGY
OPERATING THEATRE	DENTAL PRACTICE

TECHNICAL DATA

MOTOR	Oiless and maintenance-free piston pump
POWER FEEDING	220-230V / 50-60Hz
Battery	12V / 20A
ISO 10079-1 CLASSIFICATION	High vacuum / High flow
MAX VACUUM	-0.85 bar -85 kPa -637.5 mmHg value at sea level different altitudes may affect it
MAX FREE AIR FLOW RATE	50 L/min
NOISE LEVEL	60.5 dB(A)
DUTY CYCLE	Non-stop operation
WEIGHT	20 Kg
DIMENSIONS	46 x 42 x 85 cm
WARRANTY	2 years
SHIPPING CARTON	1
MANUFACTURING COUNTRY	Italy