

BS.1152-EPL

bScope binocular microscope, HWF 10x/20 mm eyepieces and quadruple nosepiece with E-plan EPL 4/10/S40/S100x oil objectives, 131 x 152/197 mm stage with integrated mechanical 75 x 36 mm rackless X-Y stage. 3 W NeoLED illumination and integrated power supply. Supplied without rechargeable batteries



HWF 10x/20 mm eyepieces

Binocular head, Siedentopf type, 30° inclined tubes. Interpupillary distance 48-76 mm

Reversed quadruple revolving nosepiece on ball-bearings

E-plan EPL 4x, 10x, S40x, S100x oil immersion objectives

All optics are anti-fungus treated and anti-reflection coated for maximum light throughput

Coaxial coarse and fine adjustments with 180 graduations. Precision 1.1 μ m, 0.2 mm per rotation. Total travel approximately 19 mm. Friction adjustment

Plain 131 x 152/197 mm rackless stage with 75 x 36 mm mechanical rackless stage

Height adjustable Abbe color coded condenser N.A. 1.25 with iris diaphragm and filter holder

3 W NeoLED illumination. Internal power supply 100-240 V (CE)

Supplied with power cord, dust cover, 5 ml immersion oil in styrofoam case and without rechargeable AA-type batteries