

TECHNICAL SPECIFICATION

Ventilation mode

V-A/C, P-A/C, V-SIMV, P-SIMV, CPAP/PSV, PRVC,PRVC- SIMV, DuoLevel, APRV, CPRV, PSV-S/T, PSV, NCPAP, SIGH, MANU

Technical specification adjusting parameter

Freq	1 /min ~ 150 /min SIMV mode: 1 /min ~ 60 /min Adult : 1 /min ~1 00 /min Neonatal: 1 /min ~ 150 /min
Tinsp	0.10 s ~ 30.00 s
I:E	4:1 ~ 1:10
VT	Adult: 100 mL ~ 2000 mL Pediatric: 20 mL ~ 300 mL Neonatal: 2.0 mL ~ 100 mL
PEEP	OFF,1 cmH ₂ O ~ 50 cmH ₂ O -20 cmH ₂ O ~ -0.5 cmH ₂ O Turn off auxiliary triggering
Ftr	0.5 L/min ~ 20.0 L/min Turn off auxiliary triggering
ΔP	Adult, Pediatric: 5 cmH ₂ O ~ 80 cmH ₂ O Neonatal: 1 cmH ₂ O ~ 80 cmH ₂ O
Ps	0 cmH ₂ O ~ 80 cmH ₂ O
Oxygen concentration	21 % ~100 %
Tip	OFF, 5 % ~ 60 %
Sigh cycle	1 ~ 20 times
Suffocation warning	5 s ~ 60 s
Airway pressure	10 cmH ₂ O ~ 85 cmH ₂ O
Pressure limit	≤115 cmH ₂ O
Neutralizer gas	Maximum output flow 6 L/min~9 L/min

Wooden case packing size

Main engine: L 570 * W 530 * H 610 mm G.W.: 20 KG
Trolley: L 920 * W 680 * H 440 mm G.W.: 30KG
Gas cylinder: L 650 * W 330 * H 290 mm

Alarm and protection

High airway pressure alarm	Suffocation warning
High tidal volume alarm	Oxygen deficit
High tidal volume alarm	High ETCO ₂ Alarm
High minute volume alarm	Low ETCO ₂ Alarm
Low minute volume alarm	High respiratory rate alarm
High oxygen concentration alarm	Low respiratory rate alarm
Low oxygen concentration alarm	Pressure safety relief valve
High positive end-tidal pressure alarm	Continuous pressure alarm

Working condition

Voltage	100 - 240V ~
Frequency	50/60Hz
Input power	100VA
Gas source	O ₂ (Medical grade)
Gas pressure	280 kPa ~ 600 kPa
Ambient temperature range	+ 5 °C ~ + 40 °C

Monitoring parameter

Frequency (Freq)	0 /min ~ 200 /min
Tidal volume (Vt)	0 mL ~ 4000 mL
MV	Adult, Pediatric: 0.0 L/min ~ 100.0 L/min Neonatal: 0.0 L/min ~ 30.0 L/min
Airway pressure	-20 cmH ₂ O ~ 120 cmH ₂ O
Dynamic lung compliance monitoring	0 mL/cmH ₂ O ~ 300 mL/cmH ₂ O
Oxygen concentration	15 % ~ 100 %
ETCO ₂ Concentration	0 mmHg ~ 150 mmHg
Oxygen concentration	0 % ~ 100 %

Oscillogram

P-T (Pressure-Time)
F-T (Flow-Time)
V-T (Volume-Time)
CO ₂ -T (End-Tidal CO ₂ - Time) / (SPO ₂ - T)
P-V Loop (Pressure-Volume Loop) / F-V Loop (Flow-Volume Loop)



Other models for your reference The picture is for reference only. For more information, please contact Superstar Medical sales representatives.



S1900A

ICU VENTILATOR

ADULT · PEDIATRIC · NEONATAL

S1900A ICU VENTILATOR

Application

This product is intended for use in an intensive care unit within a specialized medical facility, or during transit within a specialized medical facility. It is used for ventilation assistance and respiratory support for adult, pediatric and neonatal. This product should be handled by well-trained, authorized medical person. This product cannot be used in magnetic resonance imaging (MRI) environments.



Friendly interface

With neonatal, pediatric and adult mode.
Tidal volume start with 2ml, ensure all range patient using.
Different color choice ensure better view of waveform.
Automatic self testing ensure the safety using environment.

Features

- Electronically driven and electronically control
- 15.6 Inches colorful touch LCD screen
- Volume control and pressure limit
- Both non-invasive and invasive ventilation mode
- Various alarming function
- Compliance compensation function
- Built-in battery, when AC power failure, automatic exchange to backup power
- Same brand medical trolley
- ETCO₂ monitoring
- SPO₂ monitoring
- Operation key freeze function
- Oxygenation function
- Suction function
- Oxygen therapy function

Safety

31 types of sound and visual alarm information, easier for users to do some error checking and troubleshooting.
Built-in oxygen concentration sensor, ensure stable precision of oxygen concentration.
Easy to move with four casters, easy to stop with two brakes.
Separate design of electronic circuit and gas flow rate keep safe running of ventilator.
Compact long life internal battery can provide emergency power, avoid risk of patient.
Self-check before operation, eliminate system mistake.



Humidifier

Heat and wet breathing gas, makes it more comfortable for patient to breathe in.

3 types of humidifier for your choices: one with thermometer for standard, one with digital shown for option, another one with dual pipeline heating function and servo control function for option.



Breathing circuit

High temperature resistance breathing pipelines is reusable and anti-pollution.

Oxygen concentration sensor