

EN Certified Biological Safety Cabinet




Color Touch Screen
Touch operation, real-time and clearer display of various values and appointment timing function.

BIOBASE

E-mail: export@biobase.com

www.biobase.cc / www.biobase.com



Anti-paper dust structure



Wind Speed Sensor



Stepper Motor




Work Zone
Work zone, made of 304 stainless steel, is surrounded by negative pressure.



Footmaster Caster
Universal caster with brake and leveling feet.



European Standard Socket



UV Lamp
Emission of 253.7 nanometers for most efficient decontamination.

ADVANTAGE

- 7-inch large touch color display; touch operation, real-time and clearer display of various values of the safety cabinet, dynamic air flow pattern diagram, fault alarm sound and light prompt.
- The power-on password can be set to prevent mis-operation by irrelevant personnel.
- Automatically adjust the wind speed.
- Power-off memory, restore the state before power-off, and have a visual reminder to alarm.
- Side windows on both sides for easy observation.
- The operation area is integrally formed, which is easy to disassemble and clean.
- A breeze speed sensor is equipped at the working area and the outer exhaust air outlet to detect the wind speed in real time.
- It can be used both manually and electrically, and the glass door can be pulled down to close the front window when the power is off.
- The cabinet is separated from the base. The height of the adjustable base can be customized.
- Interlocking function: UV lamp and front window; UV lamp and fan; LED lamp; fan and front window.
- It has an appointment timing function, which can automatically set the timing of turning on, turning off and the running time of the UV lamp, fan, and socket.
- The closing of the front window can double trigger the signal, so that the sterilization and disinfection function of the UV lamp can be turned on normally.
- Anti-paper dust structure at the air inlet to prevent paper dust from entering the air cavity.
- Split countertop is easier to clean.
- One button front window lifting function.

TECHNICAL PARAMETERS

Model	BSC-2FA2-HA
External Size(W*D*H)	700*700*2000mm
Internal Size(W*D*H)	600*500*540mm
Work Surface Height	750mm
Max Opening Height	350mm
Safe Operation Opening Height	200mm
Airflow	Inflow 230m ³ /h(135cfm)
Volume	Down flow 65%; 428 m ³ /h(252cfm)
	Exhaust 35%; 230m ³ /h(135cfm)
Front Window	Manual and electric, glass thickness> 5mm, anti-ultraviolet
ULPA Filter	2pcs, filtration efficiency for 0.12um particles:99.9995%
Illumination	≥1000Lux
Noise	EN12469s65dB
Display	Color Touch Screen
European Standard Socket	230V, 3A
Power Supply	AC 230V, 50/60Hz
Rated Power	950W
Alarm	Alarm for abnormal wind speed, alarm for glass door not at safe height, alarm for abnormal power failure
Motor	DC single fan, Adjustable speed, high efficiency, low power
Material	Working Area: 304 stainless steel, side window glass; Frame and decorative plate: cold-rolled steel with anti-bacteria powder coating
LED Lamp	8W*2
UV Lamp	15W
Standard Accessory	Cabinet*1, Base stand*1, LED lamp*2, UV lamp*2, Drain ball valve*1, European Standard Socket*2
Optional Accessory	Arm rest, Formalin fumigation sterilizer, Infrared sterilizer S.S. water tap*2, S.S. gas tap*2
Package Size (W*D*H)	Carton: 820*910*1500mm
Gross Weight	170kg