



PRODUCTION STANDARDS		
DESIGN	EN 1171	
END CONNECTION	FLANGED EN 1092-2 / ISO 7005-2	
FACE TO FACE	EN 558 SERİ 14 / DIN 3202 F4	
MARKING	EN 19	
PRESSURE RATING	PN16	
TEST	EN 12266-1	
VALVE PRESSURE TEST		
SHELL STRENGTH	SHELL TIGHTNESS	SEAT TIGHTNESS
24 Bar	18 Bar	18 Bar

NO MATERIAL SELECTION

- 1 BODY / EN GJS 500 (Ductile Iron)
- 2 COVER / EN GJS 500 (Ductile Iron)
- 3 DISC / EN GJS 500 (Ductile Iron) + EPDM
- 4 STEM / Stainless Steel 1.4021
- 5 COVER SEALING / EPDM

DIMENSIONS								
DN (mm)	D	K	d	Øl x n	f	b	L	H
350	520	470	429	28x16	3	26,5	290	932
400	580	525	480	31x16	3	30	310	1007
450	640	585	548	31x20	4	31,5	330	1086
500	715	650	609	34x20	3	32	352	1244
600	840	770	720	37x20	4	36	392	1410

	NAME	DATE	SCALE
SKETCHER	Y. BOZKURT	11.12.2023	1/3
CONTROL	Ö.ÇAKIR	11.12.2023	

PRODUCT NAME

**DN 350-600 GATE VALVES
(Gearbox & Actuator
Compatible)**

FAF YANASANAYI
REVISION:00
FAF 6000E