TECHNICAL FILE

F-2008 Safety Goggle

Material: PVC+PC, Size 185X75 mm

Description

The safety goggles are designed to protect the eyes against mechanical risks caused by flying particles in industry, laboratories, educational establishments, DIY activities etc.

It must be worn for the whole duration of exposure to hazards, leave the work area if dizziness or irritation occurs, or if the spectacle/goggle becomes damaged. The lenses are made of impact resistant polycarbonate. This eye protector is not intended for welding use.

USAGE, STORAGE AND MAINTENANCE

In use, ensure the eye protector fits comfortably over the eyes. This eye protector should be stored in a case, out of direct sunlight, away from chemicals and abrasive substances, in a clean, dry, dust-free environment when not in use or during transportation.

To clean, rinse in 1% solution of mild detergent and dry with a dry fluff-free soft cloth. DO NOT USE abrasive cleansers. If necessary, a non-aggressive household disinfectant may be used. Under normal circumstances the eye protector should offer adequate protection for 3 years from manufacturers date. The manufacturer month and year can be found on the PPE component.

WARNING

- When in contact with the skin the frame may cause allergic reactions to susceptible individuals. If this is the case doctor's advice should be sought.
- For optimum protection when working, wear the goggle continuously.
- Clear lenses offer no protection against optical radiation given off during welding and cutting work.
- Do not continue using the goggle if the frame is broken or snapped.
- Do not continue using the eyewear if the lenses are dull, damaged or scratched-replace them.
- Do not continue using the eyewear if cleaning does not improve vision.
- Always replace the complete eye protectors immediately if the ocular become scratch and damage.
- The goggles for protection against high speed particles worn over standard ophthalmic spectacles may transmit impacts, thus creating a hazard to the wearer.
- If protection against high speed particles at extremes of temperature is required then the selected goggle should be marked with the letter T immediately after the impact letter
- If the impact letter is not followed by the letter T then the eye protector shall only be used against High speed particles at room temperature. If in doubt, consult your supplier.
- Ensure that you follow all instructions and warnings
- Improper use of this product may endanger the wearer 's health.
- Do not modify the goggles.
- Retain this information.

Specifications

Optical class: 1

Material lenses: polycarbonate

Frame: PVC

Marking:

(1) Lens

16321	Standard number
JYT	Identification of the manufacturer
1	Optical class
D	Symbol for high-speed impact
CE	CE marking

(2) Frame

16321	Standard number
JYT	Identification of the manufacturer
F-2008	Model
1-M	This protector is appropriate for the head form 1-M
CE	CE marking

Cleaning and Storage

Flush frame with lukewarm water, then wipe it with dry cloth. Use compressed air to blow dust on ocular surface. If the ocular is scratched, it must be replaced. DO NOT use solvents. Store this product in a dry place, sheltered from sun light.

Packing/Transportation

Pack the safety goggles in cartons when transporting.

Service life

The period of obsolescence of this product is 3 years.

Manufacture: Jinhua City Jinhan Safety Tools Co., Ltd.

Address: No.8, Chuangye Road, Luodian Industrial District, Jinhua City, Zhejiang Province, China