

## DECLARAȚIE

**privind dotările specifice, utilajul și echipamentul necesar pentru îndeplinirea  
corespunzătoare a contractului**

Nr. d/o	Denumirea principalelor utilaje, echipamente, mijloace de transport, baze de producție (ateliere, depozite, spații de cazare) și laboratoare propuse de ofertant ca necesare pentru prestarea serviciilor, rezultate în baza tehnologiilor pe care el urmează să le adopte	Unitatea de măsură (bucăți și seturi)	Asigurate din dotare	Asigurate de la terți sau din alte surse
0	1	2	3	4
1.	Equipment for simultaneous interpreting, BOSCH DCN + Integrus	2	Da	Nu
2.	Audipack Booths, ISO6400	4	Da	Nu
3.	Equipment for simultaneous interpreting, BOSCH DCN/CCS1000	1	Da	Nu
4	Notebooks HP with Windows 10, MS office	24	Da	Nu
5	Imprimante Konica Minolta C257i-FC-20-BA	3	Da	Nu
6	Led 11m x 3.5m impartit in 3 ecrane si anume 6m x 3.5m - 1 buc, si 2.5m x 3.5m - 2 buc, indoor pitch 3.9mm 500mm x 500mm cabinet 128 pixel x 128 pixel 16384 pixel	1	Da	Nu
7	Camera video: 1.0-type Exmor R™ CMOS Sensor NXCAM camcorder with maximum 48x zoom lens and 3 independent manual lens rings recording XAVC S, AVCHD and DV	7	Da	Nu
8	Microfoane Radio -Supercardioid 120 dB dynamic range Audio signal: 24 bit / 48 kHz AES-256 encryption for tap-proof transmission 22 compatible channels in an 8 MHz TV band Switchable transmission power 1/10 mW 9.5" metal receiver Detachable BNC antennas Ethernet port for system monitoring and configuration Frequency transmission via infrared interface Output: XLR/jack Frequency band: H51 (534 - 598 MHz)	6	Da	Nu

9	Boxe - L-Acoustics X15 HiQ	4	Da	Nu
10	Mixer - 16 mic/line inputs with balanced XLR/TRS jack, and direct output.100mm Faders – throughout 4-band EQ – comprehensive equalisation with 2 sweepable mids 6 auxiliary sends – 2 pre, 2 switched, 2 post fade (may be reconfigured) 2 stereo returns – on TRS jack Dedicated mono output fader with innovative mode for control of aux fed subs Independent A-B output to feed any number of applications, including a 2-track recorder, monitor foldback or speaker fills	1	Da	Nu
11	TV ecran 4k 50 inci pe stativ	3	Da	Nu
12	Proiector ACER FullHD :4200 Lumen X-ki: 1920x1080 HDMI / VGA /	3	Da	Nu
13	Microfoane Radio -Supercardioid 120 dB dynamic range Audio signal: 24 bit / 48 kHz AES-256 encryption for tap-proof transmission 22 compatible channels in an 8 MHz TV band Switchable transmission power 1/10 mW 9.5" metal receiver Detachable BNC antennas Ethernet port for system monitoring and configuration Frequency transmission via infrared interface Output: XLR/jack Frequency band: H51 (534 - 598 MHz)	2	Da	Nu
14	Hikvision -10/S2 32X Zoom POE Smart Track PTZ Network Security Camera	1	Da	Nu
15	Placa audio pentru distribuire sunet cu iesire XLR si Jack	1	Da	Nu
16	Placa video pentru distribuire video	1	Da	Nu
17	Carcasa din lemn cu baner imprimat 10mx4m pentru o fotografie de familie	1	Da	Nu
18	Carcasa din lemn cu baner imprimat (4 m lățime x 2,5 m înălțime)	2	Da	Nu
19	Carcasa din lemn cu baner imprimat (1.5 m lungime x 1 m latime si 3 inaltime)	4	Da	Nu
20	Boxe The dawn of a new KARA 2-way active, dual 8" Max SPL 142 DB Bandwidth 55Hz-20KHz Transducers LF: 2x 8" HF 1 x 3" Variable	8	Da	Nu

	Curvature Line source			
21	Boxe - L-Acoustics X15 HiQ	4	Da	Nu
22	SB18 Hight-power subwoofer 18", Omni Cardio subwoofer Max SPL 138 dB, low frequency limit 32Hz Transducers LF: 1x 18"	4	Da	Nu
23	Microfoane Radio -Supercardioid 120 dB dynamic range Audio signal: 24 bit / 48 kHz AES-256 encryption for tap-proof transmission 22 compatible channels in an 8 MHz TV band Switchable transmission power 1/10 mW 9.5" metal receiver Detachable BNC antennas Ethernet port for system monitoring and configuration Frequency transmission via infrared interface Output: XLR/jack Frequency band: H51 (534 - 598 MHz)	4	Da	Nu
24	Mixer Digital, 96 canale cu 2 stage rack	1	Da	Nu
25	Cabluri de semnal si putere pentru conectarea tuturor surselor – 1 set	1	Da	Nu
26	Lumini: Capuri Mobile - 3IN1 moving head light Light Source:YODN 350W 17R or OSRAM Siruis HRI 350W,8000K,1500Hrs Optics:exclusive YILONG Optical Lens Color System:14colors+open,dual positions rainbow effect Gobo:16 fixed gobos+open,high speed and shaking effect Strobe:0-13f/s,having online strobe Prism&prism rotating:3prismt,8prism,trapezoid prism Focus:linear-electrical focus Dimmer/atomized:0 -100% linear adjustment and atomize Pan scan:540°(16bit) Tilt scan: 270°(16bit) Channel:16CHs/14CHs(TWO Modes option) LCD Display,DMX 3pin or 5pin signal Input	36	Da	Nu
27	NX Wing is the complementary USB control surface to Obsidian Control Systems ONYX platform. Based on the NX 2 console the NX Wing utilizes the same rugged design and components with an identical footprint and layout.	1	Da	Nu

28	Ecran LED cu suprafata totală de 31.5 m2, 7m x 4.5m. Pich 3,9.	1	Da	Nu
29	Mediaserver - Resolume Arena software is the world's most used VJ software with Touring DJ's and big festivals.	1	Da	Nu
30	Construcții din metal în forma literei "II", lungime 12 m si h 8 m pentru -suspendarea luminilor difuze;	1	Da	Nu
31	Grille din aluminiu lung 10m	2	Da	Nu

Semnat: **electronic**

Nume: **Emilian Dzugas**

Funcția în cadrul firmei: **Director**

Denumirea firmei: **IM "TATRA-BIS" SRL**